

# Servo motor EMMS-AS-70-M-HS-RSB-S1

Part number: 1550990

**FESTO**



## Data sheet

| Feature                                    | Value                                                      |
|--------------------------------------------|------------------------------------------------------------|
| Number of pole pairs                       | 4                                                          |
| Type code                                  | EMMS-AS                                                    |
| Rotor position sensor                      | Absolute encoder, single-turn                              |
| Rotor position sensor interface            | EnDat® 22                                                  |
| Rotor position sensor measuring principle  | Inductive                                                  |
| Temperature monitoring                     | PTC resistor                                               |
| Max. rotational speed                      | 4960 1/min                                                 |
| Nominal rotary speed                       | 4400 1/min                                                 |
| Brake DC operating voltage                 | 24 V                                                       |
| Insulation protection class                | F                                                          |
| Brake power consumption                    | 11 W                                                       |
| Motor constants                            | 1.333 Nm/A                                                 |
| Nominal operating voltage DC               | 565 V                                                      |
| Motor nominal power                        | 1044 W                                                     |
| DC nominal voltage                         | 565 V                                                      |
| Motor nominal current                      | 1.7 A                                                      |
| Rotor position sensor resolution           | 18 bit                                                     |
| Phase-phase winding resistance             | 16.294 Ohm                                                 |
| Winding inductance phase-phase             | 30.834 mH                                                  |
| Type of winding switch                     | Star inside                                                |
| Peak current                               | 7.4 A                                                      |
| Voltage constant, phase-to-phase           | 80.49 mVmin                                                |
| Rating class according to EN 60034-1       | S1                                                         |
| CE marking (see declaration of conformity) | As per EU EMC directive<br>As per EU low voltage directive |
| Corrosion resistance class (CRC)           | 2 - Moderate corrosion stress                              |
| Storage temperature                        | -20 °C ... 60 °C                                           |
| Relative air humidity                      | 0 - 90 %                                                   |
| Degree of protection                       | IP65                                                       |
| Ambient temperature                        | -10 °C ... 40 °C                                           |
| Certification                              | RCM compliance mark<br>c UL us - Recognized (OL)           |
| Total output inertia moment                | 0.68 kgcm <sup>2</sup>                                     |
| Brake holding torque                       | 2 Nm                                                       |
| Brake mass moment of inertia               | 0.07 kgcm <sup>2</sup>                                     |
| Nominal torque                             | 2.26 Nm                                                    |

| Feature                          | Value                                                        |
|----------------------------------|--------------------------------------------------------------|
| Peak torque                      | 8.55 Nm                                                      |
| Stall torque                     | 2.53 Nm                                                      |
| Permissible axial shaft load     | 75 N                                                         |
| Permissible radial shaft load    | 200 N                                                        |
| MTTF, subcomponent               | 76 years, rotor position sensor<br>1769 years, holding brake |
| MTTFd, subcomponent              | 152 years, rotor position sensor                             |
| Switching cycles, holding brake  | 10 million idle actuations (without friction work!)          |
| Product weight                   | 2900 g                                                       |
| Electrical connection technology | Plug                                                         |
| Note on materials                | RoHS-compliant                                               |
| Conforms to standard             | IEC 60034                                                    |