

Printed-circuit board connector - CCV 2,5/ 4-GF-LR P20THRR56 - 1837611

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

PCB headers, nominal current: 12 A, rated voltage (III/2): 320 V, number of positions: 4, pitch: 5 mm, color: black, contact surface: Tin, mounting: THR soldering



The figure shows an 10-position version

Why buy this product

- Designed for integration into the SMT soldering process
- Maximum flexibility when it comes to device design – one header for connectors with different connection technologies
- Screwable flange for superior mechanical stability
- Automatic locking and intuitive release through Lock and Release operating lever in contrasting color



Key Commercial Data

| | |
|------------------------|---------------|
| Packing unit | 330 STK |
| Minimum order quantity | 330 STK |
| GTIN | |
| GTIN | 4055626024219 |

Technical data

Dimensions

| | |
|--------------------------|----------|
| Length [l] | 8.6 mm |
| Width | 30 mm |
| Pitch | 5 mm |
| Dimension a | 15 mm |
| Width [w] | 30 mm |
| Height [h] | 14 mm |
| Constructional height | 12 mm |
| Length of the solder pin | 2 mm |
| Pin dimensions | 1 x 1 mm |

Printed-circuit board connector - CCV 2,5/ 4-GF-LR P20THRR56 - 1837611

Technical data

Dimensions

| | |
|--------|--------|
| Length | 8.6 mm |
|--------|--------|

General

| | |
|--|------------------|
| Range of articles | CCV 2,5/..-GF-LR |
| Insulating material group | IIIa |
| Rated surge voltage (III/3) | 4 kV |
| Rated surge voltage (III/2) | 4 kV |
| Rated surge voltage (II/2) | 4 kV |
| Rated voltage (III/2) | 320 V |
| Rated voltage (II/2) | 400 V |
| Connection in acc. with standard | EN-VDE |
| Nominal current I _N | 12 A |
| Insulating material | LCP |
| Flammability rating according to UL 94 | V0 |
| Color | black |
| Number of positions | 4 |

Packaging information

| | |
|-----------------------------|-----------------|
| Type of packaging | 56 mm wide tape |
| Pieces per package | 330 |
| Denomination packing units | Pcs. |
| [W] tape width | 56 mm |
| [A] coil diameter | 330 mm |
| [W2] coil overall dimension | 62.4 mm |
| Outer packaging type | Transparent-Bag |

Standards and Regulations

| | |
|--|--------|
| Connection in acc. with standard | EN-VDE |
| Flammability rating according to UL 94 | V0 |

Environmental Product Compliance

| | |
|------------|---|
| China RoHS | Environmentally Friendly Use Period = 50 |
| | For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration" |

Approvals

Approvals

Approvals


cULus Recognized

Printed-circuit board connector - CCV 2,5/ 4-GF-LR P20THRR56 - 1837611

Approvals

Ex Approvals

Approval details

| | | | |
|--------------------|---|---|-----------------|
| cULus Recognized |  | http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm | E60425-19931011 |
| | D | B | |
| Nominal voltage UN | 300 V | 300 V | |
| Nominal current IN | 10 A | 16 A | |

Phoenix Contact 2018 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>