


Customer Information Sheet


DRAWING No.: M80-704XXXX	SHEET 2 OF 2	IF IN DOUBT - ASK	©	NOT TO SCALE	THIRD ANGLE PROJECTION	ALL DIMENSIONS IN mm







RECOMMENDED PCB LAYOUT



SPECIFICATION:
MATERIAL:
MOULDING = POLYAMIDE 46 UL94V-0, BLACK
CONTACT CLIP = BERYLLIUM COPPER
CONTACT BODY = COPPER ALLOY
JACKSCREWS & CIRCLIP = STAINLESS STEEL
FINISH (ALL OVER NICKEL):
01 = 4µ TIN/LEAD BODY, 0.30µ GOLD CLIP
05 = 0.28µ GOLD BODY, 0.30µ GOLD CLIP
42 = 4µ 100% TIN BODY, 0.30µ GOLD CLIP
ELECTRICAL:
CURRENT RATING AT 25°C = 3.0A MAX
CURRENT RATING AT 85°C = 2.2A MAX
VOLTAGE PROOF = 360V AC/DC
CONTACT RESISTANCE:
INITIAL = 20mΩ MAX
AFTER CONDITIONING = 25mΩ MAX
INSULATION RESISTANCE:
INITIAL = 1000MΩ MIN
AFTER CONDITIONING = 100MΩ MIN
MECHANICAL:
INSERTION FORCE = 2.8N MAX, 1.0N MIN
WITHDRAWAL FORCE = 1.8N MAX, 0.2N MIN
DURABILITY = 500 OPERATIONS
ENVIRONMENTAL:
OPERATING TEMPERATURE = -55°C TO +125°C
PACKING: TRAYS

NOTES:
1. FROM No. 1 POSITION, CONTACTS NUMBERED IN SEQUENCE FROM RIGHT TO LEFT AND FROM BOTTOM ROW TO TOP ROW (SEE ABOVE).
2. FOR COMPLETE SPECIFICATION, SEE COMPONENT SPECIFICATION C017XX (LATEST ISSUE).

ORDER CODE: **M80-704XXXX**

TOTAL No. OF CONTACTS:
27, 36, 45, 51, 63

FINISH:
01 = TIN/LEAD SHELL, GOLD CLIP
05 = GOLD SHELL, GOLD CLIP
42 = 100% TIN SHELL, GOLD CLIP

POTTING WALLS
BLANK = POTTING WALLS REMOVED
A = POTTING WALLS RETAINED

SM	9	15.07.11	11343
NAME	ISS.	DATE	C/NOTE

APPROVED: S. MCCULLAGH
CHECKED: M. G. PLESTED
DRAWN: M.A.TODD
CUSTOMER REF.:
ASSEMBLY DRG:

HARWiN

HARWIN USA
TEL: 603 893 5376
FAX: 603 893 5396
mis@harwin.com

HARWIN Europe (UK)
TEL: 023 9231 4545
FAX: 023 9231 4590
mis@harwin.co.uk

HARWIN Asia
TEL: +65 6 779 4909
FAX: +65 6 779 3868
mis@harwin.com.sg

THIS DRAWING AND ANY INFORMATION OR DESCRIPTIVE MATTER SET OUT HEREON ARE CONFIDENTIAL AND COPYRIGHT PROPERTY OF THE HARWIN GROUP AND MUST NOT BE DISCLOSED, LOANED, COPIED OR USED FOR MANUFACTURING, TENDERING OR FOR ANY OTHER PURPOSE WITHOUT THEIR WRITTEN PERMISSION.

TOLERANCES
X. = ±1mm
X.X = ±0.25mm
X.XX = ±0.10mm
X.XXX = ±0.01mm
ANGLES = ±5°
UNLESS STATED

MATERIAL: SEE ABOVE
FINISH: SEE ABOVE
S/AREA: mm²

TITLE: 3-ROW DATAMATE FEMALE PC TAIL SOCKET ASSEMBLY + JACKSCREWS

DRAWING NUMBER: **M80-704XXXX**

SHT 2 OF 2