


	X	Y
0.75~1.25	30.0+0.1	22.0+0.1
1.25~2.00	30.2+0.1	22.0+0.1
2.00~3.00	30.4+0.1	22.0+0.1



MATERIAL:

Body:Nylon66, UL rated:94V-2 min

Actuator:Nylon66, UL rated:94V-2 min

Terminal:Brass,silver plated

Rating: 40A 125V AC

25A 250V AC

Function:ON-OFF

Protection Grade:IP65

Contact Resistance: 50mΩ Max

Insulation Resistance:100MΩ Min at DC 500V

Dielectric Strength: 2000V/AC 1 minute

Electrical life: 10,000 cycles

Mechanical life :50,000 cycles

Operating Temperature: -20℃~80℃

Safety Approval:



公差 TOLERANCES .X±0.3 .XX±0.15 角度 ANGLE ±1° 单位 DIMENSION UNIT mm.

版本 VERSION A 比例尺 SCALE 1:1 日期 DATE 2021.03.09 品名 TITLE 图号 DRAWING NO

核准 APPROVED BY 核对 CHECKED BY 绘图 DRAWN BY 孙成 R-6-210-W5L-BG220 R-6-210-W5L-BG220_0

版本 VER 变更说明 CHANGE DESCRIPTION 日期 DATE ECN NO.