



SAW Components

SAW Rx Filter

GSM 900

Series/Type:	B9423
Ordering code:	B39941B9423K610
Date:	March 17, 2006
Version:	2.0



SAW Components

B9423

Low-Loss Filter for Mobile Communication

942.5 MHz

Data sheet




Application

- Low-loss RF filter for mobile telephone
GSM 900 systems, receive path (RX)
- Impedance transform from $50\ \Omega$ to $100\ \Omega$
- Unbalanced to balanced operation
- Very low insertion attenuation
- Low amplitude ripple
- Usable passband 35 MHz
- Suitable for GPRS class 1 to 12




Features

- Package size $1.4 \times 1.1 \times 0.4\ \text{mm}^3$
- Package code QCS5F
- RoHS compatible
- Approx. weight 0.003 g
- Package for Surface Mount Technology (SMT)
- Ni, gold-plated terminals
- Electrostatic Sensitive Device (ESD)



Pin configuration

- 1 Input, unbalanced
- 3,4 Output balanced
- 2,5 To be grounded





SAW Components

B9423

Low-Loss Filter for Mobile Communication

942.5 MHz

Data sheet



Characteristics

Operating temperature range:	T	=	-10 to +85 °C
Terminating source impedance:	Z_S	=	50 Ω
Terminating load impedance:	Z_L	=	100 Ω (balanced)

				B9423			
				min.	typ. @ 25°C	max.	
Center frequency	f_C			—	942.5	—	MHz
Maximum insertion attenuation	$\alpha_{\max}$			—	1.9	2.6	dB
925.0 ... 960.0 MHz				—	1.9	2.6	dB
Amplitude ripple (p-p)	$\Delta\alpha$			—	1.0	1.6	dB
925.0 ... 960.0 MHz				—	1.0	1.6	dB
Input VSWR				—	1.9	2.2	
925.0 ... 960.0 MHz				—	1.9	2.2	
Output VSWR				—	1.8	2.2	
925.0 ... 960.0 MHz				—	1.8	2.2	
Common mode suppression	S_{cs21}						
925.0 ... 960.0 MHz				20	27	—	dB
824.0 ... 995.0 MHz				20	24	—	dB
1648.0 ... 1990.0 MHz				20	48	—	dB
3296.0 ... 3980.0 MHz				20	33	—	dB
Attenuation	α						
0.3 ... 480.0 MHz				45	56	—	dB
480.0 ... 880.0 MHz				30	33	—	dB
880.0 ... 905.0 MHz				23	35	—	dB
905.0 ... 915.0 MHz				18	29	—	dB
980.0 ... 1850.0 MHz				23	29	—	dB
1850.0 ... 1920.0 MHz				30	48	—	dB
1920.0 ... 2400.0 MHz				25	44	—	dB
2400.0 ... 2500.0 MHz				40	44	—	dB
2500.0 ... 5150.0 MHz				30	42	—	dB
5150.0 ... 5825.0 MHz				40	45	—	dB
5825.0 ... 6000.0 MHz				30	45	—	dB
6000.0 ... 12750.0 MHz				—	—	—	dB



SAW Components		B9423
Low-Loss Filter for Mobile Communication		942.5 MHz
Data sheet	SMD	

Maximum ratings

Operable temperature range	T	-30/+85	°C	
Storage temperature range	T _{stg}	-40/+85	°C	
DC voltage	V _{DC}	5	V	
ESD voltage	V _{ESD}	100 ¹⁾	V	machine model, 10 pulses
Input Power at				
GSM850, GSM900	P _{IN}	15	dBm	effective power in the on-state duty cycle 4:8
GSM1800, GSM1900	P _{IN}	15	dBm	
Tx bands				

¹⁾ acc. to JESD22-A115A (machine model), 10 negative & 10 positive pulses.



SAW Components

B9423


Low-Loss Filter for Mobile Communication

942.5 MHz


Data sheet



Transfer function (passband)



Transfer function



Please read *cautions and warnings* and *important notes* at the end of this document.



SAW Components

B9423

Low-Loss Filter for Mobile Communication



942.5 MHz

Data sheet





Smith chart / VSWR

S_{11} function



S_{22} function



Please read *cautions and warnings* and *important notes* at the end of this document.

**SAW Components****B9423****Low-Loss Filter for Mobile Communication****942.5 MHz**

Data sheet

**References**

Type	B9423
Ordering code	B39941B9423K610
Marking and package	C61157-A8-A1
Packaging	F61074-V8212-Z000
Date codes	L_1126
S-parameters	B9423_NB.s3p B9423_WB.s3p
Soldering profile	S_6001
RoHS compatible	defined as compatible with the following documents: "DIRECTIVE 2002/95/EC OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 27 January 2003 on the restriction of the use of certain hazardous substances in electrical and electronic equipment. 2005/618/EC from April 18th, 2005, amending Directive 2002/95/EC of the European Parliament and of the Council for the purposes of establishing the maximum concentration values for certain hazardous substances in electrical and electronic equipment."

For further information please contact your local EPCOS sales office or visit our webpage at www.epcos.com.

Published by EPCOS AG

Surface Acoustic Wave Components Division

P.O. Box 80 17 09, 81617 Munich, GERMANY

© EPCOS AG 2006. This brochure replaces the previous edition.

For questions on technology, prices and delivery please contact the Sales Offices of EPCOS AG or the international Representatives.

Due to technical requirements components may contain dangerous substances. For information on the type in question please also contact one of our Sales Offices.

Please read *cautions and warnings and important notes* at the end of this document.



Important notes

The following applies to all products named in this publication:

1. Some parts of this publication contain **statements about the suitability of our products for certain areas of application**. These statements are based on our knowledge of typical requirements that are often placed on our products in the areas of application concerned. We nevertheless expressly point out **that such statements cannot be regarded as binding statements about the suitability of our products for a particular customer application**. As a rule, EPCOS is either unfamiliar with individual customer applications or less familiar with them than the customers themselves. For these reasons, it is always ultimately incumbent on the customer to check and decide whether an EPCOS product with the properties described in the product specification is suitable for use in a particular customer application.
2. We also point out that **in individual cases, a malfunction of passive electronic components or failure before the end of their usual service life cannot be completely ruled out in the current state of the art, even if they are operated as specified**. In customer applications requiring a very high level of operational safety and especially in customer applications in which the malfunction or failure of a passive electronic component could endanger human life or health (e.g. in accident prevention or life-saving systems), it must therefore be ensured by means of suitable design of the customer application or other action taken by the customer (e.g. installation of protective circuitry or redundancy) that no injury or damage is sustained by third parties in the event of malfunction or failure of a passive electronic component.
3. The warnings, cautions and product-specific notes must be observed.
4. In order to satisfy certain technical requirements, **some of the products described in this publication may contain substances subject to restrictions in certain jurisdictions (e.g. because they are classed as "hazardous")**. Useful information on this will be found in our Material Data Sheets on the Internet (www.epcos.com/material). Should you have any more detailed questions, please contact our sales offices.
5. We constantly strive to improve our products. Consequently, **the products described in this publication may change from time to time**. The same is true of the corresponding product specifications. Please check therefore to what extent product descriptions and specifications contained in this publication are still applicable before or when you place an order. We also **reserve the right to discontinue production and delivery of products**. Consequently, we cannot guarantee that all products named in this publication will always be available.
6. Unless otherwise agreed in individual contracts, **all orders are subject to the current version of the "General Terms of Delivery for Products and Services in the Electrical Industry" published by the German Electrical and Electronics Industry Association (ZVEI)**.
7. The trade names EPCOS, CeraDiode, CSSP, PhaseCap, PhaseMod, SIFI, SIKOREL, Silver-Cap, SIMID, SIOV, SIP5D, SIP5K, TOPcap, UltraCap, WindCap are **trademarks registered or pending** in Europe and in other countries. Further information will be found on the Internet at www.epcos.com/trademarks.