

# Product data sheet

## Characteristics

# 8910DPA73V06

Contactor, Definite Purpose, 75A, 3 pole, 40 HP at 575 VAC, 3 phase, 440/480 VAC 50/60 Hz coil, open

Product availability : Non-Stock - Not normally stocked in distribution facility



Price\* : 318.00 USD



### Main

Product or component type	Definite Purpose Contactor
Line Rated Current	75 A
Number of Poles	3P
Pole contact composition	3 NO
Range of product	DPA

### Complementary

Maximum Horse Power Rating	5 hp 115 V AC, 1 phase 15 hp 230 V AC, 1 phase 25 hp 230 V AC, 3 phase 40 hp 460 V AC, 3 phase 40 hp 575 V AC, 3 phase
Locked rotor rated current	450 A 277 V AC 375 A 460 V AC 300 A 575 V AC
[Ue] rated operational voltage	600 V AC
[Uc] control circuit voltage	440 V AC 50 Hz 480 V AC 60 Hz
Phase	3 phase
Electrical connection	Quick connect terminals Box lugs

### Environment

Product certifications	UL Recognized CSA
------------------------	----------------------

\* Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

## Ordering and shipping details

Category	21347 - 8910 DPA 7_(70 AMP)
Discount Schedule	CP1B
GTIN	00785901177333
Nbr. of units in pkg.	1
Package weight(Lbs)	3.78 lb(US) (1.71 kg)
Returnability	No
Country of origin	CN

## Packing Units

Package 1 Height	5.70 in (14.478 cm)
Package 1 width	5.50 in (13.970 cm)
Package 1 Length	7.20 in (18.288 cm)

## Offer Sustainability

REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information.

## Contractual warranty

Warranty	18 months
----------	-----------