
SPECIFICATIONS

Rated: 15 Amps

Terminal: 0.81 thick Brass, Tin Plate

METRIC - "SNAP-IN" PC SCREW TERMINALS

Binding Head Screw: Brass,



M3 x 6.35 L SCREW

> Mounting Detail **→** 5.00 **⊢** 0 Ó 7.00 0

> > 1.85 DIA. (4) PLS

CAT. NO. 7788 (Supplied Less Screw) М3 VERTICAL

437 [11.1]

CAT. NO. 7698 (Screw Supplied Unassembled) CAT. NO. 7696 (Screw Installed & Captivated)

NOTE: All dimensions are in millimeters

LOW PROFILE SCREW TERMINALS

These sturdy, low cost screw terminals, feature an anti-rotation tab for use with spade terminals. They are available with the screw installed and captivated, the screw unassembled or without a screw.


PRINCIPLE FEATURES

7.90

- · Easy to connect using solid or stranded wire, crimp lugs or terminals
- Anti-rotation tab for use with spade terminals
- Supplied with screw installed and captivated, with screw unassembled, or without screw
- · Stainless steel screw will not wick



10-32



M3 x 6.35 l

7.10

SCREW

- 11.50

М3

HORIZONTAL

SPECIFICATIONS

6-32

Rated: 15 Amps


SCREW TERMINALS

Terminal: .032 (.81) thick Brass, Tin Plate Screw: Combination drive. Stainless Steel

CAT. NO. 1284 (Supplied Less Screw)

CAT. NO. 1298 (Screw Supplied Unassembled)


CAT. NO. 1201 (Screw Installed & Captivated)



Screw: Combination drive. Stainless Steel

CAT. NO. 1293 (Supplied Less Screw)

CAT. NO. 1299 (Screw Supplied Unassembled) CAT. NO. 1202 (Screw Installed & Captivated)



HEAVY DUTY SCREW TERMINALS

These heavy duty terminals are available with the screw installed or unassembled, and feature easy access to connect solid or stranded wire, crimp type lugs or terminals.

PRINCIPLE FEATURES

∠.₁₈₇ [4.7] DIA.


- · Anti-rotation tab for use with spade terminals
- Below the board notched leg, to facilitate mechanical and solder connections
- Easy to connect using solid or stranded wire, crimp lugs or terminals
- Available with screw installed, unassembled, or without screw



10-32



8-32





SPECIFICATIONS Rated: 15 Amps Terminal: .064 (1.6)

thick Brass, Tin Plate Screw: Brass, Nickel Plate

CAT. NO. 1205 (Supplied Less Screw) CAT. NO. 1207 (Screw Supplied Unassembled)

CAT. NO. 1209 (Screw Installed)






SPECIFICATIONS Rated: 30 Amps

Terminal: .064 (1.6) thick Brass, Tin Plate

Screw: Steel, Nickel Plate

CAT. NO. 1206 (Supplied Less Screw) CAT. NO. 1208 (Screw Supplied Unassembled) CAT. NO. 1283 (Screw Installed)



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Keystone Electronics:

<u>7695</u> <u>7689</u> <u>7790</u>