


Technical Data

ST41xx Series



Description

A crystal controlled, low-current oscillator providing precise rise and fall times to drive AC MOS/LVCMOS loads. The tri-state function enables the output to go high impedance. Available in either a 14 or an 8 pin DIP compatible, resistance welded, all metal case. Pin 7 (or Pin 4) is grounded to case to reduce EMI. True SMD DIL 14 version also available, utilizing new adaptor technology (see separate data sheet for package dimensions).

Applications & Features

- Fiber Channel
- Gigabit Ethernet
- HCMOS/AC MOS/LVCMOS MPU's
- 3.3 or 5V operation
- High Drive capability
- Tri-State output standard
- Short circuit protected output
- Plastic SMD available, see ST41xH Series data sheet.
- Ceramic SMD available, see S19xx Series data sheet.
- True SMD version available, select option S in part number builder (see separate data sheet for package dimensions).

Frequency Range:	32 MHz to 125 MHz			
Frequency Stability:	±20, ±25, ±50 or ±100 ppm over all conditions: calibration tolerance, operating temperature, input voltage change, load change, aging*, shock and vibration. *1 year @ +40°C average ambient operating temperature			
Temperature Range:	Operating: 0 to +70°C or -40 to +85°C Storage: -55 to +125°C			
Supply Voltage:	Recommended Operating: +5V ±5% or 3.3V ±10%			
Supply Current:	50mA typ, 65mA, 35mA max @ 3.3V			
Output Drive:	Symmetry: AC MOS AC MOS TTL TTL 32 to 60 MHz 60+ to 125 MHz 32 to 60 MHz 60+ to 125 MHz 0 to +70°C: 45/55% 45/55% 45/55% 45/55% -40 to +85°C: 45/55% 40/60% 45/55% 40/60% (45/55% @ 3.3V) Rise & Fall Times: 2ns max 20% to 80% VDD 1.5ns max 0.5 to 2.5V Logic 0: 10% VDD max or 20% VDD max @ 3.3V Logic 1: 80% VDD min or 80% VDD min @ 3.3V Load: 50Ω AC MOS or 95Ω AC MOS @ 3.3V Period Jitter RMS: 13ps max 32 to 72 MHz 20ps max 72+ to 125 MHz, 0 to +70°C 25ps max 72+ to 125 MHz, -40 to +85°C			

Mechanical:

Shock:	MIL-STD-883, Method 2002, Condition B
Solderability:	MIL-STD-883, Method 2003
Terminal Strength:	MIL-STD-883, Method 2004, Condition B2
Vibration:	MIL-STD-883, Method 2007, Condition A
Solvent Resistance:	MIL-STD-202, Method 215
Resistance to Soldering Heat:	MIL-STD-202, Method 210, Condition A, B or C (I or J for Gull Wing or SMD)

Environmental:

Gross Leak Test:	MIL-STD-883, Method 1014, Condition C
Fine Leak Test:	MIL-STD-883, Method 1014, Condition A2
Thermal Shock:	MIL-STD-883, Method 1011, Condition A
Moisture Resistance:	MIL-STD-883, Method 1004

Part Numbering Guide

Series	ST41	3	0	A	106.2500	(T)
Type						
3 = 3.3V LVCMOS						
5 = 5V TTL						
6 = 5V AC MOS						
Package Style						
0 = Full Size, Metal						
9 = Half Size, Metal						
J = Half Size, Metal, Gull Wing						
K = Full Size, Metal, Gull Wing						
S = True SMD Adaptor (see product photo)						
Stability Tolerance						
AA = ±20 ppm, 0 to +70°C						
A = ±25 ppm, 0 to +70°C						
B = ±50 ppm, 0 to +70°C						
C = ±100 ppm, 0 to +70°C						
E = ±50 ppm, -40 to +85°C						
F = ±100 ppm, -40 to +85°C						
Packing Method						
(T) = Tape & Reel for SMD versions full reel increments only (200pcs)						
Blank = Bulk						
Frequency						

ST41xx Series

Tri-State Logic Table

True SMD Adaptor - 7.57mm High

Technical Data

