Molding Type Module IGBT, 2-in-1 Package, 600 V and 200 A



Double INT-A-PAK

FEATURES

- High short circuit capability
- 10 µs short circuit capability
- $V_{CE(on)}$ with positive temperature coefficient
- Maximum junction temperature 150 °C
- Latch-up free
- Low inductance case
- Fast and soft reverse recovery antiparallel FWD
- Isolated copper baseplate using DCB (Direct Copper Bonding) technology
- Material categorization: for definitions of compliance please see www.vishay.com/doc?99912

RoHS COMPLIANT

PRODUCT SUMMARY	
V_{CES}	600 V
I_C at T_C = 80 °C	200 A
$V_{CE(on)}$ (typical) at I_C = 200 A, 25 °C	1.9 V
Speed	DC to 1 kHz
Package	Double INT-A-PAK
Circuit	Half bridge

TYPICAL APPLICATIONS

- UPS
- Switching mode power supplies
- Electronic welders

DESCRIPTION

Vishay's IGBT power module provides ultra low conduction loss as well as short circuit ruggedness. It is designed for applications such as general UPS and SMPS.

ABSOLUTE MAXIMUM RATINGS (T_C = 25 °C unless otherwise noted)

PARAMETER	SYMBOL	TEST CONDITIONS	MAX.	UNITS
Collector to emitter voltage	V_{CES}		600	V
Gate to emitter voltage	V_{GES}		± 20	
Collector current	I_C	T_C = 25 °C	260	A
		T_C = 80 °C	200	
Pulsed collector current	I_{CM} (1)	t_p = 1 ms	400	
Diode continuous forward current	I_F	T_C = 80 °C	200	
Diode maximum forward current	I_{FM}	t_p = 1 ms	400	
Maximum power dissipation	P_D	T_J = 150 °C	1042	W
Short circuit withstand time	t_{SC}	T_C = 125 °C	10	µs
RMS isolation voltage	V_{ISOL}	f = 50 Hz, t = 1 min	2500	V
I^2t-value, diode	I^2t	V_R= 0 V, t = 10 ms, T_J = 125 °C	4900	A^2s

Note

(1) Repetitive rating: pulse width limited by maximum junction temperature.

For technical questions within your region: DiodesAmericas@vishay.com, DiodesAsia@vishay.com, DiodesEurope@vishay.com

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000

IGBT ELECTRICAL SPECIFICATIONS (T_C = 25 °C unless otherwise noted)						
PARAMETER	**SYMBOL**	**TEST CONDITIONS**	**MIN.**	**TYP.**	**MAX.**	**UNITS**
Collector to emitter breakdown voltage	$V_{(BR)CES}$	T_J = 25 °C	600	-	-	V
Collector to emitter voltage	$V_{CE(on)}$	V_{GE} = 15 V, I_C = 200 A, T_J = 25 °C	-	1.9	-	
		V_{GE} = 15 V, I_C = 200 A, T_J = 125 °C	-	2.3	-	
Gate to emitter threshold voltage	$V_{GE(th)}$	V_{CE} = V_{GE}, I_C = 0.25 mA, T_J = 25 °C	3.5	4.5	5.5	
Collector cut-off current	I_{CES}	V_{CE} = V_{CES}, V_{GE} = 0 V, T_J = 25 °C	-	-	5.0	µA
Gate to emitter leakage current	I_{GES}	V_{GE} = V_{GES}, V_{CE} = 0 V, T_J = 25 °C	-	-	400	nA

SWITCHING CHARACTERISTICS						
PARAMETER	**SYMBOL**	**TEST CONDITIONS**	**MIN.**	**TYP.**	**MAX.**	**UNITS**
Turn-on delay time	$t_{d(on)}$	V_{CC} = 300 V, I_C = 200 A, R_g = 4.7 Ω, V_{GE} = ± 15 V, T_J = 25 °C	-	106	-	ns
Rise time	t_r		-	45	-	
Turn-off delay time	$t_{d(off)}$		-	460	-	
Fall time	t_f		-	51	-	
Turn-on switching loss	E_{on}		-	4.2	-	mJ
Turn-off switching loss	E_{off}		-	9.0	-	
Turn-on delay time	$t_{d(on)}$	V_{CC} = 300 V, I_C = 200 A, R_g = 4.7 Ω, V_{GE} = ± 15 V, T_J = 125 °C	-	120	-	ns
Rise time	t_r		-	68	-	
Turn-off delay time	$t_{d(off)}$		-	510	-	
Fall time	t_f		-	70	-	
Turn-on switching loss	E_{on}		-	5.1	-	mJ
Turn-off switching loss	E_{off}		-	11.3	-	
Input capacitance	C_{ies}	V_{GE} = 0 V, V_{CE} = 25 V, f = 1.0 MHz	-	13.1	-	nF
Output capacitance	C_{oes}		-	0.71	-	
Reverse transfer capacitance	C_{res}		-	0.38	-	
SC data	I_{SC}	t_{sc} ≤ 10 µs, V_{GE} = 15 V, T_J = 125 °C, V_{CC} = 300 V, V_{CEM} ≤ 600 V	-	650	-	A
Stray inductance	L_{CE}		-	-	20	nH
Module lead resistance, terminal to chip	$R_{CC'+EE'}$	T_C = 25 °C	-	0.35	-	mΩ

DIODE ELECTRICAL SPECIFICATIONS (T_C = 25 °C unless otherwise noted)							
PARAMETER	**SYMBOL**	**TEST CONDITIONS**		**MIN.**	**TYP.**	**MAX.**	**UNITS**
Diode forward voltage	V_F	I_F = 200 A	T_J = 25 °C	-	1.4	1.6	V
			T_J = 125 °C	-	1.6	1.8	
Diode reverse recovery charge	Q_{rr}	I_F = 200 A, V_R = 300 V, dI/dt = -6000 A/µs, V_{GE} = -15 V	T_J = 25 °C	-	9	-	µC
			T_J = 125 °C	-	16	-	
Diode peak reverse recovery current	I_{rr}		T_J = 25 °C	-	140	-	A
			T_J = 125 °C	-	165	-	
Diode reverse recovery energy	E_{rec}		T_J = 25 °C	-	2.4	-	mJ
			T_J = 125 °C	-	4.2	-	

For technical questions within your region: DiodesAmericas@vishay.com, DiodesAsia@vishay.com, DiodesEurope@vishay.com
THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000

THERMAL AND MECHANICAL SPECIFICATIONS							
PARAMETER		**SYMBOL**	**TEST CONDITIONS**	**MIN.**	**TYP.**	**MAX.**	**UNITS**
Operating junction temperature range		T_J		-40	-	150	°C
Storage temperature range		T_{STG}		-40	-	125	
Junction to case	IGBT	R_{thJC}		-	-	0.12	K/W
	Diode			-	-	0.27	
Case to sink		R_{thCS}	Conductive grease applied	-	0.03	-	
Mounting torque			Power terminal screw: M6	2.5 to 5.0			Nm
			Mounting screw: M6	3.0 to 6.0			
Weight				325			g




Fig. 1 - Typical Output Characteristics




Fig. 3 - Switching Loss vs. Collector Current




Fig. 2 - Typical Transfer Characteristics




Fig. 4 - Switching Loss vs. Gate Resistor

For technical questions within your region: DiodesAmericas@vishay.com, DiodesAsia@vishay.com, DiodesEurope@vishay.com
THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000




Fig. 5 - Gate Charge Characteristics




Fig. 7 - Switching Times vs. I_C




Fig. 6 - Typical Capacitance vs. Collector to Emitter Voltage




Fig. 8 - Typical Switching Times vs. Gate Resistance R_g




Fig. 9 - Diode Typical Forward Characteristics

For technical questions within your region: DiodesAmericas@vishay.com, DiodesAsia@vishay.com, DiodesEurope@vishay.com
THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000





Fig. 10 - Diode Transient Thermal Impedance

CIRCUIT CONFIGURATION




LINKS TO RELATED DOCUMENTS	
Dimensions	www.vishay.com/doc?95525

For technical questions within your region: DiodesAmericas@vishay.com, DiodesAsia@vishay.com, DiodesEurope@vishay.com
THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000

Double INT-A-PAK

DIMENSIONS in millimeters (inches)



For technical questions within your region: DiodesAmericas@vishay.com, DiodesAsia@vishay.com, DiodesEurope@vishay.com

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000

Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, “Vishay”), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay’s knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer’s responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer’s technical experts. Product specifications do not expand or otherwise modify Vishay’s terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.