
www.eicsemi.com

AR3500S - AR3510S

AUTOMOTIVE RECTIFIER DIODES

PRV : 50 - 1000 Volts
Io : 35 Amperes



FEATURES :

* High current capability
* High surge current capability
* High reliability
* Low reverse current
* Low forward voltage drop
* Pb / RoHS Free

MECHANICAL DATA :

* Case : Molded plastic
* Epoxy : UL94V-O rate flame retardant
* Lead : Axial lead solderable per MIL-STD-202, Method 208 guaranteed
* Polarity : Cathode to lead, For anode to lead use "R" suffix.
* Mounting position : Any
* Weight : 2.29 grams

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Rating at 25 °C ambient temperature unless otherwise specified.
Single phase, half wave, 60 Hz, resistive or inductive load.
For capacitive load, derate current by 20%.

RATING	SYMBOL	AR 3500	AR 3501S	AR 3502S	AR 3504S	AR 3506S	AR 3508S	AR 3510S	UNIT
Maximum Repetitive Peak Reverse Voltage	V_{RRM}	50	100	200	400	600	800	1000	V
Maximum RMS Voltage	V_{RMS}	35	70	140	280	420	560	700	V
Maximum DC Blocking Voltage	V_{DC}	50	100	200	400	600	800	1000	V
Average Rectified Forward Current Tc = 150°C	$I_{F(AV)}$	35							A
Peak Forward Surge Current Single half sine wave superimposed on rated load (JEDEC Method)	I_{FSM}	400							A
Maximum Forward Voltage at I_F = 35 Amps.	V_F	1.1							V
Maximum DC Reverse Current Ta = 25 °C	I_R	5.0							µA
at rated DC Blocking Voltage Ta = 100 °C	$I_{R(H)}$	1.0							mA
Thermal Resistance (Note 1)	RθJC	1.0							°C/W
Junction Temperature Range	T_J	- 65 to + 175							°C
Storage Temperature Range	T_{STG}	- 65 to + 175							°C

Note : (1) Thermal resistance from junction to case. Single side cooled.

Download from alldatasheet.com

RATING AND CHARACTERISTIC CURVES (AR3500S - AR3510S)

FIG.1 - DERATING CURVE FOR OUTPUT RECTIFIED CURRENT




FIG.2 - MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT




FIG.3 - TYPICAL FORWARD CHARACTERISTICS





FIG.4 - TYPICAL REVERSE CHARACTERISTICS



Download from alldatasheet.com