

Features

- Plastic package has Underwriters Laboratory Flammability Classification 94V-0
- Types up to 1000 V V_{RRM}
- Ideal for printed circuit board
- High surge overload rating
- High temperature soldering guaranteed: 260°C/ 10 seconds, 0.375(9.5mm) lead length
- Glass passivated chip junction
- High case dielectric strength 1500 V_{RMS}

Mechanical Data

Case: Molded plastic body over passivated junctions

Mounting position: Any

Terminals: Plated leads, solderable per MIL-STD-750

Method 2026 guaranteed

GBU Package



Maximum ratings, at $T_J = 25\text{ }^{\circ}\text{C}$, unless otherwise specified

Parameter	Symbol	Conditions	GBU8A	GBU8B	GBU8D	GBU8G	Unit
Repetitive peak reverse voltage	V_{RRM}		50	100	200	400	V
RMS reverse voltage	V_{RMS}		35	70	140	280	V
DC blocking voltage	V_{DC}		50	100	200	400	V
Continuous forward current	I_F	$T_C \leq 100\text{ }^{\circ}\text{C}$	8	8	8	8	A
Surge non-repetitive forward current, Half Sine Wave	I_{FSM}	$T_C = 25\text{ }^{\circ}\text{C}$, $t_p = 8.3\text{ ms}$	200	200	200	200	A
Operating temperature	T_J		-55 to 150	-55 to 150	-55 to 150	-55 to 150	$^{\circ}\text{C}$
Storage temperature	T_{stg}		-55 to 150	-55 to 150	-55 to 150	-55 to 150	$^{\circ}\text{C}$

Electrical characteristics, at $T_J = 25\text{ }^{\circ}\text{C}$, unless otherwise specified

Parameter	Symbol	Conditions	GBU8A	GBU8B	GBU8D	GBU8G	Unit
Diode forward voltage	V_F	$I_F = 8\text{ A}$, $T_J = 25\text{ }^{\circ}\text{C}$	1.1	1.1	1.1	1.1	V
Reverse current	I_R	$V_R = 50\text{ V}$, $T_J = 25\text{ }^{\circ}\text{C}$	5	5	5	5	μA
		$V_R = 50\text{ V}$, $T_J = 125\text{ }^{\circ}\text{C}$	500	500	500	500	


Thermal characteristics

Thermal resistance, junction - case	$R_{\theta JA}$	21.0	21.0	21.0	21.0	$^{\circ}\text{C/W}$
	$R_{\theta JL}$	2.2	2.2	2.2	2.2	




AVERAGE FORWARD OUTPUT CURRENT,
AMPERES

FIG.1-DERIVATIVE CURVE FOR OUTPUT RECTIFIER CURRENT




PEAK FORWARD SURGE CURRENT,
AMPERES

FIG. 2 - MAXIMUM NON-REPETITIVE PEAK
FORWARD SURGE CURRENT PER LEG




INSTANTANEOUS FORWARD CURRENT, AMPERES

FIG.3-TYPICAL FORWARD CHARACTERISTICS PER LEG




INSTANTANEOUS REVERSE CURRENT, MICROAMPERES

FIG.4-TYPICAL REVERSE CHARACTERISTICS PER LEG



JUNCTION CAPACITANCE, pF

FIG.5-TYPICAL JUNCTION CAPACITANCE PER LEG



TRANSIENT THERMAL IMPEDANCE, °C/W

FIG.6-TYPICAL TRANSIENT THERMAL IMPEDANCE

