
This document was generated on 05/25/2010

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 0887418320
Status: Active
Overview: microcross_dvi
Description: MicroCross™ DVI Digital Visual Interface, Shielded I/O Cable Assembly: DVI-Analog-to-VGA, Black, 5.0m (16.40') Length



Series image - Reference only

Documents:
Drawing (PDF)
RoHS Certificate of Compliance (PDF)

General

Product Family	Cable Assemblies
Series	88744
Connector to Connector	DVI-Analog-to-VGA
Overview	microcross_dvi
Product Name	MicroCross™DVI

Physical

Cable Length	5.0m (16.40')
Circuits (Loaded)	29
Color - Resin	Black, Natural
Gender	Plug/Plug
Lock to Mating Part	None
Material - Metal	Brass
Material - Plating Mating	Gold
Material - Plating Termination	Tin
Material - Resin	Low Density Polyethylene, Polyester
Packaging Type	Bag
Pitch - Mating Interface (in)	0.075 In, 0.100 In
Pitch - Mating Interface (mm)	1.90 mm, 2.54 mm
Plating min: Mating (µin)	10, 2
Plating min: Mating (µm)	0.05, 0.25
Plating min: Termination (µin)	150
Plating min: Termination (µm)	3.75
Single Ended	No
Termination Interface: Style	Solder or Weld
Wire Insulation Diameter	N/A
Wire Size AWG	N/A
Wire/Cable Type	N/A

Electrical

Current - Maximum per Contact	3A
Shielded	Yes

Material Info

Reference - Drawing Numbers

Sales Drawing	SD-88741-004

EU RoHS
ELV and RoHS Compliant
REACH SVHC
Not Reviewed
Halogen-Free Status
Not Reviewed

China RoHS

Need more information on product environmental compliance?

Email productcompliance@molex.com
For a multiple part number RoHS Certificate of Compliance, click here


Please visit the Contact Us section for any non-product compliance questions.

Search Parts in this Series
88744Series

Mates With
74320 MicroCross™ DVI-I Digital/Analog Visual Interface, PCB Receptacle

This document was generated on 05/25/2010

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION



88741-8421	DVI_A-P&D_A ANALOG CABLE ASS'Y 5M PARCHMENT WHT	5000 ± 150 / 196.9 ± 5.9	PARCHMENT WHITE	887808286
88741-8411	DVI_A-P&D_A ANALOG CABLE ASS'Y 3M PARCHMENT WHT	3000 ± 80 / 118.1 ± 3.1	PARCHMENT WHITE	887808286
88741-8401	DVI_A-P&D_A ANALOG CABLE ASS'Y 2M PARCHMENT WHT	2000 ± 60 / 78.7 ± 2.4	PARCHMENT WHITE	887808286
88741-8420	DVI_A-P&D_A ANALOG CABLE ASS'Y 5M BLK	5000 ± 150 / 196.9 ± 5.9	BLACK	887808277
88741-8410	DVI_A-P&D_A ANALOG CABLE ASS'Y 3M BLK	3000 ± 80 / 118.1 ± 3.1	BLACK	887808277
88741-8400	DVI_A-P&D_A ANALOG CABLE ASS'Y 2M BLK	2000 ± 60 / 78.7 ± 2.4	BLACK	887808277
MX P/N	DESCRIPTION	LENGTH	CABLE COLOR	CABLE P/N

CXXX
- WEEK NO. FOR YEAR.
- YEAR NO.
- "C" FOR MOLEX CHINA

DETAIL C

ENTER DESCRIPTION
EC NO: DG2006-0186 2006/03/09
DRWN: PDAI 2006/03/09
CH'KD: 2006/03/10
APPR: TKAN
DESCRIPTION
REV

QUALITY SYMBOLS
▼=0
Ⓒ=0

GENERAL TOLERANCES (UNLESS SPECIFIED)

	mm	INCH
4 PLACES	± ---	± ---
3 PLACES	± ---	± ---
2 PLACES	± ---	± ---
1 PLACE	± ---	± ---
ANGULAR ±---°		

DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS

DIMENSION STYLE: MM/IN
SCALE: ---
DESIGN UNITS: METRIC
THIRD ANGLE PROJECTION

DRAWN BY: PDAI DATE: 2006/03/07
CHECKED BY: ZXDENG DATE: 2006/03/07
APPROVED BY: BORON DATE: 2006/03/07
MATERIAL NO.: SEE TABLE

TITLE: DVI_D-P&D_A ANALOG CBL

MOLEX INCORPORATED

DOCUMENT NO.: SD-88741-005
SHEET NO.: 1 OF 2

SIZE A4

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

NOTE: 1. OVERMOLD SPECIFICATION

1.1 DVI BOOT MOLDED WITH SNOW WHITE PVC RESIN P/N IS 887800076.

1.2 UL94V-0, COLOR: MAD432

1.3 HARDNESS (DUROMETER): SHORE A 90-95

1.4 P&D BOOT MOLDED WITH PVC RESIN P/N IS 887800053.

2. MECHANICAL SPECIFICATION

2.1 CABLE SHOULD STAND THE PULL FORCE 89-111N FOR 30 SECONDS WITH NO VISIBLE TERMINATION DAMAGE.

2.2 CABLE SHOULD PASS THE FLEX TEST IN 100 CYCLES AT EACH OF PLANES, PER EIA 364-41, CONDITION I.

3. CABLE ELECTRICAL SPECIFICATION

3.1 DIELECTRIC STRENGTH: 300VDC FOR 10MS

3.2 SIGNAL LINE INSULATION RESISTANCE: 20 MEGA Ohms

3.3 COAXIAL LINES CHARACTERISTIC IMPEDANCE: 75±7.5 Ohms @TDR.

4. DVI CONNECTOR SPECIFICATION

4.1 REFER TO PRODUCT SPEC. PS74320-0001.

4.2 CONTACT PLATING: AU FLASH.

5. THIS PRODUCT MUST MEET MX RoHS COMPLIANCE.

6. CONNECTION DIAGRAM

SHIELD	SHIEDL	GROUND
C 5	C 5	ANLOG GROUND
C 4	PIN 5	HORIZONTAL SYNC
C 3	C 4	ANLOG
C 2	C 2	ANLOG
C 1	C 1	ANLOG
PIN 16	PIN 16	HOT PLUG DETECT
PIN 15	PIN 4,25	GROUND(+5V & HV SYNC)
PIN 14	PIN 28	POWER +5V
PIN 8	PIN 6	VERTICAL SYNC
PIN 7	PIN 26	DDC DATA
PIN 6	PIN 27	DDC CLOCK
DVI_A	P&D_A	CABLE FUNCTION

7. MATERIAL LIST

ITEM	DESCRIPTION
F	EVC THUMB SCREW(WHITE) 71757 1000
E	EVC BOOT (WHITE) 737840001
D	EVC CONNECTOR 674850011
C	DVI THUMB SCREW 887806005
B	DVI_A G/F CONNECTOR 743230011
A	DVI ANALOG CABLE (SEE TABLE)

ENTER DESCRIPTION
EC NO: DG2006-0186 2006/03/09
DRWN:PDAI 2006/03/09
CH'KD: 2006/03/10
APPR: TKAN
DESCRIPTION
REV

QUALITY SYMBOLS
▼=0
Ⓒ=0

GENERAL TOLERANCES (UNLESS SPECIFIED)

	mm	INCH
4 PLACES	± ---	± ---
3 PLACES	± ---	± ---
2 PLACES	± ---	± ---
1 PLACE	± ---	± ---
ANGULAR ±---°		

DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS

DIMENSION STYLE: MM/IN
SCALE: ---
DESIGN UNITS: METRIC
THIRD ANGLE PROJECTION

DRAWN BY: PDAI DATE: 2006/03/06
CHECKED BY: ZXDENG DATE: 2006/03/06
APPROVED BY: BORON DATE: 2006/03/06

TITLE: DVI_A-P&D_A ANALOG CBL

MOLEX INCORPORATED

MATERIAL NO.: SEE TABLE
DOCUMENT NO.: SD-88741-005
SHEET NO.: 2 OF 2

SIZE: A4

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION