




## Thermoelectric Cooler



MI1025T

### Performance Values

Hot Side Temperature (°C)	27°C	50°C
Δ Tmax (°C-dry N <sub>2</sub> ):	64	73
Qmax (watts):	5.2	5.8
I <sub>max</sub> (amps):	1.8	1.8
V <sub>max</sub> (vdc):	4.4	4.9
AC Resistance (ohms):	2.1	---



### Mechanical Characteristics



### Ordering Options

MI1025T-01	both surfaces are metallized
MI1025T-02	hot side exterior is metallized
MI1025T-03	no metallization



- For example, and MI1025T with only the hot side metallized is specified as an MI1025T-02AC
- Pretinned metallized ceramic surface(s) with 117°C solder.
- Thermistor mounted on edge of cold side ceramic. (Calibration available.)
- Elevated temperature burn-in with test data provided.

## Performance Curves

Environment: One atmosphere dry nitrogen

Hot Side Temperature: 27°C

Hot Side Temperature: 50°C



For performance information in a vacuum or with hot side temperatures other than 27°C or 50°C, consult one of our Applications Engineers.

## Installation

Recommended mounting methods: Bonding with thermal epoxy or soldering with metallized ceramics. For additional information, please refer to our TEC Installation Guide.

## Operation Cautions

For maximum reliability, storage and operation below 85°C in a non-condensing environment is recommended. To minimize thermal stress, use linear/proportional temperature control or a similar method rather than an ON/OFF method.



### Marlow Industries, Inc.

10451 Vista Park Road  
Dallas Texas 75238-1645

TEL: 214-340-4900

FAX: 214-341-5212

Internet: <http://www.marlow.com>

### Marlow Industries Europe

Aberdeen House, South Road  
Haywards Heath

West Sussex RH164NG UK

TEL: +44 (0)1444-443404

FAX: +44 (0)1444-443334

### Marlow Industries Asia

1-1-8-401

Uehara, Shibuya-ku  
Tokyo, Japan 151-0064

TEL: +81 (3) 5454-5280

FAX: +81 (3) 5454-5281