

SKM100GB12T4G



SEMITRANS®3

Fast IGBT4 Modules

SKM100GB12T4G

Features

- IGBT4 = 4. Generation (Trench)IGBT
- VCEsat with positive temperature coefficient
- High short circuit capability, self limiting to 6 x I_{CNOM}
- Soft switching 4. Generation CAL diode (CAL4)

Typical Applications

- AC inverter drives
- UPS
- Electronic welders at fsw up to 20 kHz

Remarks

- Case temperature limited to T_c = 125°C max, recomm. Top = -40 ... +150°C, product rel. results valid for T_j = 150°



GB

Absolute Maximum Ratings				
Symbol	Conditions		Values	Unit
IGBT				
V _{CES}			1200	V
I _C	T _j = 175 °C	T _c = 25 °C	154	A
		T _c = 80 °C	118	A
I _{Cnom}			100	A
I _{CRM}	I _{CRM} = 3xI _{Cnom}		300	A
V _{GES}			-20 ... 20	V
t _{psc}	V _{CC} = 800 V	T _j = 150 °C	10	µs
	V _{GE} ≤ 15 V			
	V _{CES} ≤ 1200 V			
T _j			-40 ... 175	°C
Inverse diode				
I _F	T _j = 175 °C	T _c = 25 °C	118	A
		T _c = 80 °C	89	A
I _{Fnom}			100	A
I _{FRM}	I _{FRM} = 3xI _{Fnom}		300	A
I _{FSM}	t _p = 10 ms, sin 180°, T _j = 25 °C		486	A
T _j			-40 ... 175	°C
Module				
I _{t(RMS)}			500	A
T _{stg}			-40 ... 125	°C
V _{isol}	AC sinus 50Hz, t = 1 min		4000	V

Characteristics						
Symbol	Conditions		min.	typ.	max.	Unit
IGBT						
V _{CE(sat)}	I _C = 100 A	V _{GE} = 15 V chiplevel	T _j = 25 °C	1.85	2.1	V
			T _j = 150 °C	2.2	2.4	V
V _{CE0}			T _j = 25 °C	0.8	0.9	V
			T _j = 150 °C	0.7	0.8	V
r _{CE}	V _{GE} = 15 V		T _j = 25 °C	10.5	12.0	mΩ
			T _j = 150 °C	15.0	16.0	mΩ
V _{GE(th)}	V _{GE} =V _{CE} , I _C = 3.4 mA		5	5.8	6.5	V
I _{CES}	V _{GE} = 0 V	V _{CE} = 1200 V	T _j = 25 °C	0.1	0.3	mA
			T _j = 150 °C			mA
C _{ies}	V _{CE} = 25 V	V _{GE} = 0 V	f = 1 MHz	5.54		nF
C _{oes}			f = 1 MHz	0.41		nF
C _{res}			f = 1 MHz	0.32		nF
Q _G	V _{GE} = - 8 V...+ 15 V			560		nC
R _{Gint}	T _j = 25 °C			2.0		Ω
t _{d(on)}	V _{CC} = 600 V	T _j = 150 °C		167		ns
t _r	I _C = 100 A	V _{GE} = ±15 V	T _j = 150 °C	37		ns
E _{on}	R _{G on} = 1 Ω	T _j = 150 °C		16.1		mJ
t _{d(off)}	R _{G off} = 1 Ω	T _j = 150 °C		380		ns
t _f	di/dt _{on} = 3300 A/µs	T _j = 150 °C		78		ns
E _{off}	di/dt _{off} = 1300 A/µs	T _j = 150 °C		8.6		mJ
R _{th(j-c)}	per IGBT				0.29	K/W



SEMITRANS®3

Fast IGBT4 Modules

SKM100GB12T4G

Features

- IGBT4 = 4. Generation (Trench)IGBT
- VCEsat with positive temperature coefficient
- High short circuit capability, self limiting to $6 \times I_{CNOM}$
- Soft switching 4. Generation CAL diode (CAL4)

Typical Applications

- AC inverter drives
- UPS
- Electronic welders at fsw up to 20 kHz

Remarks

- Case temperature limited to $T_c = 125^\circ\text{C}$ max, recomm.
Top = $-40 \dots +150^\circ\text{C}$, product rel. results valid for $T_j = 150^\circ$

Characteristics						
Symbol	Conditions		min.	typ.	max.	Unit
Inverse diode						
$V_F = V_{EC}$	$I_F = 100 \text{ A}$ $V_{GE} = 0 \text{ V}$ chip	$T_j = 25^\circ\text{C}$		2.22	2.54	V
		$T_j = 150^\circ\text{C}$		2.18	2.5	V
V_{F0}		$T_j = 25^\circ\text{C}$		1.3	1.5	V
		$T_j = 150^\circ\text{C}$		0.9	1.1	V
r_F		$T_j = 25^\circ\text{C}$		9.2	10.4	m Ω
		$T_j = 150^\circ\text{C}$		12.8	14.0	m Ω
I_{RRM}	$I_F = 100 \text{ A}$	$T_j = 150^\circ\text{C}$		47		A
Q_{rr}	$di/dt_{off} = 1600 \text{ A}/\mu\text{s}$	$T_j = 150^\circ\text{C}$		17		μC
E_{rr}	$V_{GE} = \pm 15 \text{ V}$ $V_{CC} = 600 \text{ V}$	$T_j = 150^\circ\text{C}$		6		mJ
$R_{th(j-c)}$	per diode				0.49	K/W
Module						
L_{CE}				15	20	nH
$R_{CC'+EE'}$	terminal-chip	$T_c = 25^\circ\text{C}$		0.25		m Ω
		$T_c = 125^\circ\text{C}$		0.5		m Ω
$R_{th(c-s)}$	per module			0.02	0.038	K/W
M_s	to heat sink M6		3		5	Nm
M_t		to terminals M6	2.5		5	Nm
						Nm
w					325	g



GB




Fig. 1: Typ. output characteristic, inclusive $R_{CC'+EE'}$




Fig. 2: Rated current vs. temperature $I_C = f(T_C)$




Fig. 3: Typ. turn-on /-off energy = $f(I_C)$




Fig. 4: Typ. turn-on /-off energy = $f(R_G)$




Fig. 5: Typ. transfer characteristic




Fig. 6: Typ. gate charge characteristic




Fig. 7: Typ. switching times vs. I_C




Fig. 8: Typ. switching times vs. gate resistor R_G




Fig. 9: Transient thermal impedance




Fig. 10: CAL diode forward characteristic




Fig. 11: CAL diode peak reverse recovery current




Fig. 12: Typ. CAL diode peak reverse recovery charge

