

SURFACE-MOUNT CHIP BEAD ARRAY



ACBA SERIES

FEATURES:

- Array construction
- Avoid crosstalk

OPTIONS:

- Tape & Reel is standard

APPLICATIONS:

- Wireless application
- Networking System

STANDARD SPECIFICATIONS:

Part Number	Z (Ω) $\pm 25\%$	Freq MHz	R _{DC} Ω Max	I _{RATE} Max mA
1206 Series				
ACBA-1206-30	30	100	0.20	500
ACBA-1206-60	60	100	0.25	400
ACBA-1206-120	120	100	0.30	350
ACBA-1206-150	150	100	0.35	250
ACBA-1206-220	220	100	0.35	250
ACBA-1206-300	300	100	0.40	250
ACBA-1206-470	470	100	0.50	200
ACBA-1206-600	600	100	0.50	200
ACBA-1206-1000	1000	100	0.75	150

Length (L)	0.126 \pm 0.008 (3,20 \pm 0,20)	Termination (D1)	0.016 \pm 0.006 (0,40 \pm 0,15)
Width (W)	0.063 \pm 0.008 (1,60 \pm 0,20)	Termination (D2)	0.008 \pm 0.004 (0,20 \pm 0,10)
Thickness (T)	0.035 \pm 0.008 (0,90 \pm 0,20)	Distance (D3)	0.031 \pm 0.004 (0,80 \pm 0,10)

• Operating Temperature: -40°C to +125°C

Note: All specifications subject to change without notice.

PHYSICAL CHARACTERISTICS:

