

HGL26025AA

POWERPACT H-FRAME, CIRCUIT BREAKER, THERMAL-MAGNETIC, 25A, 2P, 600V, 18kA



Price** : 1,566.00 USD



Main

Product or component type	Circuit breaker
Range of product	PowerPact H
Trip Unit Type	Thermal-magnetic
Breaking capacity code	G
Options	Auxiliary switch 1 NC + 1 NC

Complementary

Line Rated Current	25 A
Number of Poles	2P
Interrupt Rating	20 kA 500 V DC 65 kA 240 V AC 35 kA 480 V AC 18 kA 600 V AC 20 kA 250 V DC
[Ue] rated operational voltage	250 V DC 600 V AC 500 V DC
Continuous current rating	80 %
Mounting mode	Unit mount
Electrical connection	Lugs load Lugs line
Wire Gauge	AWG 14...AWG 3/0 aluminium/copper
Magnetic hold current	350 A
Magnetic tripping current	750 A
Maximum Height	6.4 in (162.56 mm)
Width	2.74 in (69.60 mm)
Depth	4.36 in (110.74 mm)
Tightening torque	44.25 lbf.in (5 N.m) 0.00...0.15 in ² (2.5...95 mm ²) AWG 14...AWG 3/0)

Environment

Product certifications	UL Listed CE IEC CSA CCC
Ambient air temperature for operation	104 °F (40 °C)

Ordering and shipping details

Category	01115-HG,HJ,JG,JJ UNIT MT BREAKER/SWITCH
Discount Schedule	DE2
Package weight(Lbs)	4.00 lb(US) (1.814 kg)
Returnability	No
Country of origin	US

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: DINP and DIDP which is known to the State of California to cause Carcinogen and Reproductive harm. For more information go to www.p65warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations