



ELECTRONICS, INC.

44 FARRAND STREET

BLOOMFIELD, NJ 07003

(973) 748-5089

<http://www.nteinc.com>

NTE30135 thru NTE30139 Super Bright LED Indicators 5mm, Bullet Head Type

Features:

- Low Power Consumption
- High Efficiency
- General Purpose Leads
- High Intensity
- All 5mm Bullet Head Super Bright Types w/Water Clear Lens:
 - NTE30135 (Yellow Green, AlGaInP)
 - NTE30136 (Yellow, AlGaInP)
 - NTE30137 (Red, AlGaInP)
 - NTE30138 (Blue, InGaN)
 - NTE30139 (White, InGaN)

Absolute Maximum Ratings: ($T_A = +25^{\circ}\text{C}$ unless otherwise specified)

Power Dissipation, P_D

NTE30135, NTE30136, NTE30137 75mW

NTE30138, NTE30139 90mW

Peak Forward Current (1/10th Duty Cycle, 0.1ms Pulse Width), I_{FM} 100mA

Continuous Forward Current, I_F

NTE30135, NTE30136, NTE30137 30mA

NTE30138, NTE30139 25mA

Derating Linear from $+50^{\circ}\text{C}$ 0.4mA/ $^{\circ}\text{C}$

Reverse Voltage, V_R 5V

Operating Temperature Range, T_{opr} -40° to $+85^{\circ}\text{C}$

Storage Temperature Range, T_{stg} -40° to $+100^{\circ}\text{C}$

Lead Temperature (During Soldering, 4mm from Body, 5sec Max), T_L $+260^{\circ}\text{C}$

Electrical Optical Characteristics: ($T_A = +25^{\circ}\text{C}$ unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Luminous Intensity	I_V	$I_F = 20\text{mA}$	600	1000	–	mcd
NTE30135						
NTE30136						
NTE30137						
NTE30138						
NTE30139						
View Angle of Half Power	$2 \theta_{1/2}$	$I_F = 20\text{mA}$	–	6	–	deg
Chromaticity Coordinates (NTE30139 ONLY)	X	$I_F = 20\text{mA}$	–	0.29	–	
	Y		–	0.29	–	
Color Temperature (NTE30139 ONLY)	CCT	$I_F = 20\text{mA}$	–	9500	–	K



Electrical Optical Characteristics (Cont'd): ($T_A = +25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Peak Emission Wavelength NTE30135	λ_P	$I_F = 20\text{mA}$	–	565	–	nm
NTE30136			–	591	–	nm
NTE30137			–	630	–	nm
NTE30138			–	470	–	nm
Dominant Emission Wavelength NTE30135	λ_d	$I_F = 20\text{mA}$	566	570	573	nm
NTE30136			586	590	592	nm
NTE30137			618	622	627	nm
NTE30138			464	470	473	nm
Spectral Line Half-Width NTE30135, NTE30136	$\Delta\lambda$	$I_F = 20\text{mA}$	–	20	–	nm
NTE30137			–	15	–	nm
NTE30138			–	30	–	nm
Forward Voltage NTE30135	V_F	$I_F = 20\text{mA}$	1.8	2.1	2.5	V
NTE30136, NTE30137			1.8	2.0	2.4	V
NTE30138			2.8	3.0	3.4	V
NTE30139			2.8	3.0	3.2	V
Reverse Current	I_R	$V_R = 5\text{V}$	–	–	10	μA

