



Screw Connectors

1000/ 3

Terminal Block, 3 pole, Insulating Material: PA 6, Cross-Section: 6.0 mm², Pin Spacing: 12.0 mm, Fixing: Screw, Voltage Rating: 500 V, Current Rating: 41 A



Order Info

| | |
|------------------------------------|---|
| Reference Number (ref. no.) | 125203 |
| Applications | Lighting, Installation, Electrical Appliances, Transformers |
| PU | 400 |
| EAN | 4028012100873 |

Type

| | |
|--------------------------------|---------------------|
| Type | Terminal Block |
| Number of poles | 3 pole |
| Clamping Units per Pole | 1 |
| Colour | natural |
| Cross-Section | 6.0 mm ² |
| Connection Type | Screw |

Technical Data

| | |
|---|---|
| Voltage Rating | 500 V |
| Current Rating | 41 A |
| Insulating Material | PA 6 |
| Contact Material | Brass |
| Core Cross-Section min. | 0.5 mm ² |
| Core Cross-Section max. | 10.0 mm ² |
| Flammability Rating | V-2 |
| max. Ambient Temperature Operation | 85 °C |
| Type of Conductor Solid | yes |
| Type of Conductor Flexible | yes |
| Type of Conductor Stranded | yes |
| Stripping Length | 7.5-8.0 mm |
| Assembly Contact Screw | 0.8x4.0 / ⚙ 0.8 Nm |
| Pin Spacing | 12.0 mm |
| Fixing | Screw |
| Approbation EN60998 | 1000_EN60998_20070806_20160412_VDE_ENEC_40021747_web.p |
| Approbation UL | 500_1000_19770222_20071007_UL_E63492_1-01_Description_wet |
| Approbation CSA | Schraub_Steck_Schraubenlos_SI_Klemmen_20160429_CSA_700765 |

Accessories

| | |
|-------------------|--------|
| 1000 BZ/ 3 | 191403 |
| ABK 406/ 3 | 193303 |
| ZEL 110 | 196420 |