

CUT-OUT

Nut Torque: 5 ~ 14Nm

Operating Pressure: 400gf ± 150gf

Operating Stroke: 1.5mm ± 0.3

Protection Grade: IP65

Function: (ON)-OFF

Base: PA66

Shell: Brass, Ni Plating

Button: SUS

Rating: 0.2A 250V AC/0.5A 12V DC

Contact Resistance: 50mΩ MAX.

Insulation Resistance: 100MΩ MIN.

Dielectric Strength: 1500V/AC of 1 minute

Electrical life: 50,000 cycles


Mechanical life: 200,000 cycles

Operating Temperature: -20°C ~ 80°C

Relative Air Humidity: 45% ~ 85%

Safety Approval: RoHS CCC

SWITCHING CIRCUIT



公差 TOLERANCES .X± 0.5 .XX± 0.3 角度 ANGLE ±1° 单位 DIMENSION UNIT mm.

版本 VERSION A0 比例尺 SCALE 1:1 日期 DATE 2020.12.08 品名 TITLE 图号 DRAWING NO

核准 CHECKED BY 孙成 绘图 DRAWN BY 孙成 PBM-12M11-FT-N-NN-B8S PBM-12M11-FT-N-NN-B8S_A0

版本 VER 变更说明 CHANGE DESCRIPTION

日期 DATE ECN NO.

APPROVED BY

CHECKED BY

DRAWN BY

PBM-12M11-FT-N-NN-B8S

PBM-12M11-FT-N-NN-B8S_A0