Product data sheet
Characteristics

HOM2175SB
LOAD CENTER HOM SECONDARY SURGE ARRESTOR

Product availability: Stock - Normally stocked in distribution facility



Main

Product	Secondary surge arrester
Range	Homeline Surge Breaker

Complementary

Surge Current	22.5 kA
System Voltage	120/240 V AC
Phase	1 phase
Wiring Configuration	3-wire
MCOV	150 V 300 V
Line Rated Current	5 kA
SCCR	22 kA
Local Signalling	1 LED, green = normal operation
Product destination	Load center Homeline
Height	3.7 in
Width	2 in
Depth	2.6 in

Environment

Enclosure Rating	NEMA 1
Standards	UL 1449 type II ed. 4
Ambient Operating	149 °F (65 °C)

Ordering and shipping details

Category	08461 - SURGE PROTECTION RESI
Discount Schedule	DE1B
GTIN	00785901210900
Nbr. of units in pkg.	1
Package weight(Lbs)	0.81000000000000005
Returnability	Y
Country of origin	MX

Offer Sustainability

RoHS (date code: YYWW)	Will be compliant on 3Q2014
REACh	Reference not containing SVHC above the threshold
California proposition 65	WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Contractual warranty

Warranty period	18 months