2018-12-14
Product version 00
Document revision 00

Data sheet

Order No.: 1716941

Type: LPC 6/ 4-STL3-7,62

PCB connector, Push-in spring connection




Figure shows a 4-pos. version (GL3 = locking flange on pole 3)

1 Main features



- No. of pos. 4
- Conductor cross section 6 mm²
- Color green (6021)
- Pitch 7.62 mm
- Connection method Push-in spring connection
- Nominal current 41 A
- Nominal voltage 1000 V
- Connection direction 0 °
- Type of packaging packed in cardboard

2 Your advantages

- Tool-free lever principle enables time-saving connection and release of conductors with/without ferrules
- Clear lever positions provide reliable feedback on opened or closed clamping spaces
- Defined contact force ensures that contact remains stable over the long term
- Time-saving push-in connection when lever is closed
- Intuitive locking mechanism prevents accidental disconnection

Make sure you always use the latest documentation.
It can be downloaded at: phoenixcontact.net/product/1716941

© PHOENIX CONTACT 2018

3 Table of contents

1 Main features ... 1
2 Your advantages ... 1
3 Table of contents ... 2
4 3D model in PDF can be activated (Acrobat Reader only) ... 3
5 item properties ... 4
6 Dimensions ... 6
7 Series drawing ... 7
8 Packaging information ... 8
9 Application ... 8
10 General tests ... 9
11 Mechanical tests ... 9
12 Electrical tests ... 11
13 Current carrying capacity/derating curves ... 12
14 Environmental and durability tests ... 13
15 Classification for connectors ... 13
16 Approvals ... 13
17 Commercial Data ... 14
18 corresponding headers ... 14
19 Accessories ... 14
20 Combination tests ... 15

© PHOENIX CONTACT 2018

4 3D model in PDF can be activated (Acrobat Reader only)



© PHOENIX CONTACT 2018

5 item properties

Order No.	1716941
Type	LPC 6/ 4-STL3-7,62
Plug-in system	POWER COMBICON 6
Product type	PCB connector
Type of contact	Female connector
Range of articles	LPC 6/..-STL2
Pitch	7.62 mm
Range of positions	2...6
Number of positions	4
Number of levels	1
Number of connections	4
Number of potentials	4
Connection method	Push-in spring connection
Type of locking	Snap-in locking
	Self-locking flange
Connection direction of the connector to the PCB	
Solder pins per potential	1

5.1 Connection capacity

Conductor cross section, solid	0.75 mm² ... 10 mm²
Conductor cross section, flexible	0.75 mm² ... 6 mm²
Conductor cross section flexible, with ferrule without plastic sleeve	0.75 mm² ... 6 mm²
Conductor cross section flexible, with ferrule with plastic sleeve	0.75 mm² ... 6 mm²
Cylindrical gauge a x b / diameter	4.3 mm x 4.0 mm / 4.0 mm
Stripping length	18 mm

5.2 Connection capacity AWG

Conductor cross section AWG	18 ... 8

5.3 Material data

Material of metal parts		
Note	WEEE/RoHS-compliant, whisker-free acc. to IEC 60068-2-82/JEDEC JESD 201	
Contact material	Cu alloy	
Terminal point surface	Tin (4 - 8 µm Sn)	
Surface contact area	Tin (4 - 8 µm Sn)	
Surface characteristics	Tin-plated	

Insulating material data	Housing	Actuation element
Insulating material	PA GF	PA
Insulating material group	I	I
CTI according to IEC 60112	600	600
Flammability rating according to UL 94	V0	V0
Color	green (6021)	

© PHOENIX CONTACT 2018

1716941 LPC 6/ 4-STL3-7,62

Insulating material data	Housing	Actuation element
Glow wire flammability index GWFI according to EN 60695-2-12	850	
Glow wire ignition temperature GWIT according to EN 60695-2-13	775	
Temperature for the ball pressure test according to EN 60695-10-2	125 °C	

© PHOENIX CONTACT 2018

6 Dimensions


6.1 Dimensions for the product

Length	48 mm
Width	40.1 mm
Height (without solder pin)	35.65 mm
Total height	35.65 mm
Dimension a	

© PHOENIX CONTACT 2018

1716941 LPC 6/ 4-STL3-7,62

7 Series drawing



Weitergabe sowie Vervielfältigung dieses Dokuments, Verwertung und Mitteilung seines Inhalts sind verboten, soweit nicht ausdrücklich gestattet. Zuwiderhandlungen verpflichten zu Schadenersatz. Alle Rechte für den Fall der Patent-, Gebrauchsmuster- oder Designeintragung vorbehalten.

Transfer or duplication of this document as well as the utilisation or communication of its content are not permitted unless express consent is granted. Violations give rise to claims for damages. All rights reserved in case of patent, utility model or design patent registrations.

© PHOENIX CONTACT 2018

8 Packaging information

Type of packaging	packed in cardboard
Pieces per package	25

9 Application

9.1 Temperature limit values

Ambient temperature (storage/transport)	-40 °C ... 70 °C
Ambient temperature (assembly)	-5 °C ... 100 °C
Ambient temperature (operation)	-40 °C (dependent on the derating curve)

© PHOENIX CONTACT 2018

10 General tests

10.1 Specification

Specification	IEC 61984
Specification	IEC 60999-1

11 Mechanical tests

11.1 Check for damage to conductor or loosening

Result	Test passed
Specification	IEC 60999-1:1999-11

11.2 Pull-out test

Specification	IEC 60999-1:1999-11
Result	Test passed
Conductor cross section/conductor type/tractive force actual value	0.75 mm^2 / solid / > 30 N
Conductor cross section/conductor type/tractive force actual value	0.75 mm^2 / flexible / > 30 N
Conductor cross section/conductor type/tractive force actual value	10 mm^2 / solid / > 90 N
Conductor cross section/conductor type/tractive force actual value	6 mm^2 / flexible / > 80 N

11.3 Repeated connection and disconnection

Specification	IEC 60999-1:1999-11
Result	Test passed

11.4 Conductor connection

Specification	IEC 60999-1:1999-11
Result	Test passed

11.5 Mechanical test group A

Specification	IEC 61984:2008-10
Visual examination	Test passed
Specification	IEC 60512-1-1:2002-02
Dimensional test	Test passed
Specification	IEC 60512-1-2:2002-02
Resistance of marking	Test passed
Specification	IEC 60068-2-70:1995-12
Insertion and withdrawal force	Test passed
Specification	IEC 60512-13-2:2006-02
No. of cycles	25
Insertion strength per pos. approx.	11 N
Withdraw strength per pos. approx.	10 N
Polarization and coding	Test passed

© PHOENIX CONTACT 2018

1716941 LPC 6/ 4-STL3-7,62

Specification	IEC 60512-13-5:2006-02
Test force	20 N
Contact retention in insert	Test passed
Specification	IEC 60512-15-1:2008-05
Test force per pos.	20 N

© PHOENIX CONTACT 2018

12 Electrical tests

12.1 Electrical data

Rated current / conductor cross section	41 A / 6 mm²
Rated insulation voltage (III/2)	1000 V
Rated surge voltage (III/2)	8 kV
Contact resistance	0.5 mΩ
Degree of pollution	2

12.2 Air and creepage distances

Component	PCB connector		
Specification	IEC 60664-1:2007-04		
Mains type	unearthed mains		
Insulating material group	I		
Comparative tracking index (IEC 60112:2003-01)	CTI 600		
Rated insulation voltage	800 V	1000 V	1000 V
Rated surge voltage	8 kV	8 kV	6 kV
Degree of pollution	3	2	2
Overvoltage category	III	III	II
Minimum clearance case A (inhomogeneous field)	8 mm	8 mm	5.5 mm
Minimum value of the creepage path requirement in acc. with table	10 mm	5 mm	5 mm

12.3 Electrical function

Specification	IEC 60999-1:1999-11
Result	Test passed
Voltage drop	Voltage drop (U) after the load ≤ 15 mV
Conductor cross section, flexible	0.75 mm² ... 6 mm²
Conductor cross section, solid	0.75 mm² ... 10 mm²

12.4 Temperature cycles


Specification	
Result	Test passed
Voltage drop	Voltage drop (U) after the load ≤ 22.5 mV or 1.5 x $U_{\text{after 24 h}}$ The small value is to be used.
Test current (minimum cross section)	9 A DC
Test current (maximum cross section)	41 A DC
Temperature cycles	192
Conductor cross section, flexible	0.75 mm² ... 6 mm²
Conductor cross section, solid	0.75 mm² ... 10 mm²

© PHOENIX CONTACT 2018

13 Current carrying capacity/derating curves

Specification	IEC 61984:2008-10
Note	Representation based on IEC 60512-5-2:2002-02
Reduction factor	0.8
Number of positions	See diagram
Conductor cross section	6 mm²

Typ: LPC 6/...-STL...-7,62 mit PC 6/...-GL...-7,62



Insulation resistance	
Specification	IEC 60512-3-1:2002-02
Result	Test passed
Insulation resistance, neighboring positions	> 4 TΩ

© PHOENIX CONTACT 2018

14 Environmental and durability tests

14.1 Vibration test

Specification	IEC 60068-2-6:2007-12
Result	Test passed
Frequency	10 - 150 - 10 Hz
Sweep speed	1 octave/min
Amplitude	0.35 mm (10 - 60.1 Hz)
Acceleration	5 g (60.1 - 150 Hz)
Test duration per axis	2.5 h
Test directions	X-, Y- and Z-axis
Note	The connected conductor loops were guided to the test sample at a distance of approx. 10 cm.

15 Classification for connectors

Specification	IEC 61984:2008-10
Main features	Connectors without switching capacity (COC)
Construction form	Fixed connectors
Strain relief elements	without strain relief
Connection method	Can be reconnected
Protection against electric shock	Not encapsulated - touch-proof when inserted
Protective conductor	without PE
Lock	no
Connection method	Screwless terminal points

15.1 Insulation resistance

Specification	IEC 60512-3-1:2002-02
Result	Test passed
Insulation resistance, neighboring positions	> 4 TΩ

16 Approvals

cULus Recognized				
Use group	F	B	C	
mm^2/AWG/kcmil	18-8	18-8	18-8	
Voltage	600 V	600 V	600 V	
Current	32 A	32 A	32 A	

© PHOENIX CONTACT 2018

17 Commercial Data

Order No.	1716941
Type	LPC 6/ 4-STL3-7,62
Pieces per package	25
Net weight	2.22 g
GTIN	4055626522449
	Information that applies locally, see link on page 1
Country of origin	Information that applies locally, see link on page 1

18 corresponding headers


Order No.	Type
1717035	PC 6/ 4-GL3-7,62


19 Accessories

Description	Order No.	Type
Coding profile, for plugging into the coding ribs of the plug at a later date, insulating material, color: Red	1701967	CP-PC RD
	3200603	AI 6 -18 YE
Crimping pliers, for uninsulated and insulated ferrules, DIN 46228 Part 1 and 4, from 0.14 mm^2 … 6 mm^2, also for TWIN ferrules up to 2 x 4 mm^2, automatic cross section adjustment, lateral insertion, equipped with fall protection	1213144	CRIMPFOX CENTRUS 6S
Stripping tool, for cables and conductors from 0.02 - 10 mm^2, self-adjusting, stripping length of up to 18 mm, cutting capacity of up to 10 mm^2 stranded/1.5 mm^2 solid, replaceable stripping blade	1212150	WIREFOX 10

© PHOENIX CONTACT 2018

20 Combination tests





LPC 6/..-STL2	**PC 6/..-GL2**
IEC 61984	IEC 61984
Mechanical tests (A)	
Insertion/withdrawal force per position	approx. 11 N / 10 N
Polarization when inserted Requirement >20 N	Test passed
Contact holder in insert Requirements >20 N	Test passed
Durability tests (B)	
Contact resistance R_1	0.5 mΩ
Insertion/withdrawal cycles	25
Contact resistance R_2	0.5 mΩ
Rated impulse voltage at sea level Voltage waveform ≥ (1.2/50 µs)	7.3 kV
Power-frequency withstand voltage Voltage waveform ≥ (50/60 Hz)	3.31 kV
Thermal tests (C)	
Tested number of positions	4
Tested conductor cross section	6 mm^2
Test current	41 A
Upper limiting temperature Requirements < 100°C	Test passed
Climatic tests (D)	
Test sequence 1: low temperature storage	-40 °C/2 h
Test sequence 2: heat storage	100 °C/168 h
Test sequence 3: noxious gas storage (ISO 6988)	0.2 dm^3 SO_2 on 300 dm^3/ 40 °C/1 cycle
Rated impulse voltage at sea level Voltage waveform ≥ (1.2/50 µs)	7.3 kV
Power-frequency withstand voltage Voltage waveform ≥ (50/60 Hz)	3.31 kV
Environmental and endurance tests (E)	
Specification	IEC 61984:2008-10
Degree of protection	Finger safety with IP20 test finger

© PHOENIX CONTACT 2018