DATA SHEET


GBJ6A~GBJ6K

GLASS PASSIVATED SINGLE-PHASE BRIDGE RECTIFIER

VOLTAGE - 50 to 800 Volts CURRENT - 6.0 Amperes

GBJ

Unit: inch (mm)



FEATURES

- Plastic material has Underwriters Laboratory Flammability Classification 94V-O
- Ideal for printed circuit board
- Reliable low cost construction utilizing molded plastic technique
- Surge overload rating: 175 Amperes peak
- High temperature soldering guaranteed: 260°C/10 seconds/.375"(9.5mm) lead length at 5 lbs. (2.3kg) tension

MECHANICAL DATA

Case: Reliable low cost construction utilizing molded plastic technique

Terminals: Leads solderable per MIL-STD-202, Method 208

Mounting position: Any

Mounting torque: 5 in. lb. Max.

Weight: 0.15 ounce, 4.0 grams

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Rating at 25°Cambient temperature unless otherwise specified. Resistive or inductive load, 60Hz.
For Capacitive load derate current by 20%.

	GBJ6A	GBJ6B	GBJ6D	GBJ6G	GBJ6J	GBJ6K	UNIT
Maximum Recurrent Peak Reverse Voltage	50	100	200	400	600	800	V
Maximum RMS Input Voltage	35	70	140	280	420	560	V
Maximum DC Blocking Voltage	50	100	200	400	600	800	V
Maximum Average Forward T_C=100°C Rectified Output Current	6.0						A
I^2t Rating for fusing (t<8.3ms)	127						A^2sec
Peak Forward Surge Current single sine-wave superimposed on rated load (JEDEC method)	175						Apk
Maximum Instantaneous Forward Voltage Drop per element at 6.0A	1.0						Vpk
Maximum Reverse Leakage at rated T_A=25° CDc Blocking Voltage per element T_C=100°C	5 500						μA μA
Typical Thermal Resistance per leg(Note 2) RθJA	8.6						°C / W
Typical Thermal Resistance per leg(Note 3) RθJC	3.1						°C / W
Operating and Storage Temperature Range, T_J,TSTG	-55 to +150						°C

NOTES:

1. Recommended mounting position is to bolt down on heatsink with silicone thermal compound for maximum heat transfer with #6 screw.
2. Units Mounted in free air, no heatsink, P.C.B at 0.375"(9.5mm) lead length with 0.5 x 0.5"(12 x 12mm)copper pads.
3. Units Mounted on a 2.6 x 1.4" x 0.06" thick (6.5 x 3.5 x 0.15cm) AL plate.

RATING AND CHARACTERISTIC CURVES




Fig. 1- DERATING CURVE FOR OUTPUT RECTIFIED CURRENT




Fig. 2- TYPICAL INSTANTANEOUS FORWARD CHARACTERISITCS PER ELEMENT




Fig. 3- TYPICAL REAK REVERSE CHARACTERISTICS




Fig. 4- MAXIMUM NON-REPETITEVE PEAK FORWARD SURGE CURRENT




Fig. 5- TYPICL JUNCTION CAPACITANCE PER ELEMENT