


Sales Region	Worldwide (except Japan)
Series	FPS
Model	FPS3000
Status	 Production
Feature	
Options	
Option Lineup	Please refer to here.
Recommended EMC Filter	
Accessories	Please refer to here.
Brand	TDK-Lambda



Electrical Characteristics

Input	Single-phase
Input Voltage Range[AC]	85 to 265Vac
Input Voltage Range[DC]	
Efficiency	86% Typ.
Rated Output Voltage[DC]	32Vdc
Output Voltage Range[DC]	28.8 to 38.4Vdc
Maximum Output Current	31A
Maximum Output Power	2976W

Package Type & Size

Package / Mounting	Rack mount
Industry Standard Size	
Width(W)	400mm Nom. (15.75in Nom.)
Height(H)	44mm Nom. (1.73in Nom.)
Depth(D)	351mm Nom. (13.82in Nom.)
Weight	10kg Typ. (22.0lbs Typ.)

Other

Operating Temp. Range	0 to 70°C
Cooling	Forced air
Safety Standard(Certified)	EN60950-1 UL60950-1
Safety Standard(Conformed)	

Remarks This page only shows representative characteristics. Please refer to the technical data for detailed specifications and conditions.

! Images are for reference only and show exemplary products.
! This PDF document was created based on the data listed on the TDK Corporation website.
! All specifications are subject to change without notice.