

# SN5433, SN54LS33, SN7433, SN74LS33 QUADRUPLE 2-INPUT POSITIVE-NOR BUFFERS WITH OPEN-COLLECTOR OUTPUTS

SDLS101

DECEMBER 1983—REVISED MARCH 1988

- Package Options Include Plastic "Small Outline" Packages, Ceramic Chip Carriers and Flat Packages, and Plastic and Ceramic DIPs
- Dependable Texas Instruments Quality and Reliability

## description


These devices contain four independent 2-input NOR buffer gates with open-collector outputs. Open-collector outputs require resistive pull-up to perform logically but can deliver higher  $V_{OH}$  levels and are commonly used in wired-AND applications.

The SN5433 and SN54LS33 are characterized for operation over the full military temperature range of  $-55^{\circ}\text{C}$  to  $125^{\circ}\text{C}$ . The SN7433, and SN74LS33 are characterized for operation from  $0^{\circ}\text{C}$  to  $70^{\circ}\text{C}$ .

FUNCTION TABLE (each gate)


| INPUTS |   | OUTPUT |
|--------|---|--------|
| A      | B | Y      |
| H      | X | L      |
| X      | H | L      |
| L      | L | H      |

## logic symbol†




† This symbol is in accordance with ANSI/IEEE Std 91-1984 and IEC Publication 617-12.  
Pin numbers shown are for D, J, N, and W packages.

SN5433, SN54LS33 . . . J OR W PACKAGE  
SN7433 . . . N PACKAGE  
SN74LS33 . . . D OR N PACKAGE  
(TOP VIEW)




SN54LS33 . . . FK PACKAGE  
(TOP VIEW)



NC - No internal connection

## logic diagram



## positive logic

$$Y = \overline{A + B} \text{ or } Y = \overline{A} \cdot \overline{B}$$


PRODUCTION DATA documents contain information current as of publication date. Products conform to specifications per the terms of Texas Instruments standard warranty. Production processing does not necessarily include testing of all parameters.

TEXAS  
INSTRUMENTS

POST OFFICE BOX 655012 • DALLAS, TEXAS 75265

# **SN5433, SN54LS33, SN7433, SN74LS33** **QUADRUPL 2-INPUT POSITIVE-NOR BUFFERS WITH OPEN-COLLECTOR OUTPUTS**

schematics (each gate)



Resistor values shown are nominal.

**absolute maximum ratings over operating free-air temperature range (unless otherwise noted)**

|                                       |                |
|---------------------------------------|----------------|
| Supply voltage, $V_{CC}$ (see Note 1) | 7 V            |
| Input voltage: '33                    | 5.5 V          |
| 'LS33                                 | 7 V            |
| Off-state output voltage              | 7 V            |
| Operating free-air temperature: SN54' | -55°C to 125°C |
| SN74'                                 | 0°C to 70°C    |
| Storage temperature range             | -65°C to 150°C |

NOTE 1: Voltage values are with respect to network ground terminal.

**TEXAS**  
**INSTRUMENTS**

POST OFFICE BOX 655012 • DALLAS, TEXAS 75265

# SN5433, SN7433

## QUADRUPLE 2-INPUT POSITIVE-NOR BUFFERS WITH OPEN-COLLECTOR OUTPUTS

### recommended operating conditions

|                 |                                | SN5433 |     |     | SN7433 |     |      | UNIT |
|-----------------|--------------------------------|--------|-----|-----|--------|-----|------|------|
|                 |                                | MIN    | NOM | MAX | MIN    | NOM | MAX  |      |
| V <sub>CC</sub> | Supply voltage                 | 4.5    | 5   | 5.5 | 4.75   | 5   | 5.25 | V    |
| V <sub>IH</sub> | High-level input voltage       | 2      |     |     | 2      |     |      | V    |
| V <sub>IL</sub> | Low-level input voltage        |        |     | 0.8 |        |     | 0.8  | V    |
| V <sub>OH</sub> | High-level output voltage      |        |     | 5.5 |        |     | 5.5  | V    |
| I <sub>OL</sub> | Low-level output current       |        |     | 48  |        |     | 48   | mA   |
| T <sub>A</sub>  | Operating free-air temperature | -55    |     | 125 | 0      |     | 70   | °C   |

### electrical characteristics over recommended operating free-air temperature range (unless otherwise noted)

| PARAMETER        | TEST CONDITIONS†                                                        | SN5433 |      |      | SN7433 |      |      | UNIT |
|------------------|-------------------------------------------------------------------------|--------|------|------|--------|------|------|------|
|                  |                                                                         | MIN    | TYP‡ | MAX  | MIN    | TYP‡ | MAX  |      |
| V <sub>IK</sub>  | V <sub>CC</sub> = MIN, I <sub>I</sub> = -12 mA                          |        |      | -1.5 |        |      | -1.5 | V    |
| I <sub>OH</sub>  | V <sub>CC</sub> = MIN, V <sub>IL</sub> = 0.8 V, V <sub>OH</sub> = 5.5 V |        |      |      |        |      | 0.25 | mA   |
|                  | V <sub>CC</sub> = MIN, V <sub>IL</sub> = 0.7 V, V <sub>OH</sub> = 5.5 V |        |      | 0.25 |        |      |      |      |
| V <sub>OL</sub>  | V <sub>CC</sub> = MIN, V <sub>IH</sub> = 2 V, I <sub>OL</sub> = 16 mA   |        | 0.2  | 0.4  |        | 0.2  | 0.4  | V    |
| I <sub>I</sub>   | V <sub>CC</sub> = MAX, V <sub>I</sub> = 5.5 V                           |        |      | 1    |        |      | 1    | mA   |
| I <sub>IH</sub>  | V <sub>CC</sub> = MAX, V <sub>I</sub> = 2.4 V                           |        |      | 40   |        |      | 40   | μA   |
| I <sub>IL</sub>  | V <sub>CC</sub> = MAX, V <sub>I</sub> = 0.4 V                           |        |      | -1.6 |        |      | -1.6 | mA   |
| I <sub>CCH</sub> | V <sub>CC</sub> = MAX, V <sub>I</sub> = 0                               |        | 3    | 6    |        | 3    | 6    | mA   |
| I <sub>CCL</sub> | V <sub>CC</sub> = MAX, See Note 2                                       |        | 9    | 16.5 |        | 9    | 16.5 | mA   |

†For conditions shown as MIN or MAX, use the appropriate value specified under recommended operating conditions.

‡All typical values are at V<sub>CC</sub> = 5 V, T<sub>A</sub> = 25°C.

NOTE 2: One input at 4.5 V, all others at 0 V.

### switching characteristics, V<sub>CC</sub> = 5 V, T<sub>A</sub> = 25°C (see Figure 1)

| PARAMETER        | FROM (INPUT) | TO (OUTPUT) | TEST CONDITIONS                                  | MIN | TYP | MAX | UNIT |
|------------------|--------------|-------------|--------------------------------------------------|-----|-----|-----|------|
| t <sub>PLH</sub> | A or B       | Y           | R <sub>L</sub> = 133 kΩ, C <sub>L</sub> = 50 pF  |     | 10  | 15  | ns   |
| t <sub>PHL</sub> |              |             |                                                  |     | 12  | 18  | ns   |
| t <sub>PLH</sub> |              |             | R <sub>L</sub> = 133 kΩ, C <sub>L</sub> = 150 pF |     | 15  | 22  | ns   |
| t <sub>PHL</sub> |              |             |                                                  |     | 16  | 24  | ns   |

NOTE 3: Load circuits and voltage waveforms are shown in Section 1.



POST OFFICE BOX 655012 • DALLAS, TEXAS 75265

# SN54LS33, SN74LS33

## QUADRUPLE 2-INPUT POSITIVE-NOR BUFFERS WITH OPEN-COLLECTOR OUTPUTS

### recommended operating conditions

|                                      | SN54LS33 |     |     | SN74LS33 |     |      | UNIT |
|--------------------------------------|----------|-----|-----|----------|-----|------|------|
|                                      | MIN      | NOM | MAX | MIN      | NOM | MAX  |      |
| $V_{CC}$ Supply voltage              | 4.5      | 5   | 5.5 | 4.75     | 5   | 5.25 | V    |
| $V_{IH}$ High-level input voltage    | 2        |     |     | 2        |     |      | V    |
| $V_{IL}$ Low-level input voltage     |          |     | 0.7 |          |     | 0.8  | V    |
| $V_{OH}$ High-level output voltage   |          |     | 5.5 |          |     | 5.5  | V    |
| $I_{OL}$ Low-level output current    |          |     | 12  |          |     | 24   | mA   |
| $T_A$ Operating free-air temperature | -55      |     | 125 | 0        |     | 70   | °C   |

### electrical characteristics over recommended operating free-air temperature range (unless otherwise noted)

| PARAMETER | TEST CONDITIONS †                                                                        | SN54LS33 |       |     | SN74LS33 |       |     | UNIT |
|-----------|------------------------------------------------------------------------------------------|----------|-------|-----|----------|-------|-----|------|
|           |                                                                                          | MIN      | TYP ‡ | MAX | MIN      | TYP ‡ | MAX |      |
| $V_{IK}$  | $V_{CC} = \text{MIN}, I_I = -18 \text{ mA}$                                              |          | -1.5  |     |          | -1.5  |     | V    |
| $I_{OH}$  | $V_{CC} = \text{MIN}, V_{IH} = 2 \text{ V}, V_{IL} = \text{MAX}, V_{OH} = 5.5 \text{ V}$ |          | 0.25  |     |          | 0.25  |     | mA   |
| $V_{OL}$  | $V_{CC} = \text{MIN}, V_{IH} = 2 \text{ V}, V_{IL} = \text{MAX}, I_{OL} = 12 \text{ mA}$ | 0.25     | 0.4   |     | 0.25     | 0.4   |     | V    |
|           | $V_{CC} = \text{MIN}, V_{IL} = \text{MAX}, I_{OL} = 24 \text{ mA}$                       |          |       |     | 0.35     | 0.5   |     |      |
| $I_I$     | $V_{CC} = \text{MAX}, V_I = 7 \text{ V}$                                                 |          | 0.1   |     |          | 0.1   |     | mA   |
| $I_{IH}$  | $V_{CC} = \text{MAX}, V_I = 2.7 \text{ V}$                                               |          | 20    |     |          | 20    |     | μA   |
| $I_{IL}$  | $V_{CC} = \text{MAX}, V_I = 0.4 \text{ V}$                                               |          | -0.4  |     |          | -0.4  |     | mA   |
| $I_{CCH}$ | $V_{CC} = \text{MAX}, V_I = 0$                                                           | 1.8      | 3.6   |     | 1.8      | 3.6   |     | mA   |
| $I_{CCL}$ | $V_{CC} = \text{MAX}, \text{ See Note 2}$                                                | 6.9      | 13.8  |     | 6.9      | 13.8  |     | mA   |

†For conditions shown as MIN or MAX, use the appropriate value specified under recommended operating conditions.

‡All typical values are at  $V_{CC} = 5 \text{ V}, T_A = 25^\circ\text{C}$ .

NOTE 2: One input at 4.5 V, all others at 0 V.

### switching characteristics, $V_{CC} = 5 \text{ V}, T_A = 25^\circ\text{C}$ (see note 3)

| PARAMETER | FROM (INPUT) | TO (OUTPUT) | TEST CONDITIONS                         | MIN | TYP | MAX | UNIT |
|-----------|--------------|-------------|-----------------------------------------|-----|-----|-----|------|
| $t_{PLH}$ | A or B       | Y           | $R_L = 667 \Omega, C_L = 45 \text{ pF}$ |     | 20  | 32  | ns   |
| $t_{PHL}$ |              |             |                                         |     | 18  | 28  | ns   |

NOTE 3: Load circuits and voltage waveforms are shown in Section 1.



POST OFFICE BOX 655012 • DALLAS, TEXAS 75265

## IMPORTANT NOTICE

Texas Instruments (TI) reserves the right to make changes to its products or to discontinue any semiconductor product or service without notice, and advises its customers to obtain the latest version of relevant information to verify, before placing orders, that the information being relied on is current.

TI warrants performance of its semiconductor products and related software to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are utilized to the extent TI deems necessary to support this warranty. Specific testing of all parameters of each device is not necessarily performed, except those mandated by government requirements.

Certain applications using semiconductor products may involve potential risks of death, personal injury, or severe property or environmental damage ("Critical Applications").

TI SEMICONDUCTOR PRODUCTS ARE NOT DESIGNED, INTENDED, AUTHORIZED, OR WARRANTED TO BE SUITABLE FOR USE IN LIFE-SUPPORT APPLICATIONS, DEVICES OR SYSTEMS OR OTHER CRITICAL APPLICATIONS.

Inclusion of TI products in such applications is understood to be fully at the risk of the customer. Use of TI products in such applications requires the written approval of an appropriate TI officer. Questions concerning potential risk applications should be directed to TI through a local SC sales office.

In order to minimize risks associated with the customer's applications, adequate design and operating safeguards should be provided by the customer to minimize inherent or procedural hazards.

TI assumes no liability for applications assistance, customer product design, software performance, or infringement of patents or services described herein. Nor does TI warrant or represent that any license, either express or implied, is granted under any patent right, copyright, mask work right, or other intellectual property right of TI covering or relating to any combination, machine, or process in which such semiconductor products or services might be or are used.

## **IMPORTANT NOTICE**

Texas Instruments and its subsidiaries (TI) reserve the right to make changes to their products or to discontinue any product or service without notice, and advise customers to obtain the latest version of relevant information to verify, before placing orders, that information being relied on is current and complete. All products are sold subject to the terms and conditions of sale supplied at the time of order acknowledgement, including those pertaining to warranty, patent infringement, and limitation of liability.

TI warrants performance of its semiconductor products to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are utilized to the extent TI deems necessary to support this warranty. Specific testing of all parameters of each device is not necessarily performed, except those mandated by government requirements.

CERTAIN APPLICATIONS USING SEMICONDUCTOR PRODUCTS MAY INVOLVE POTENTIAL RISKS OF DEATH, PERSONAL INJURY, OR SEVERE PROPERTY OR ENVIRONMENTAL DAMAGE ("CRITICAL APPLICATIONS"). TI SEMICONDUCTOR PRODUCTS ARE NOT DESIGNED, AUTHORIZED, OR WARRANTED TO BE SUITABLE FOR USE IN LIFE-SUPPORT DEVICES OR SYSTEMS OR OTHER CRITICAL APPLICATIONS. INCLUSION OF TI PRODUCTS IN SUCH APPLICATIONS IS UNDERSTOOD TO BE FULLY AT THE CUSTOMER'S RISK.

In order to minimize risks associated with the customer's applications, adequate design and operating safeguards must be provided by the customer to minimize inherent or procedural hazards.

TI assumes no liability for applications assistance or customer product design. TI does not warrant or represent that any license, either express or implied, is granted under any patent right, copyright, mask work right, or other intellectual property right of TI covering or relating to any combination, machine, or process in which such semiconductor products or services might be or are used. TI's publication of information regarding any third party's products or services does not constitute TI's approval, warranty or endorsement thereof.