



Product availability: Non-Stock - Not normally stocked in distribution facility



Main

Product or component type	Automatic switch
Range of product	PowerPact L
Trip unit technology	Magnetic

Complementary

Line Rated Current	600 A
System Voltage	600 V AC
Mounting mode	I-Line
Poles description	3P
Breaking capacity	125 kA 240 V AC 100 kA 480 V AC 50 kA 600 V AC
Breaking capacity code	L
Electrical connection	I-Line connection line Lugs load
AWG gauge	AWG 3/0...500 kcmil aluminium/copper 2
Terminal identifier	AL600LF52K3
Magnetic tripping current	6600 A
Height	13 in
Width	6 in
Depth	4.75 in
Tightening torque	50 N.m 0.15...0.37 in ² (95...240 mm ²) AWG 3/0...500 kcmil

Environment

Product certifications	CCC CE CSA IEC UL listed NMX
------------------------	---

Ordering and shipping details

Category	01118 - L ELEC TRIP I-LINE BREAKER/SW
Discount Schedule	DE2
GTIN	00785901146254
Nbr. of units in pkg.	1
Package weight(Lbs)	17
Returnability	Y
Country of origin	US

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1132 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available End Of Life Information
Product end of life instructions	Available
California proposition 65	WARNING: This product can expose you to chemicals including:
- - - - - Substance 1	DINP, which is known to the State of California to cause cancer, and
- - - - - Substance 2	DIDP, which is known to the State of California to cause Birth Defects or other reproductive harm.
- - - - - More information	For more information go to www.p65warnings.ca.gov

Contractual warranty

Warranty period	18 months
-----------------	-----------