

**CABLE / Kabel**


 Flat cable LIYZ 2x0.14mm<sup>2</sup>  
 colour white  
 ends of wires stripped and tinned

 Flachkabel LIYZ 2x0.14 mm<sup>2</sup>  
 Farbe weiss  
 Enden abisoliert und verzinkt

 Abmessungen / dimensions (mm)  
 unspecified tolerances acc. to DIN ISO 2768-m

**MARKING / Aufdruck**

 MEDER-Label, Type  
 Production code EN60062/  
 Factory code, circuit diagram

 MEDER-Logo, Typ  
 Produktionscode  
 EN60062/Fertigungsstätte  
 Schaltbild

**CIRCUIT DIAGRAM  
Schaltbild**


Magnetical properties	Conditions	Min	Typ	Max	Unit
Pull in	at 20 °C	33		53	AT
Test equipment		KMS-14			

Special Product Data	Conditions	Min	Typ	Max	Unit
Contact - form		A - NO			
Contact rating	Any DC combination of V & A not to exceed their individual max.'s			10	W
operating voltage	DC or Peak AC			180	VDC
operating ampere	DC or Peak AC			1,25	A
Switching current				0,5	A
Sensor-resistance	measured with 40% overdrive			290	mOhm
Housing material		PBT glass fibre reinforced			
Case color		white			
Sealing compound		Polyurethan			

Environmental data	Conditions	Min	Typ	Max	Unit
Operating temperature	Cable not moved	-30		70	°C
Operating temperature	cable moved	-5		70	°C
Storage temperature		-30		70	°C

Cable specification	Conditions	Min	Typ	Max	Unit
Cable typ		flat cable			
Cable material		PVC, white			
Cross section [mm <sup>2</sup> ]		2x0,14			

General data	Conditions	Min	Typ	Max	Unit
Mounting advice		from 5m cable, a pre-resistor is recommended.			
Mounting advice		Decreased switching distances by mounting on iron.			
Mounting advice		Magnetically conductive screws must not be used.			
tightening torque	Screw M3 ISO 1207 Disk ISO 7089			0,5	Nm