



Price** : 1,223.00 USD



Main

Product or component type	Motor Circuit Protector
Range of product	PowerPact H
Trip Unit Type	Electronic, standard,
Breaking capacity code	L

Complementary

Line Rated Current	30 A
Number of Poles	3P
Interrupt Rating	125 kA 240 V AC 100 kA 480 V AC 50 kA 600 V AC
[Ue] rated operational voltage	600 V AC
Mounting mode	Unit mount
Electrical connection	Lugs load Lugs line
Wire Gauge	AWG 14...AWG 3/0 aluminium/copper
[Ith] conventional free air thermal current	1.5...25 A
Magnetic tripping current	9...325 A
Maximum Height	6.4 in (162.56 mm)
Width	4.12 in (104.65 mm)
Depth	4.36 in (110.74 mm)
Tightening torque	44.25 lbf.in (5 N.m) 0.00...0.15 in ² (2.5...95 mm ²) AWG 14...AWG 3/0)

Environment

Product certifications	IEC CE
------------------------	-----------

UR
CCC

Ambient air temperature for operation	104 °F (40 °C)
---------------------------------------	----------------

Ordering and shipping details

Category	01127 - HL, JL UNT MNT MTR CIRCUIT PROTECTR
Discount Schedule	DE2
GTIN	00785901632139
Package weight(Lbs)	4.32 lb(US) (1.96 kg)
Returnability	Yes
Country of origin	MX

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------