


ZWS75BAF-48/CO2



Sales Region	Worldwide
Series	ZWS-BAF
Status	Production
Feature	
Option	With coating on both sides of PCB model
Option Lineup	Please refer to here.
Recommended EMC Filter	Please refer to here.
Accessories	Please refer to the catalog



Electrical Characteristics	
Input Voltage Range[AC]	85 to 265V
Input Voltage Range[DC]	120 to 370V
Efficiency	88% Typ.
Rated Output Voltage[DC]	48V
Output Voltage Range[DC]	39.5 to 52.8V
Maximum Output Current	1.6A
Maximum Output Power	76.8W

Cases Shape & Size	
Case'□ shape	PC board
Width(W)	50mm Nom.
Height(H)	33mm Nom.
Depth(D)	150mm Nom.
Weight	230g Typ.

Other	
Operating Temp. Range	-10 to 70°C
Cooling	Convection cooling
Safety Standard(Certified)	UL60950-1
	CSA C22.2 No.60950-1
	EN60950-1
Safety Standard(Conformed)	EN50178 (OV II)
	Den-an
Remarks	This page only shows representative characteristics. Please refer to the technical data for detailed specifications and conditions.

! Images are for reference only and show exemplary products.
! This PDF document was created based on the data listed on the TDK Corporation website.
! All specifications are subject to change without notice.