

SS0115TW

SURFACE MOUNT SCHOTTKY BARRIER DIODE

VOLTAGE 15 Volt **CURRENT** 0.1 Ampere

FEATURES


- Low voltage high speed switching application
- Small surface mounting type
- Low V_F and low I_R
- Three diodes in parallel installation
- Power dissipation is 200mW
- Maximum peak forward current is 200mA
- Lead free in compliance with EU RoHS 2011/65/EU directive
- Green molding compound as per IEC61249 Std. . (Halogen Free)

MECHANICAL DATA

- Case : SOT-363, Plastic
- Terminals : Solderable per MIL-STD-750, Method 2026
- Approx. Weight : 0.0002 ounces, 0.006 grams
- Marking : 115

SOT-363

Unit : inch(mm)



MAXIMUM RATINGS (at $T_A=25^\circ\text{C}$ unless otherwise specified)


Ratings	Symbol	Limits	Unit
Maximum Recurrent Peak Reverse Voltage	V_{RRM}	15	V
Maximum RMS Voltage	V_{RMS}	10	V
Maximum DC Blocking Voltage	V_{DC}	15	V
Maximum Average Forward Rectified Current	I_O	0.1	A
Peak Forward Surge Current at 8.3ms single half sine-wave	I_{FSM}	1.0	A
Typical Junction Capacitance between Terminal (Note 1)	C_J	40	pF
Operating Junction and Storage Temperature Range	T_J, T_{STG}	-55 to +125	$^\circ\text{C}$

ELECTRICAL CHARACTERISTICS (at $T_A=25^\circ\text{C}$ unless otherwise specified)





Characteristics	Symbol	Min.	Typ.	Max.	Unit
Maximum Instantaneous Forward Voltage at $I_F=1\text{mA}$	V_F	-	0.18	-	V
$I_F=5\text{mA}$		-	0.23	0.30	
$I_F=100\text{mA}$		-	0.35	0.50	
Maximum Average Reverse Current at $V_R=10\text{V}$	I_R	-	-	20	μA

NOTES : 1.Measured at 1.0MHz and applied reverse voltage of 0 volts

2. ESD sensitive product handling required



SS0115TW




SS0115TW

MOUNTING PAD LAYOUT

SOT-363

Unit : inch(mm)



ORDER INFORMATION

- Packing information
 - T/R - 10K per 13" plastic Reel
 - T/R - 3K per 7" plastic Reel

SS0115TW

Part No_packing code_Version

SS0115TW_R1_00001

SS0115TW_R2_00001

For example :

RB500V-40_R2_00001

Part No.

Serial number

Version code means HF

Packing size code means 13"

Packing type means T/R

Packing Code XX				Version Code XXXXX		
Packing type	1 st Code	Packing size code	2 nd Code	HF or RoHS	1 st Code	2 nd ~5 th Code
Tape and Ammunition Box (T/B)	A	N/A	0	HF	0	serial number
Tape and Reel (T/R)	R	7"	1	RoHS	1	serial number
Bulk Packing (B/P)	B	13"	2			
Tube Packing (T/P)	T	26mm	X			
Tape and Reel (Right Oriented) (TRR)	S	52mm	Y			
Tape and Reel (Left Oriented) (TRL)	L	PANASERT T/B CATHODE UP (PBCU)	U			
FORMING	F	PANASERT T/B CATHODE DOWN (PBCD)	D			



SS0115TW

Disclaimer

- Reproducing and modifying information of the document is prohibited without permission from Panjit International Inc..
- Panjit International Inc. reserves the rights to make changes of the content herein the document anytime without notification. Please refer to our website for the latest document.
- Panjit International Inc. disclaims any and all liability arising out of the application or use of any product including damages incidentally and consequentially occurred.
- Panjit International Inc. does not assume any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.
- Applications shown on the herein document are examples of standard use and operation. Customers are responsible in comprehending the suitable use in particular applications. Panjit International Inc. makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.
- The products shown herein are not designed and authorized for equipments requiring high level of reliability or relating to human life and for any applications concerning life-saving or life-sustaining, such as medical instruments, transportation equipment, aerospace machinery et cetera. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Panjit International Inc. for any damages resulting from such improper use or sale.
- Since Panjit uses lot number as the tracking base, please provide the lot number for tracking when complaining.