

NT24k[®]-12GX4-POE Industrial PoE+ Switch

N-Tron[®] Networking Series



▶▶▶ Industrial Managed Gigabit PoE+ Ethernet Switch

Red Lion's N-Tron[®] series NT24k[®]-12GX4-POE compact managed Gigabit Ethernet switch features eight 10/100/1000Base-T(X) ports with PoE+ and four 1000Base-FX fiber ports with SC connectors, providing a robust solution for transmitting power and data to equipment in harsh environments.

The NT24k-12GX4-POE managed switch features 12 ports (eight Gigabit IEEE 802.3af/at Power over Ethernet Plus (PoE+) ports and four 1000Base-FX fiber ports) and is housed in a compact, hardened metal DIN-rail enclosure with redundant 22-49 VDC power inputs. Designed to handle the most demanding environments, the NT24k-12GX4-POE provides up to 30 Watts of power per port, high shock and vibration ratings and a wide -40° to 80°C operating temperature range.



APPLICATIONS

- > Alternative Energy
- > Manufacturing
- > Oil & Gas
- > Transportation
- > Water/Wastewater

PRODUCT HIGHLIGHTS

- > IEEE 802.3af/at PoE+ Output
- > Smart Plug-and-Play Operation
- > 22 to 49 VDC Redundant Power Inputs
- > -40° to 80°C Wide Operating Temperature
- > Robust Remote Monitoring
- > N-Ring™ & N-Link™ Network Ring Technology

FEATURES & BENEFITS

- > 12 Copper and Fiber Ports
 - Eight 10/100/1000Base-T(X) copper ports, supporting PoE+ on each port
 - Four 1000Base-FX ports with SC connectors
- > Redundant 22 to 49 VDC Power Inputs
 - Boosts power to meet PoE+ output requirements
- > IEEE 802.3af/at PoE Output
 - Supports PoE+ output on all copper ports simultaneously
- > Extended Environmental Specifications
 - -40° to 80°C operating temperature range
 - > 2M hours MTBF
 - UL/cUL: Class I, Div. 2 Groups A, B, C and D
- > Plug-and-Play Operation:
 - IGMP auto-configuration
 - MDIX auto-sensing cable
 - Simple network ring configuration
 - Backup and restore via recovery card or XML
- > Fully Managed Features Include:
 - Jumbo frame support
 - SNMP v1, v2, v3
 - Web browser management
 - Detailed ring map and fault location charting
 - RSTP - 802.1d, 802.1w, 802.1D
 - Trunking and port mirroring
 - 802.1Q tag VLAN and port VLAN
 - IEEE 802.1x with RADIUS remote server authentication
 - 802.1p QoS, port QoS and DSCP
 - DHCP client
 - Event Log
 - SNTP (Simple Network Time Protocol)
 - Multi-Member N-Ring technology with ~30ms healing
 - N-Link redundant ring technology
 - N-View™ monitoring technology
 - EtherNet/IP™ CIP™ messaging

industrial
networking



EtherNet/IP™

▶▶▶ NT24k-12GX4-POE Specifications

SWITCH PROPERTIES

Operation: Managed
Number of MAC Addresses: 16,000
IEEE Compliant: 802.3, 802.3u, 802.3ab, 802.3x, 802.3af/at,
802.1d/D/w, 802.1p, 802.1Q, 802.1x
Latency (Typical): 1.6 μ s
Switching Method: Store-and-Forward
Supports 30 Watts per Port (25.5 Watts at the PD)
LED Status Indicators
Configurable Alarm Contact
Onboard Temperature Sensor
Supports Full/Half Duplex Operation
Maximum Throughput: Up to 24 Gb/s
MDIX Auto Sensing Cable
Auto Sensing Speed and Flow Control
Communications: Full Wire Speed
MTBF: >2 million hours

POWER INPUT

Input Voltage: 22-49 VDC
Steady Input Current: 11.37 A @ 24 VDC
Inrush: 60 A / .2 ms @ 24 VDC
BTU/HR: 122

POWER OVER ETHERNET

PoE Standard: IEEE 802.3af/at Gigabit PSE
PoE Output Power: 57 VDC / 30 Watts Output (25.5 W at PD)
Power Pin Assignment: Pins 1/2 (-), Pins 3/6 (+)
PSE Type: Type 2

CONNECTORS

10/100/1000BaseT: Eight (8) RJ-45 ports
ESD and surge protection diodes on all copper ports
1000BaseFX: Four (4) SC duplex fiber ports
Configuration Port: One (1) USB Type B

NETWORK MEDIA

10BaseT: \geq Cat3 cable
100BaseTX: \geq Cat5 cable
1000BaseT: \geq Cat5e cable
1000BaseSX Multimode: 50-62.5/125 μ m
1000BaseLX Singlemode: 7-10/125 μ m

RECOMMENDED WIRING CLEARANCE

Front: 4" (10.16 cm)
Top: 4" (10.16 cm)

ENVIRONMENTAL

Operating Temperature: -40°C to 80°C
Storage Temperature: -40°C to 85°C
Operating Humidity: 10% to 95% (non condensing)
Operating Altitude: 0 to 10,000 ft.
Shock: 200 g @ 10 ms (bulkhead mounted)
Vibration: 50 g @ 5-20 Hz, Triaxial (bulkhead mounted)

CERTIFICATION & COMPLIANCE

Product Safety:
ANSI/ISA 12.12.01-2013 Class I and II, Div. 2 and Class III, Div. 1 and 2, Groups A, B, C and D Hazardous Locations
UL508 Industrial Control Equipment
CAN/CSA-C22.2 No. 213-M1987 Class I Div. 2 Hazardous Locations
CAN/CSA-C22.2 No. 14-M1987 Industrial Control Equipment
Emissions:
FCC Title 47, Part 15, Radio Frequency Devices, Subpart B ANSI C63.4-2009; Industry Canada ICES-003, EN 55011; EN 61000-6-4, EN 61000-3-2, EN61000-3-3, EN 55032
Immunity:
EN 55024, EN 61000-6-2; IEC 61000-4-2 (ESD); IEC 61000-4-3 (RFAM); IEC 61000-4-4 (EFT); IEC 61000-4-5 (SURGE); IEC 61000-4-6 (RFM); IEC 61000-4-8 (PFMF); IEC 61000-4-11 (VDI)
Rail:
EN 50155, EN 50121 and EN 61373
Designed to Comply with:
IEEE 1613 (Electric Utility Substations), NEMA TS1/TS2 (Traffic Control)
Other:
ABS Type Approval for Shipboard Applications; EMC Directive 2014/30/EU; LV Directive 2014/35/EU GOST-R, RoHS Compliant

MECHANICAL

Case Dimensions:
Height: 5.88" (14.92 cm)
Width: 4.28" (10.88 cm)
Depth: 5.54" (14.07 cm)
Weight: 3.32 lbs (1.51 kg)
Mount: DIN Rail 35 mm

WARRANTY

3 Years on Design and Manufacturing Defects

▶▶▶ NT24k-12GX4-POE Specifications

FIBER TRANSCEIVER CHARACTERISTICS

| | | | | |
|--------------------|--------------------------------------|----------|---------|---------|
| Fiber Mode | MM | SM | SM | SM |
| Fiber Length* | 550m @ 50/125µm 300m @ 62.5/125µm | 10 km | 40 km | 80 km |
| TX Power Min | -9.5 dBm | -9.5 dBm | -5 dBm | 0 dBm |
| RX Sensitivity Max | -17 dBm | -20 dBm | -23 dBm | -24 dBm |
| Wavelength | 850 nm | 1310 nm | 1310 nm | 1550 nm |
| Laser Type | VCSEL | FP | DFB | DFB |


* Fiber Length distances represent typical performance.
Link budgets should be evaluated based on specific application conditions.

ORDERING GUIDE

| PART NUMBER | DESCRIPTION |
|------------------------|--|
| NT24K-12GX4-SC-POE | 12-Port Gigabit Managed POE+ Industrial Ethernet Switch (8 10/100/1000BaseT, 4 1000BaseSX, multimode 550m ports) |
| NT24K-12GXE4-SC-ZZ-POE | 12-Port Gigabit Managed POE+ Industrial Ethernet Switch (8 10/100/1000BaseT, 4 1000BaseLX, singlemode ports) |
| NTCD-CFG | NT24k Configuration Recovery Device |
| NTPS-24-20 | DIN-Rail Power Supply, 20 Amp @ 24VDC |
| NTPS-48-10 | DIN-Rail Power Supply, 10 Amp @ 48VDC |
| NT24K-NM-PMK | NT24k Non-Modular Panel Mount Kit |

Where ZZ=10, 40, or 80

DIMENSIONS



All specifications are subject to change. Consult the company website for more information.



www.redlion.net

Connect. Monitor. Control.

Americas
sales@redlion.net

Asia-Pacific
asia@redlion.net

**Europe
Middle East
Africa**
europe@redlion.net

+1 (717) 767-6511

As the global experts in communication, monitoring and control for industrial automation and networking, Red Lion has been delivering innovative solutions for over forty years. Our automation, Ethernet and cellular M2M technology enables companies worldwide to gain real-time data visibility that drives productivity. Product brands include Red Lion, N-Tron and Sixnet. With headquarters in York, Pennsylvania, the company has offices across the Americas, Asia-Pacific and Europe. Red Lion is part of Spectris plc, the productivity-enhancing instrumentation and controls company. For more information, please visit www.redlion.net.

ADLD0423 051916 © 2016 Red Lion Controls, Inc. All rights reserved. Red Lion, the Red Lion logo, N-Tron and Sixnet are registered trademarks of Red Lion Controls, Inc. All other company and product names are trademarks of their respective owners.