


CUT-OUT

| | X | Y |
|-----------|----------|---------|
| 0.75~1.25 | 13.6-0.1 | 8.7±0.1 |
| 1.25~2.00 | 13.7-0.1 | 8.7±0.1 |
| 2.00~3.00 | 13.8-0.1 | 8.7±0.1 |



MATERIAL:

Cover:Nylon66, UL rated:94V-2 min
 Base:Nylon66, UL rated:94V-2 min
 Terminal:Brass, silver or tin plated
 Rating:6A 125V AC (UL CUL)
 3A 250V AC (UL CUL VDE CE CQC)

Function:ON-OFF
 Contact Resistance: 50mΩ Max
 Insulation Resistance: 100MΩ Min
 Dielectric Strength: 2000VAC 1 minute
 Dielectrical life: 10,000 cycles
 Mechanical life :50,000 cycles
 Operating Temperature: -20℃~80℃
 Safety Approval: **UL** **DVE** **CQC** **CE** **RoHS**



公差 TOLERANCES .X±0.3 .XX±0.15 角度 ANGLE ±1° 单位 DIMENSION UNIT mm.

| 版本 VER | 变更说明 CHANGE DESCRIPTION | 日期 DATE | ECN NO. | 核准 APPROVED BY | 核对 CHECKED BY | 绘图 DRAWN BY | 品名 TITLE | 图号 DRAWING NO |
|--------|-------------------------|---------|---------|----------------|---------------|-------------|----------------|------------------|
| | | | | | | 陈汉文 | MR5-111-C5N-WW | MR5-111-C5N-WW_0 |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |