

Europe: +49 / 7731 8399 0 | Email: info@meder.com
USA: +1 / 508 295 0771 | Email: salesusa@meder.com
Asia: +852 / 2955 1682 | Email: salesasia@meder.com

Item No.:
2220711074
Item:
MK02/0-1A66-700W

Dimensions mm[inch]
tolerances acc. to DIN ISO 2768-m
Toleranzen gem. DIN ISO 2768-m




Isometric
Scale 1:2
Maßstab 1:2




Cable
PVC LIYY 2x025qmm
colour of mantle: grey
colour of wires: white, brown
PVC LIYY 2x0,25qmm
Mantelfarbe: grau
Aderfarben: weiß. braun

Terminals/Connector
Ends tinned
Enden verzinnt


Schematic




Marking
according to EN60062/factory code
gem. EN60062/Fertigungsstätte



Housing



Switching distances



Modifications in the sense of technical progress are reserved

Designed at:	17.08.06	Designed by:	KSCHIELENSKI	Approval at:	09.10.07	Approval by:	BUELTZHOEFFER	
Last Change at:	15.11.12	Last Change by:	OMUELLER	Approval at:	15.11.12	Approval by:	TFRITSCHI	**Version:** 04

MEDER electronic
Products for tomorrow...

Europe: +49 / 7731 8399 0 | Email: info@meder.com
USA: +1 / 508 295 0771 | Email: salesusa@meder.com
Asia: +852 / 2955 1682 | Email: salesasia@meder.com

Item No.:
2220711074
Item:
MK02/0-1A66-700W

Magnetic properties	Conditions	Min	Typ	Max	Unit
Pull in	at 20°C	4,5		10	mm
Drop out	at 20°C	5,5		13,5	mm
Test equipment		SV 002			

Special Product Data	Conditions	Min	Typ	Max	Unit
Contact - No.		66			
Contact - form		A - NO			
Contact rating	Any DC combination of V & A not to exceed their individual max.'s			10	W
operating voltage	DC or Peak AC			180	V
operating ampere	DC or Peak AC			1,25	A
Switching current	DC or Peak AC			0,5	A
Sensor-resistance	measured with 40% overdrive Sensor deactivated			260	mOhm
Housing material		PBT glass fibre reinforced			
Case color		blue			
Sealing compound		Polyurethan			

Environmental data	Conditions	Min	Typ	Max	Unit
Operating temperature	cable not moved	-30		80	°C
Operating temperature	cable moved	-5		80	°C
Storage temperature		-30		80	°C

Cable specification	Conditions	Min	Typ	Max	Unit
Cable typ		round cable			
Cable material		PVC			
Cross section		0,25 qmm			

General data	Conditions	Min	Typ	Max	Unit
Mounting advice		over 5m cable, a series resistor is recommended.			
mounting advice 1		Decreased switching distances by mounting on iron			
mounting advice 2		Don`t use magnetically conductive screws			
tightening torque	Screw M3 ISO 1207 Disk ISO 7089			0,5	Nm

Modifications in the sense of technical progress are reserved

Designed at: 17.08.06 Designed by: KSCHIELENSKI Approval at: 09.10.07 Approval by: BUELTZHOEFFER
Last Change at: 15.11.12 Last Change by: OMUELLER Approval at: 15.11.12 Approval by: TFRITSCHI **Version:** 04