



SPECIFICATIONS

- 1、Current Rating: 2A AC, DC
- 2、Voltage Rating: 250V AC, DC
- 3、Temperatuer Range: $-25^{\circ}\text{C} \sim +85^{\circ}\text{C}$
- 4、Contact Resistance: $20\text{m}\Omega$ Max
- 5、Insulation Resistance: $1000\text{M}\Omega$ Min
- 6、Withstanding Voltang: 1000V AC/minute
- 7、Material: Wafer LCP, UL94V-0
PIN Brass Tin-plated
Solder tad Brass Tin-plated

编 号	尺寸 (mm)	
	A	B
HC-HY-2AWT	2.00	8.00
HC-HY-3AWT	4.00	10.00
HC-HY-4AWT	6.00	12.00
HC-HY-5AWT	8.00	14.00
HC-HY-6AWT	10.00	16.00
HC-HY-7AWT	12.00	18.00
HC-HY-8AWT	14.00	20.00
HC-HY-9AWT	16.00	22.00
HC-HY-10AWT	18.00	24.00
HC-HY-11AWT	20.00	26.00
HC-HY-12AWT	22.00	28.00
HC-HY-13AWT	24.00	30.00
HC-HY-14AWT	26.00	32.00
HC-HY-15AWT	28.00	34.00
HC-HY-16AWT	30.00	36.00

PCB LAYOUT

制图 DRAWN	变更内容 DESCRIPTION	日期 DATE	GENERAL TOLERANCE		制图 DRAWING	钱岳生		料号 PART NO.	HC-HY-NAWT		版本 REV.	A
			X. \pm 0.25	X.* \pm 2'		2013、07、01	品名 TITLE		HY贴片 WAFER SMT TYPE	页次 SHEET		1/1
			.X \pm 0.20	.X* \pm 1'		审核 CHECK	2013、07、03		客户料号 CUTL NO.			
			.XX \pm 0.15	.XX* \pm 0.5'		核准 APPROVAL	2013、07、05		张名			
.XXX \pm 0.10	.XXX* \pm 0.5'	单位 UNITS	MM	比例 SCALE	1:1	深圳市华灿天禄电子有限公司						