


Servo motor EMMS-AS-100-LK-HV-RSB-S1

Part number: 1563002

FESTO



Data sheet

Feature	Value
Number of pole pairs	6
Type code	EMMS-AS
Rotor position sensor	Absolute encoder, single-turn
Rotor position sensor interface	EnDat® 22
Rotor position sensor measuring principle	Inductive
Temperature monitoring	PTC resistor
Max. rotational speed	4040 1/min
Nominal rotary speed	3400 1/min
Brake DC operating voltage	24 V
Insulation protection class	F
Brake power consumption	18 W
Motor constants	1.66 Nm/A
Nominal operating voltage DC	565 V
Motor nominal power	2240 W
DC nominal voltage	565 V
Motor nominal current	3.79 A
Rotor position sensor resolution	18 bit
Phase-phase winding resistance	1.98 Ohm
Winding inductance phase-phase	7.76 mH
Type of winding switch	Star inside
Peak current	24.8 A
Voltage constant, phase-to-phase	98.93 mVmin
Rating class according to EN 60034-1	S1
CE marking (see declaration of conformity)	As per EU EMC directive As per EU low voltage directive
Corrosion resistance class (CRC)	2 - Moderate corrosion stress
Storage temperature	-20 °C ... 60 °C
Relative air humidity	0 - 90 %
Degree of protection	IP65
Ambient temperature	-10 °C ... 40 °C
Certification	RCM compliance mark c UL us - Recognized (OL)
Total output inertia moment	7.21 kgcm ²
Brake holding torque	9 Nm
Brake mass moment of inertia	0.61 kgcm ²
Nominal torque	6.29 Nm

Feature	Value
Peak torque	35.4 Nm
Stall torque	10.93 Nm
Permissible axial shaft load	150 N
Permissible radial shaft load	650 N
MTTF, subcomponent	76 years, rotor position sensor 3356 years, holding brake
MTTFd, subcomponent	152 years, rotor position sensor
Switching cycles, holding brake	10 million idle actuations (without friction work!)
Product weight	9390 g
Electrical connection technology	Plug
Note on materials	RoHS-compliant
Conforms to standard	IEC 60034
Featherkey shaft design	DIN 6885 A 6 x 6 x 32