

MJE18604D2

Advance Information

High Speed, High Gain Bipolar NPN Power Transistor with Integrated Collector-Emitter Diode and Built-in Efficient Antisaturation Network for 1600 V Applications

POWER TRANSISTORS
3 AMPERES
1600 VOLTS
100 WATTS





CASE 221A–06
TO–220AB

The MJE18604D2 is state–of–art High Speed High gain BIPolar transistor (H2BIP). Tight dynamic characteristics and lot to lot low spread (±150 ns on storage time) make it ideally suitable for light ballast applications. Therefore, there is no more a need to guarantee an h_{fe} window.

Main features:

- Low Base Drive Requirement
- High DC Current Gain (30 Typical) @ I_C = 400 mA
- Extremely Low Storage Time Min/Max Guarantees Due to the Internal Active Antisaturation (H2BIP) Structure which Minimizes the Spread
- Integrated Collector–Emitter Free Wheeling Diode Matched with the Power Transistor
- Fully Characterized and Guaranteed Dynamic $V_{CE(sat)}$
- "6 Sigma" Process Providing Tight and Reproductible Parameter Spreads

MAXIMUM RATINGS

Rating	Symbol	Value	Unit
Collector–Emitter Breakdown Voltage	V_{CEO}	800	Vdc
Collector–Emitter Sustaining Voltage @ R = 200 Ω	V_{CER}	800	Vdc
Collector–Base Breakdown Voltage	V_{CBO}	1600	Vdc
Collector–Emitter Breakdown Voltage	V_{CES}	1600	Vdc
Emitter–Base Voltage	V_{EBO}	12	Vdc
Collector Current — Continuous — Peak (1)	I_C I_{CM}	3 8	Adc
Base Current — Continuous — Peak (1)	I_B I_{BM}	2 4	Adc
*Total Device Dissipation @ T_C = 25°C *Derate above 25°C	P_D	100 0.8	Watt W/°C
Operating and Storage Temperature	T_J, T_{stg}	–65 to 150	°C

THERMAL CHARACTERISTICS

Thermal Resistance — Junction to Case — Junction to Ambient	$R_{\theta JC}$ $R_{\theta JA}$	1.25 62.5	°C/W
Maximum Lead Temperature for Soldering Purposes: 1/8″ from case for 5 seconds	T_L	260	°C

(1) Pulse Test: Pulse Width = 5 ms, Duty Cycle ≤ 10%.

This document contains information on a new product. Specifications and information herein are subject to change without notice.

Designer's and SWITCHMODE are trademarks of Motorola, Inc.

© Motorola, Inc. 1995

ELECTRICAL CHARACTERISTICS (T_C = 25°C unless otherwise noted)

Characteristic			Symbol	Min	Typ	Max	Unit
OFF CHARACTERISTICS							
Collector–Emitter Sustaining Voltage (I_C = 100 mA, L = 25 mH, R_{BE} = 200 Ω)			$V_{CER(sus)}$	800			Vdc
Collector–Base Breakdown Voltage (I_{CBO} = 1 mA)			V_{CBO}	1600			Vdc
Emitter–Base Breakdown Voltage (I_{EBO} = 1 mA)			V_{EBO}	12	14		Vdc
Collector Cutoff Current (V_{CBO} = Rated V_{CBO}, I_B = 0)			I_{CBO}			100	μAdc
Collector Cutoff Current (V_{CE} = Rated V_{CES}, V_{EB} = 0)	@ T_C = 25°C		I_{CES}			100	μAdc
	@ T_C = 125°C					1000	
(V_{CE} = 1300 V, V_{EB} = 0)	@ T_C = 125°C					100	
Emitter–Cutoff Current (V_{EB} = 11 Vdc, I_C = 0)			I_{EBO}			500	μAdc
ON CHARACTERISTICS							
Base–Emitter Saturation Voltage			$V_{BE(sat)}$				Vdc
(I_C = 0.5 Adc, I_B = 0.1 Adc)	@ T_C = 25°C				0.8	1.1	
	@ T_C = 125°C				0.6	1	
(I_C = 1 Adc, I_B = 0.1 Adc)	@ T_C = 25°C				0.8	1	
	@ T_C = 125°C					1	
(I_C = 2 Adc, I_B = 0.4 Adc)	@ T_C = 25°C				0.9	1.2	
	@ T_C = 125°C				0.8	1.1	
Collector–Emitter Saturation Voltage			$V_{CE(sat)}$				Vdc
(I_C = 250 mAdc, I_B = 25 mAdc)	@ T_C = 25°C				1	1.25	
	@ T_C = 125°C				1.7		
(I_C = 0.5 Adc, I_B = 50 mAdc)	@ T_C = 25°C				2.1	2.4	
	@ T_C = 125°C				4		
(I_C = 0.8 Adc, I_B = 80 mAdc)	@ T_C = 25°C				3.7	5	
	@ T_C = 125°C						
DC Current Gain			h_{FE}				—
(I_C = 0.4 Adc, V_{CE} = 3 Vdc)	@ T_C = 25°C			20		40	
	@ T_C = 125°C			6	10		
(I_C = 5 mAdc, V_{CE} = 10 Vdc)	@ T_C = 25°C			20	35		
	@ T_C = 125°C			20	55		
DYNAMIC SATURATION VOLTAGE							
Dynamic Saturation Voltage: Determined 1 μs and 3 μs respectively after rising I_{B1} reaches 90% of final I_{B1}	I_C = 0.3 Adc, I_{B1} = 50 mA, V_{CC} = 300 V	@ 1 μs	@ T_C = 25°C	$V_{CE(dsat)}$		4.7		V
			@ T_C = 125°C			9.3		
		@ 3 μs	@ T_C = 25°C			2.6		
			@ T_C = 125°C			5.4		
	I_C = 0.5 Adc, I_{B1} = 50 mA, V_{CC} = 300 V	@ 1 μs	@ T_C = 25°C			9.7		
			@ T_C = 125°C			18		
		@ 3 μs	@ T_C = 25°C			6.4		
			@ T_C = 125°C			12.3		
DIODE CHARACTERISTICS							
Forward Diode Voltage			V_{EC}				V
(I_{EC} = 0.4 Adc)	@ T_C = 25°C				0.9	1.2	
	@ T_C = 125°C				0.6		
(I_{EC} = 1 Adc)	@ T_C = 25°C				1.05	1.5	
	@ T_C = 125°C				0.7		
Forward Recovery Time			t_{fr}				μs
(I_F = 0.4 Adc, di/dt = 10 A/μs)	@ T_C = 25°C				0.9		
	@ T_C = 125°C				1.5		
(I_F = 1.0 Adc, di/dt = 10 A/μs)	@ T_C = 25°C				1.15		
	@ T_C = 125°C				1.6		


ELECTRICAL CHARACTERISTICS (T_C = 25°C unless otherwise noted)

Characteristic			Symbol	Min	Typ	Max	Unit
DYNAMIC CHARACTERISTICS							
Current Gain Bandwidth (I_C = 0.5 Adc, V_{CE} = 10 Vdc, f = 1 MHz)			f_T		13		MHz
Output Capacitance (V_{CB} = 10 Vdc, I_E = 0, f = 1 MHz)			C_{ob}		230	500	pF
Input Capacitance (V_{CE} = 8 Vdc)			C_{ib}		480	1000	pF
SWITCHING CHARACTERISTICS: Resistive Load (D.C. ≤ 10%, Pulse Width = 40 μs)							
Delay Time	I_C = 0.5 Adc I_{B1} = 66 mAdc I_{B2} = 390 mAdc V_{CC} = 125 V	@ T_C = 25°C @ T_C = 125°C	t_d		95 110	150	ns
Rise Time		@ T_C = 25°C @ T_C = 125°C	t_r		475 900	750	ns
Storage Time		@ T_C = 25°C @ T_C = 125°C	t_s	400	 910	700	ns
Fall Time		@ T_C = 25°C @ T_C = 125°C	t_f		675 775	850	ns
Turn–on Time	I_C = 0.3 Adc I_{B1} = 50 mAdc I_{B2} = 50 mAdc V_{CC} = 125 V	@ T_C = 25°C @ T_C = 125°C	t_{on}		440 570		ns
Storage Time		@ T_C = 25°C @ T_C = 125°C	t_s		4 5.9		μs
Fall Time		@ T_C = 25°C @ T_C = 125°C	t_f		375 675		ns
Turn–off Time		@ T_C = 25°C @ T_C = 125°C	t_{off}		4.5 6.6		μs
Turn–on Time	I_C = 0.3 Adc I_{B1} = 50 mAdc I_{B2} = 150 mAdc V_{CC} = 125 V	@ T_C = 25°C @ T_C = 125°C	t_{on}		465 550	600	ns
Storage Time		@ T_C = 25°C @ T_C = 125°C	t_s	500	 1800	800	ns
Fall Time		@ T_C = 25°C @ T_C = 125°C	t_f		800 550	1000	ns
Turn–off Time		@ T_C = 25°C @ T_C = 125°C	t_{off}		1.5 2.4	1.75	μs
Turn–on Time	I_C = 0.5 Adc I_{B1} = 50 mAdc I_{B2} = 50 mAdc V_{CC} = 125 V	@ T_C = 25°C @ T_C = 125°C	t_{on}		550 1300		ns
Storage Time		@ T_C = 25°C @ T_C = 125°C	t_s		4.35 5		μs
Fall Time		@ T_C = 25°C @ T_C = 125°C	t_f		500 2000		ns
Turn–off Time		@ T_C = 25°C @ T_C = 125°C	t_{off}		4.8 7		μs
Delay Time	I_C = 0.5 Adc I_{B1} = 50 mAdc I_{B2} = 250 mAdc V_{CC} = 125 V	@ T_C = 25°C	t_d		100	300	ns
Rise Time		@ T_C = 25°C	t_r		300	800	ns
Storage Time		@ T_C = 25°C	t_s		1	1.2	μs
Fall Time		@ T_C = 25°C	t_f		200	350	ns

ELECTRICAL CHARACTERISTICS (T_C = 25°C unless otherwise noted)

Characteristic			Symbol	Min	Typ	Max	Unit
SWITCHING CHARACTERISTICS: Inductive Load (V_{CC} = 15 V)							
Fall Time	I_C = 300 mAdc I_{B1} = 50 mAdc I_{B2} = 50 mAdc V_Z = 300 V L_C = 200 µH	@ T_C = 25°C @ T_C = 125°C	t_f		170 210		ns
Storage Time		@ T_C = 25°C @ T_C = 125°C	t_s		1.7 2.7		µs
Crossover Time		@ T_C = 25°C @ T_C = 125°C	t_c		150 400		ns
Fall Time	I_C = 300 mAdc I_{B1} = 50 mAdc I_{B2} = 150 mAdc V_Z = 300 V L_C = 200 µH	@ T_C = 25°C @ T_C = 125°C	t_f		160 150	250	ns
Storage Time		@ T_C = 25°C @ T_C = 125°C	t_s	0.7	 1.1	1	µs
Crossover Time		@ T_C = 25°C @ T_C = 125°C	t_c		160 160	250	ns
Fall Time	I_C = 500 mAdc I_{B1} = 50 mAdc I_{B2} = 50 mAdc V_Z = 300 V L_C = 200 µH	@ T_C = 25°C @ T_C = 125°C	t_f		165 700		ns
Storage Time		@ T_C = 25°C @ T_C = 125°C	t_s		3 4.1		µs
Crossover Time		@ T_C = 25°C @ T_C = 125°C	t_c		200 800		ns
Fall Time	I_C = 500 mAdc I_{B1} = 50 mAdc I_{B2} = 250 mAdc V_Z = 300 V L_C = 200 µH	@ T_C = 25°C @ T_C = 125°C	t_f		110 130	175	ns
Storage Time		@ T_C = 25°C @ T_C = 125°C	t_s	0.7	 1.8	1	µs
Crossover Time		@ T_C = 25°C @ T_C = 125°C	t_c		130 250	200	ns

PACKAGE DIMENSIONS



NOTES:
1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: INCH.
3. DIMENSION Z DEFINES A ZONE WHERE ALL BODY AND LEAD IRREGULARITIES ARE ALLOWED.

	INCHES		MILLIMETERS	
DIM	MIN	MAX	MIN	MAX
A	0.570	0.620	14.48	15.75
B	0.380	0.405	9.66	10.28
C	0.160	0.190	4.07	4.82
D	0.025	0.035	0.64	0.88
F	0.142	0.147	3.61	3.73
G	0.095	0.105	2.42	2.66
H	0.110	0.155	2.80	3.93
J	0.018	0.025	0.46	0.64
K	0.500	0.562	12.70	14.27
L	0.045	0.060	1.15	1.52
N	0.190	0.210	4.83	5.33
Q	0.100	0.120	2.54	3.04
R	0.080	0.110	2.04	2.79
S	0.045	0.055	1.15	1.39
T	0.235	0.255	5.97	6.47
U	0.000	0.050	0.00	1.27
V	0.045	—	1.15	—
Z	—	0.080	—	2.04

STYLE 1:
PIN 1. BASE
2. COLLECTOR
3. EMITTER
4. COLLECTOR

CASE 221A–06
TO–220AB
ISSUE Y

Motorola reserves the right to make changes without further notice to any products herein. Motorola makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does Motorola assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation consequential or incidental damages. “Typical” parameters can and do vary in different applications. All operating parameters, including “Typicals” must be validated for each customer application by customer’s technical experts. Motorola does not convey any license under its patent rights nor the rights of others. Motorola products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the Motorola product could create a situation where personal injury or death may occur. Should Buyer purchase or use Motorola products for any such unintended or unauthorized application, Buyer shall indemnify and hold Motorola and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that Motorola was negligent regarding the design or manufacture of the part. Motorola and Ⓜ are registered trademarks of Motorola, Inc. Motorola, Inc. is an Equal Opportunity/Affirmative Action Employer.

How to reach us:
USA / EUROPE: Motorola Literature Distribution;
P.O. Box 20912; Phoenix, Arizona 85036. 1–800–441–2447

MFAX: RMFAX0@email.sps.mot.com – TOUCHTONE (602) 244–6609
INTERNET: http://Design–NET.com

JAPAN: Nippon Motorola Ltd.; Tatsumi–SPD–JLDC, Toshikatsu Otsuki,
6F Seibu–Butsuryu–Center, 3–14–2 Tatsumi Koto–Ku, Tokyo 135, Japan. 03–3521–8315

HONG KONG: Motorola Semiconductors H.K. Ltd.; 8B Tai Ping Industrial Park,
51 Ting Kok Road, Tai Po, N.T., Hong Kong. 852–26629298