



PCB Holes Diagram
xqc; Top View

NOTE:
1. MATERIAL:
a. HOUSING: THERMOPLASTIC GLASS FIBRE UL94V-0
b. CONTACT: PHOSPHOR BRONZE
(SURFACE PLATING: A*U*)
SEE ORDERING INFORMATION
2. ELECTRIC:
a. CONTACT RESISTANCE: 30 MILLIOHMS MAX
b. INSULATION RESISTANCE: 1000 MEGA OHMS MIN
c. DIELECTRIC VOLTAGE: 750V AC ONE SEC LEVEL
d. OPERATING TEMPERATURE: -55°C~ +85°C

ORDERING INFORMATION

BS-1057-A**0*012

电池座系列
BS-1057系列
SMT 180° TYPE

PLATING:

J-Sn100U~120U"
K-Sn150U"
A-Au 1u"
1A-Au 3u"

MATERIAL:

1A-PBT WHITE
1B-PBT BLACK
2A-PA66 WHITE
2B-PA66 BLACK
3A-LCP WHITE
3B-LCP BLACK

CRUST:
0-WITHOUT

Tolerance: Unless otherwise specified

LINEAR	ANGLE	3	TERMINAL-2	PHOSPHOR BRONZE	AU-Plated
x. ±1	x' ±5'	2	TERMINAL-1	PHOSPHOR BRONZE	AU-Plated
.x ±0.38	.x' ±2'	1	HOUSING	LCP	WHITE
.xx ±0.25	.xx' ±1'	NO.	PART NAME	MATERIAL	COLOR/FINISHED
.xxx ±0.10	.xxx' ±1'				

日期 DATE	单位 UNITS	审核 CHECK	BATTERY HDLDR	PART NO.
2014.04.20	mm	QJ.LIU		BS-12(1057)
比例 SCALE	制图 DRAW	设计 DESIGN	TITLE:	
1/1	QJ.QILIU	QJ.HUAN	QJ-1057电池座 (CR2032SMT)	