Freescale Semiconductor
Technical Data

Document Number: MMG3013NT1
Rev. 2, 8/2005

RoHS

Heterojunction Bipolar Transistor Technology (InGaP HBT)

Broadband High Linearity Amplifier

The MMG3013NT1 is a General Purpose Amplifier that is internally input matched and internally output matched. It is designed for a broad range of Class A, small-signal, high linearity, general purpose applications. It is suitable for applications with frequencies from 0 to 6000 MHz such as Cellular, PCS, BWA, WLL, PHS, CATV, VHF, UHF, UMTS and general small-signal RF.

MMG3013NT1

0-6000 MHz, 20 dB
20.5 dBm
InGaP HBT



CASE 1514-01, STYLE 1
SOT-89
PLASTIC

Features

- Frequency: 0-6000 MHz
- P1dB: 20.5 dBm @ 900 MHz
- Small-Signal Gain: 20 dB @ 900 MHz
- Third Order Output Intercept Point: 36 dBm @ 900 MHz
- Single 5 Volt Supply
- Internally Matched to 50 Ohms
- Low Cost SOT-89 Surface Mount Package
- Pb-Free and RoHS Compliant
- In Tape and Reel. T1 Suffix = 1000 Units per 12 mm, 7 inch Reel.

Table 1. Typical Performance (1)

Characteristic	Symbol	900 MHz	2140 MHz	3500 MHz	Unit
Small-Signal Gain (S21)	G_p	20	17	14.5	dB
Input Return Loss (S11)	IRL	-17	-19	-15	dB
Output Return Loss (S22)	ORL	-11	-9	-12	dB
Power Output @1dB Compression	P1db	20.5	20.5	19	dBm
Third Order Output Intercept Point	IP3	36	34	32	dBm

1. V_{CC} = 5 Vdc, T_C = 25°C, 50 ohm system

Table 2. Maximum Ratings

Rating	Symbol	Value	Unit
Supply Voltage (2)	V_{CC}	7	V
Supply Current (2)	I_{CC}	300	mA
RF Input Power	P_{in}	12	dBm
Storage Temperature Range	T_{stg}	-65 to +150	°C
Junction Temperature (3)	T_J	150	°C

2. Continuous voltage and current applied to device.
3. For reliable operation, the junction temperature should not exceed 150°C.

Table 3. Thermal Characteristics (V_{CC} = 5 Vdc, I_{CC} = 90 mA, T_C = 25°C)

Characteristic	Symbol	Value (4)	Unit
Thermal Resistance, Junction to Case	$R_{\theta JC}$	42	°C/W

4. Refer to AN1955, *Thermal Measurement Methodology of RF Power Amplifiers.* Go to http://www.freescale.com/rf. Select Documentation/Application Notes - AN1955.

© Freescale Semiconductor, Inc., 2005. All rights reserved.

freescale semiconductor

Table 4. Electrical Characteristics (V_{CC} = 5 Vdc, 900 MHz, T_C = 25°C, 50 ohm system, in Freescale Application Circuit)

Characteristic		Symbol	Min	Typ	Max	Unit
Small-Signal Gain (S21)	900 MHz 2140 MHz	G_p	19.3 16	20 17	— —	dB
Input Return Loss (S11)		IRL	—	-17	—	dB
Output Return Loss (S22)		ORL	—	-11	—	dB
Power Output @ 1dB Compression		P1dB	—	20.5	—	dBm
Third Order Output Intercept Point		IP3	—	36	—	dBm
Noise Figure		NF	—	4	—	dB
Supply Current (1)		I_{CC}	80	90	110	mA
Supply Voltage (1)		V_{CC}	—	5	—	V

1. For reliable operation, the junction temperature should not exceed 150°C.

Table 5. Functional Pin Description

Pin Number	Pin Function
1	RF_{in}
2	Ground
3	RF_{out}/DC Supply



Figure 1. Functional Diagram

Table 6. ESD Protection Characteristics

Test Methodology	Class
Human Body Model (per JESD 22-A114)	1A (Minimum)
Machine Model (per EIA/JESD 22-A115)	A (Minimum)
Charge Device Model (per JESD 22-C101)	IV (Minimum)

Table 7. Moisture Sensitivity Level

Test Methodology	Rating	Package Peak Temperature	Unit
Per JESD 22-A113, IPC/JEDEC J-STD-020	1	260	°C

50 OHM TYPICAL CHARACTERISTICS



Figure 2. Small-Signal Gain (S21) versus Frequency



Figure 3. Input/Output Return Loss versus Frequency



Figure 4. Small-Signal Gain versus Output Power



Figure 5. P1dB versus Frequency



Figure 6. Collector Current versus Collector Voltage



Figure 7. Third Order Output Intercept Point versus Frequency

50 OHM TYPICAL CHARACTERISTICS



Figure 8. Third Order Output Intercept Point versus Collector Voltage



Figure 9. Third Order Output Intercept Point versus Case Temperature



Figure 10. Third Order Intermodulation versus Output Power



NOTE: The MTTF is calculated with V_{CC} = 5 Vdc, I_{CC} = 90 mA

Figure 11. MTTF versus Junction Temperature



Figure 12. Noise Figure versus Frequency



Figure 13. Single-Carrier W-CDMA Adjacent Channel Power Ratio versus Output Power

50 OHM APPLICATION CIRCUIT: 40-800 MHz



Z1, Z5	0.347″ x 0.058″ Microstrip	Z4	0.403″ x 0.058″ Microstrip
Z2	0.575″ x 0.058″ Microstrip	PCB	Getek Grade ML200C, 0.031″, ε_r = 4.1
Z3	0.172″ x 0.058″ Microstrip		

Figure 14. 50 Ohm Test Circuit Schematic



Figure 15. S21, S11 and S22 versus Frequency



Figure 16. 50 Ohm Test Circuit Component Layout

Table 8. 50 Ohm Test Circuit Component Designations and Values

Part	Description	Part Number	Manufacturer
C1, C2	0.01 μF Chip Capacitors	0603A103JAT2A	AVX
C3	0.1 μF Chip Capacitor	0603A102JAT2A	AVX
C4	1 μF Chip Capacitor	0603A105JAT2A	AVX
L1	470 nH Chip Inductor	BK2125HM471	Taiyo Yuden
R1	0 Ω Chip Resistor	ERJ3GEY0R00V	Panasonic

50 OHM APPLICATION CIRCUIT: 800 - 3600 MHz



Z1, Z5	0.347″ x 0.058″ Microstrip	Z4	0.403″ x 0.058″ Microstrip
Z2	0.575″ x 0.058″ Microstrip	PCB	Getek Grade ML200C, 0.031″, ε_r = 4.1
Z3	0.172″ x 0.058″ Microstrip		

Figure 17. 50 Ohm Test Circuit Schematic



Figure 18. S21, S11 and S22 versus Frequency



Figure 19. 50 Ohm Test Circuit Component Layout

Table 9. 50 Ohm Test Circuit Component Designations and Values

Part	Description	Part Number	Manufacturer
C1, C2	150 pF Chip Capacitors	0603A151JAT2A	AVX
C3	0.1 μF Chip Capacitor	0603A102JAT2A	AVX
C4	1 μF Chip Capacitor	0603A105JAT2A	AVX
L1	56 nH Chip Inductor	HK160856NJ-T	Taiyo Yuden
R1	0 Ω Chip Resistor	ERJ3GEY0R00V	Panasonic

50 OHM TYPICAL CHARACTERISTICS

Table 10. Class A Common Emitter S-Parameters at V_{CC} = 5 Vdc, I_{CC} = 90 mA, T_C = 25°C

f	S_{11}		S_{21}		S_{12}		S_{22}	
GHz	$\|S_{11}\|$	$\angle\phi$	$\|S_{21}\|$	$\angle\phi$	$\|S_{12}\|$	$\angle\phi$	$\|S_{22}\|$	$\angle\phi$
0.1	0.162717	171.108	11.479238	174.775	0.069393	-1.296	0.106264	-133.221
0.15	0.160561	167.971	11.415032	171.459	0.069131	-1.887	0.112247	-134.322
0.2	0.160153	163.027	11.337210	168.606	0.068870	-2.702	0.118610	-135.449
0.25	0.157910	159.994	11.263950	165.874	0.068640	-3.308	0.127240	-136.522
0.3	0.155640	156.091	11.200930	163.101	0.068460	-3.908	0.134977	-137.648
0.35	0.152870	152.178	11.160790	160.282	0.068400	-4.523	0.144410	-138.763
0.4	0.150710	148.189	11.096270	157.597	0.068380	-5.134	0.154090	-139.895
0.45	0.148730	144.135	11.027770	154.845	0.068210	-5.794	0.164250	-140.998
0.5	0.145840	140.465	10.957540	152.097	0.068260	-6.391	0.174550	-142.085
0.55	0.143950	136.404	10.876040	149.449	0.068090	-6.918	0.185240	-143.132
0.6	0.141980	132.557	10.785240	146.811	0.068040	-7.57	0.195510	-144.211
0.65	0.140120	128.67	10.695820	144.176	0.068000	-8.199	0.206040	-145.338
0.7	0.138450	124.924	10.604510	141.59	0.067790	-8.743	0.216910	-146.461
0.75	0.137510	121.228	10.504830	139.003	0.067690	-9.285	0.227810	-147.659
0.8	0.136570	117.62	10.400340	136.446	0.067590	-9.831	0.238140	-148.902
0.85	0.134433	114.245	10.295550	133.89	0.067520	-10.415	0.248290	-150.118
0.9	0.132707	110.998	10.186390	131.409	0.067420	-10.866	0.258400	-151.55
0.95	0.131087	107.842	10.073620	128.963	0.067380	-11.449	0.268360	-153.097
1	0.129567	104.859	9.965510	126.525	0.067220	-11.901	0.277810	-154.786
1.05	0.128275	102.209	9.842290	124.132	0.067050	-12.399	0.287510	-156.435
1.1	0.127137	99.637	9.725320	121.744	0.066970	-12.949	0.297010	-158.367
1.15	0.125513	97.509	9.610100	119.381	0.066930	-13.483	0.306110	-160.411
1.2	0.124020	95.409	9.485500	117.045	0.066790	-13.882	0.314950	-162.397
1.25	0.122379	93.482	9.367530	114.76	0.066840	-14.46	0.323700	-164.386
1.3	0.121234	91.761	9.251560	112.507	0.066710	-14.928	0.332570	-166.443
1.35	0.120081	90.16	9.129800	110.251	0.066685	-15.375	0.339940	-168.554
1.4	0.118817	88.664	9.011610	108.055	0.066670	-15.818	0.348650	-170.582
1.45	0.116609	87.326	8.892430	105.876	0.066687	-16.365	0.356290	-172.695
1.5	0.115374	86.23	8.772640	103.703	0.066764	-16.815	0.360061	-174.724
1.55	0.113850	80.021	8.708890	101.399	0.066970	-17.493	0.364627	-177.374
1.6	0.113120	77.212	8.598320	99.278	0.067057	-17.963	0.369410	-179.169
1.65	0.112080	75.253	8.485180	97.137	0.067090	-18.477	0.374600	179.129
1.7	0.111350	72.833	8.379040	95.075	0.067170	-18.984	0.380650	177.406
1.75	0.110660	70.651	8.273700	93.021	0.067200	-19.462	0.386070	175.7
1.8	0.110070	68.704	8.167240	90.99	0.067260	-19.938	0.391590	174.044
1.85	0.109570	66.752	8.063390	88.942	0.067320	-20.42	0.396600	172.328
1.9	0.108940	64.808	7.958390	86.97	0.067420	-20.891	0.402290	170.798
1.95	0.107610	63.28	7.856150	84.972	0.067460	-21.389	0.407630	169.234
2	0.106800	61.916	7.751440	83.012	0.067560	-21.917	0.412720	167.75
2.05	0.106240	60.415	7.651320	81.047	0.067600	-22.347	0.418620	166.176
2.1	0.104410	59.082	7.553170	79.114	0.067810	-22.888	0.423200	164.723
2.15	0.103200	57.787	7.452840	77.223	0.067960	-23.444	0.428690	163.19
2.2	0.102820	56.94	7.354920	75.325	0.067980	-23.91	0.433410	161.75
2.25	0.101220	55.6	7.259510	73.436	0.068230	-24.487	0.438440	160.241
2.3	0.100260	54.54	7.163530	71.577	0.068190	-24.984	0.442830	158.869
2.35	0.098910	53.312	7.072340	69.734	0.068480	-25.485	0.447010	157.463

Table 10. Class A Common Emitter S-Parameters at V_{CC} = 5 Vdc, I_{CC} = 90 mA, T_C = 25°C (continued)

f	S_{11}		S_{21}		S_{12}		S_{22}	
GHz	$\|S_{11}\|$	$\angle\phi$	$\|S_{21}\|$	$\angle\phi$	$\|S_{12}\|$	$\angle\phi$	$\|S_{22}\|$	$\angle\phi$
2.4	0.097870	52.576	6.980770	67.882	0.068550	-26.108	0.451420	155.974
2.45	0.096530	51.814	6.892310	66.059	0.068780	-26.694	0.457800	154.6
2.5	0.095360	50.69	6.802480	64.259	0.068940	-27.154	0.460110	153.074
2.55	0.094140	49.939	6.719330	62.461	0.069120	-27.644	0.464930	151.617
2.6	0.093150	49.177	6.634260	60.65	0.069290	-28.295	0.469350	150.014
2.65	0.092180	48.019	6.554070	58.859	0.069490	-28.971	0.473140	148.442
2.7	0.091130	47.141	6.471630	57.062	0.069610	-29.561	0.477010	146.825
2.75	0.090470	46.394	6.392370	55.299	0.069850	-30.111	0.481850	145.214
2.8	0.089850	45.454	6.314980	53.505	0.070210	-30.649	0.485260	143.56
2.85	0.088790	44.657	6.238550	51.724	0.070340	-31.402	0.489440	141.782
2.9	0.088180	44.083	6.166300	50.021	0.070550	-32.044	0.494180	140.078
2.95	0.087640	43.291	6.088480	48.207	0.070750	-32.738	0.497180	138.23
3	0.086490	42.549	6.020040	46.489	0.071030	-33.388	0.501590	136.357
3.05	0.087170	42.041	5.950380	44.764	0.071280	-34.097	0.505070	134.738
3.1	0.086660	41.37	5.881680	43.022	0.071610	-34.666	0.509400	132.754
3.15	0.086130	41.387	5.814190	41.268	0.071920	-35.528	0.514040	130.875
3.2	0.086330	41.301	5.749680	39.547	0.072150	-36.302	0.518490	128.954
3.25	0.086760	41.239	5.684930	37.829	0.072340	-36.943	0.523620	126.955
3.3	0.086510	41.638	5.619060	36.098	0.072640	-37.799	0.525880	124.995
3.35	0.086820	41.81	5.557890	34.368	0.072800	-38.546	0.530230	123.081
3.4	0.087230	42.12	5.498110	32.629	0.073130	-39.319	0.534740	121.057
3.45	0.087680	42.727	5.437290	30.936	0.073490	-40.144	0.538080	119.195
3.5	0.087990	43.424	5.376810	29.22	0.073710	-40.92	0.542580	117.253
3.55	0.088730	44.082	5.319060	27.529	0.073970	-41.673	0.546650	115.36
3.6	0.089200	45.12	5.259990	25.838	0.074200	-42.467	0.550400	113.481



Recommended Solder Stencil

NOTES:
1. THERMAL AND RF GROUNDING CONSIDERATIONS SHOULD BE USED IN PCB LAYOUT DESIGN.
2. DEPENDING ON PCB DESIGN RULES, AS MANY VIAS AS POSSIBLE SHOULD BE PLACED ON THE LANDING PATTERN.
3. IF VIAS CANNOT BE PLACED ON THE LANDING PATTERN, THEN AS MANY VIAS AS POSSIBLE SHOULD BE PLACED AS CLOSE TO THE LANDING PATTERN AS POSSIBLE FOR OPTIMAL THERMAL AND RF PERFORMANCE.
4. RECOMMENDED VIA PATTERN SHOWN HAS 0.381 x 0.762 MM PITCH.

Figure 20. Recommended Mounting Configuration

PACKAGE DIMENSIONS



NOTES:
1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.
2. ALL DIMENSIONS ARE IN MILLIMETERS.
3. DIMENSION DOES NOT INCLUDE MOLD FLASH, PROTRUSIONS OR GATE BURRS. MOLD FLASH, PROTRUSIONS OR GATE BURRS SHALL NOT EXCEED 0.5MM PER END. DIMENSION DOES NOT INCLUDE INTERLEAD FLASH OR PROTRUSION. INTERLEAD FLASH OR PROTRUSION SHALL NOT EXCEED 0.5MM PER SIDE.
4. DIMENSIONS ARE DETERMINED AT THE OUTMOST EXTREMES OF THE PLASTIC BODY EXCLUSIVE OF MOLD FLASH, TIE BAR BURRS, GATE BURRS AND INTERLEAD FLASH, BUT INCLUDING ANY MISMATCH BETWEEN THE TOP AND BOTTOM OF THE PLASTIC BODY.
5. TERMINAL NUMBERS ARE SHOWN FOR REFERENCE ONLY.





BOTTOM VIEW

STYLE 1:
PIN 1. RF INPUT
2. GROUND
3. RF OUTPUT

CASE 1514-01
ISSUE C
SOT-89
PLASTIC

How to Reach Us:

Home Page:
www.freescale.com

E-mail:
support@freescale.com

USA/Europe or Locations Not Listed:
Freescale Semiconductor
Technical Information Center, CH370
1300 N. Alma School Road
Chandler, Arizona 85224
+1-800-521-6274 or +1-480-768-2130
support@freescale.com

Europe, Middle East, and Africa:
Freescale Halbleiter Deutschland GmbH
Technical Information Center
Schatzbogen 7
81829 Muenchen, Germany
+44 1296 380 456 (English)
+46 8 52200080 (English)
+49 89 92103 559 (German)
+33 1 69 35 48 48 (French)
support@freescale.com

Japan:
Freescale Semiconductor Japan Ltd.
Headquarters
ARCO Tower 15F
1-8-1, Shimo-Meguro, Meguro-ku,
Tokyo 153-0064
Japan
0120 191014 or +81 3 5437 9125
support.japan@freescale.com

Asia/Pacific:
Freescale Semiconductor Hong Kong Ltd.
Technical Information Center
2 Dai King Street
Tai Po Industrial Estate
Tai Po, N.T., Hong Kong
+800 2666 8080
support.asia@freescale.com

For Literature Requests Only:
Freescale Semiconductor Literature Distribution Center
P.O. Box 5405
Denver, Colorado 80217
1-800-441-2447 or 303-675-2140
Fax: 303-675-2150
LDCForFreescaleSemiconductor@hibbertgroup.com

RoHS-compliant and/or Pb- free versions of Freescale products have the functionality and electrical characteristics of their non-RoHS-compliant and/or non-Pb- free counterparts. For further information, see http://www.freescale.com or contact your Freescale sales representative.

For information on Freescale.s Environmental Products program, go to http://www.freescale.com/epp.

Information in this document is provided solely to enable system and software implementers to use Freescale Semiconductor products. There are no express or implied copyright licenses granted hereunder to design or fabricate any integrated circuits or integrated circuits based on the information in this document.

Freescale Semiconductor reserves the right to make changes without further notice to any products herein. Freescale Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does Freescale Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation consequential or incidental damages. “Typical” parameters that may be provided in Freescale Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including “Typicals”, must be validated for each customer application by customer’s technical experts. Freescale Semiconductor does not convey any license under its patent rights nor the rights of others. Freescale Semiconductor products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the Freescale Semiconductor product could create a situation where personal injury or death may occur. Should Buyer purchase or use Freescale Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold Freescale Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that Freescale Semiconductor was negligent regarding the design or manufacture of the part.

Freescale™ and the Freescale logo are trademarks of Freescale Semiconductor, Inc. All other product or service names are the property of their respective owners.
© Freescale Semiconductor, Inc. 2005. All rights reserved.

freescale™
semiconductor

Document Number: MMG3013NT1
Rev. 2, 8/2005