Extract from the online catalog

VS-PPC-F1-RJ45-P0BK-1R-PHA

Order No.: 1657847



http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1657847

RJ45 panel mounting frame, IP67, for push-pull interlocking, plastic, for PCB connection, for square panel cutout, with grommet, without mounting screws

Product notes

WEEE/RoHS-compliant since: 01/01/2008

http://www.download.phoenixcontact.com
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Commercial data

GTIN (EAN)	4 046356 131919
sales group	D510
Pack	1 pcs.
Customs tariff	85366990
Catalog page information	Page 195 (PC-2009)

Technical data

Mechanical characteristics

Insertion/withdrawal cycles	≥ 500
Color	black
Ambient temperature (operation)	-40 °C ... 70 °C

Material data	
Inflammability class acc. to UL 94	V0
Housing material	PA-GF
Material	Plastic
Sealing material	NBR
Seal material	NBR
Degree of protection	IP65/67

Electrical characteristics	
Pollution degree	2


Accessories

Item	Designation	Description
Female insert		
1653087	VS-08-BU-RJ45-6/LH-1	RJ45 socket insert, for PCB assembly, CAT6, 8-pos., shielded, with angled solder pins, 1x
1653090	VS-08-BU-RJ45-6/LV-1	RJ45 socket insert, for PCB assembly, CAT6, 8-pos., shielded, with straight solder pins, 1x


Diagrams/Drawings

Drilling plan/solder pad geometry


Drilling diagram



Dimensioned drawing



Push-Pull panel mounting frame RJ45



Panel cutout

Address

PHOENIX CONTACT Deutschland GmbH
Flachsmarktstr. 8
32825 Blomberg,Germany
Phone +49 5235 3 12000
Fax +49 5235 3 41200
http://www.phoenixcontact.de



© 2011 Phoenix Contact
Technical modifications reserved;