PASTERNACK®
www.pasternack.com

75 Ohm F Female Connector Solder Attachment 4 Hole Flange Pin Terminal, .500 inch Hole Spacing



TECHNICAL DATA SHEET PE44329

75 Ohm F Female Connector Solder Attachment 4 Hole Flange Pin Terminal, .500 inch Hole Spacing

Configuration

Connector	F Female
Connector Interface Type	Pin
Cable Attachment Method (Shield/Contact)	Solder
Body Style	Straight
Mount Method	4 Hole Flange

Electrical Specifications

Frequency Range, MHz	DC to 1,000
Impedance, Ohms	75

Mechanical Specifications

Temperature

Operating Range, deg C	-65 to +165

Size

Length, in [mm]	1.03 [26.16]
Width/Dia., in [mm]	0.69 [18]
Height, in [mm]	0.69 [17.53]
Weight, lbs [g]	0.11 [49.9]

Connector

Type	F Female
Contact Material and Plating	Brass, Gold
Contact Plating Specification	30µ in. minumum
Body Material and Plating	Brass, Nickel
Body Plating Specification	100µ in. minumum
Dielectric Type	Teflon

Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant	Yes

Plotted and Other Data

Notes:	Values at 25 °C, sea level

Click the following link (or enter part number in “SEARCH” on website) to obtain additional part information including price, inventory and certifications: 75 Ohm F Female Connector Solder Attachment 4 Hole Flange Pin Terminal, .500 inch Hole Spacing PE44329

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623
Phone: (866) 727-8376 or (949) 261-1920 • **Fax:** (949) 261-7451
Sales@Pasternack.com • Techsupport@Pasternack.com

ISO 9001 : 2008 Registered

© 2013 Pasternack Enterprises All Rights Reserved

PASTERNACK®
www.pasternack.com

75 Ohm F Female Connector Solder Attachment 4 Hole Flange Pin Terminal, .500 inch Hole Spacing



TECHNICAL DATA SHEET PE44329

75 Ohm F Female Connector Solder Attachment 4 Hole Flange Pin Terminal, .500 inch Hole Spacing from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in “SEARCH” on website) to obtain additional part information including price, inventory and certifications: 75 Ohm F Female Connector Solder Attachment 4 Hole Flange Pin Terminal, .500 inch Hole Spacing PE44329

URL: http://www.pasternack.com/f-female-standard-pin-terminal-connector-pe44329-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.


Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623
Phone: (866) 727-8376 or (949) 261-1920 • **Fax:** (949) 261-7451
Sales@Pasternack.com • Techsupport@Pasternack.com

ISO 9001 : 2008 Registered

© 2013 Pasternack Enterprises All Rights Reserved

PE44329 CAD Drawing

75 Ohm F Female Connector Solder Attachment 4 Hole
Flange Pin Terminal, .500 inch Hole Spacing



NOTES:
1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.
3. DIMENSIONS ARE IN INCHES [mm].
4. FITS MIL-C-17 AND EQUIVALENT CABLES.

CAD FILE	SCALE	SIZE	
062211-B	N/A	A	2233

DWG TITLE **PE44329**

FSCM NO. 53919

PASTERNACK®
Pasternack Enterprises, Inc.
P.O. Box 16759 | Irvine | CA | 92623
Phone: (949) 261-1920 | **Fax:** (949) 261-7451
Website: www.pasternack.com | **E-Mail:** sales@pasternack.com

© 2013 Pasternack Enterprises All Rights Reserved