



- NOTES:
1. ALL DIMENSIONS IN MM [INCH]
 2. GENERAL TOLERANCE: X.X=± 0.4
X.XX=± 0.25
 3. ELECTRICAL LIFE: 6,000 [cURus]
10,000 [VDE]
 4. CONTACT RESISTANCE: 20 mΩ MAX. INITIAL
 5. INSULATION RESISTANCE: 100 MΩ AT 500VDC
 6. OPERATING TEMPERATURE: -20°C TO +65°C [cURus]
-20°C TO +125°C [VDE]
 7. CONTACT RATING: 16A, 125VAC-250VAC, [cURus]
16(4)A, 250VAC, 1E4 T125/55[VDE]
 8. DIELECTRIC STRENGTH: 1000V FOR 1 MINUTE
 9. ACTUATION FORCE: 500 +/- 200 g
 10. TRAVEL:
TO LOCK POSITION: 3.0mm
FULL TRAVEL: 5.0mm
 11. ▲ DENOTES CRITICAL PARAMETER
 12. 2002/95/EC (RoHS) COMPLIANT.
 - ▲13. PLASTIC COMPONENTS TO BE UL94-V0 RATED



TITLE PA5FN11CV0

B	21532	Housing change to locking tab	7/25/14	rc
REV	PCR NO	DESCRIPTION	DATE	BY

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED

SCALE	DATE	DR	DWG	REV
1.5	7/25/2014	rc	14-PA5FN11C-V0	B