60 Watt Universal 2-Wire Input Adapter



Features

- Low Cost
- DOE Level VI Compliant
- Class B EMI
- Ecodesign ErP Directive 2009/125/EC Compliant
- Non-vented/Spill-proof Case
- No Load Power consumption 150mW max
- Low Profile Design
- Limited Power Source

Applications

- Portable Equipment
- Peripherals
- Networking
- Gaming Machines

Safety Approvals

- cUL/UL
- CB
- CE

Mechanical Characteristics

- Length: 130mm (5.12in)
- Width: 60mm (2.36in)
- Height: 32mm (1.30in)
- Weight: 305g (10.76oz)

Output Specifications

Model	DC Output Voltage	Load		Ripple [1] P-P (max.)	Regulation Line & Load
		Min.	Max.		
PSAC60W-120	+12V	0A	5.0A	200mV	±5%
PSAC60W-180	+18V	0A	3.33A	180mV	±5%
PSAC60W-240	+24V	0A	2.5A	350mV	±5%
PSAC60W-480	+48V	0A	1.25A	480mV	±5%
PSAC60W-560	+56V	0A	1.08A	560mV	±5%

(1) Measured with a 10uF capacitor and a 0.1uF capacitor at output connector terminal and oscilloscope set at 20MHz.

Phihong is not responsible for any error, and reserves the right to make changes without notice. Please visit our website at www.phihong.com for the most up-to-date specifications and contact information.

PSAC60W Characteristics WWW.PHIHONG.COM

Input:

AC Input Voltage Rating
100 to 240V AC

AC Input Frequency
47 to 63Hz

Input Current
1.5A at 120V AC

Leakage Current
0.25mA maximum at 254V AC and 60Hz

Inrush Current
90A maximum at 100V AC
150A maximum at 240V AC

Input Power Saving
150mW max

Output:

Output Power
60W

Efficiency
DOE Level VI

Environmental:

Temperature

Operation	0 to +40℃
Non-operation	-20 to +70℃
Humidity	5 to 90%

Emissions
FCC Class B
EN55022 Class B

Immunity

IEC61000-4-2	Level 4
IEC61000-4-5	Level 3

Over-Voltage Protection
Latch off

Over-Current Protection
Auto-restart

Short-Circuit Protection
Output can be shorted permanently without damage

Isolation
>7M OHM

Dielectric Withstand (Hi-pot) Test
Primary to Secondary: 3000V AC for 1 min., 10mA

DC Output Connector
2.1mm x 5.5mm x 9.5mm Center Positive Barrel

Dimension Diagram Unit: mm (inch)

