

High Sensitivity Hall Effect Sensor Latch IC

Features

- On-Chip Hall Sensor
- Wide Operating Voltage Range: 2.2V to 24V
- Low Operating Supply Current
- Built-in Pull-up Resistor
- High Sensitivity Hall Effect Sensor IC: $\pm 60\text{G}$
- 3 Pin SOT-23 Package
- Lead Free and Green Devices Available (RoHS Compliant)


Applications

- Brushless DC Motor
- Brushless DC Fan
- Revolution Counting
- Speed Measurement


General Description

The APX9137A is an integrated Hall-Effect sensor latch IC designed for electric commutation of three-phase Brushless DC motor applications. The APX9137A is available in a low cost SOT-23-3 package.

Pin Configuration



Simplified Application Circuit



Ordering and Marking Information

<p>APX9137A □□-□□□</p> <p>└─ Assembly Material</p> <p>└─ Handling Code</p> <p>└─ Temperature Range</p> <p>└─ Package Code</p>	<p>Package Code A : SOT-23-3 Temperature Range I : -40 to 150 °C Handling Code TR : Tape & Reel Assembly Material G : Halogen and Lead Free Device</p>
<p>APX9137A A: A37X</p>	<p>X - Date Code</p>

Note: ANPEC lead-free products contain molding compounds/die attach materials and 100% matte tin plate termination finish; which are fully compliant with RoHS. ANPEC lead-free products meet or exceed the lead-free requirements of IPC/JEDEC J-STD-020D for MSL classification at lead-free peak reflow temperature. ANPEC defines "Green" to mean lead-free (RoHS compliant) and halogen free (Br or Cl does not exceed 900ppm by weight in homogeneous material and total of Br and Cl does not exceed 1500ppm by weight).

ANPEC reserves the right to make changes to improve reliability or manufacturability without notice, and advise customers to obtain the latest version of relevant information to verify before placing orders.

Absolute Maximum Ratings (Note 1)

Symbol	Parameter	Rating	Unit
V _{DD}	VDD Pin Supply Voltage	-0.3 to 28	V
V _{OUT}	Output Pin Output Voltage	-0.3 to 28	V
I _{OUT}	Maximum Output Pin Sink Current	50	mA
T _J	Maximum Junction Temperature	150	°C
T _{STG}	Storage Temperature	-65 to 150	°C
T _{SOR}	Maximum Lead Soldering Temperature, 10 Seconds	260	°C

Note 1: Absolute Maximum Ratings are those values beyond which the life of a device may be impaired. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

Thermal Characteristics

Symbol	Parameter	Typical Value	Unit
θ_{JA}	Thermal Resistance-Junction to Ambient ^(Note 2) SOT-23-3	385	°C/W
P _D	Power Dissipation, T _A = 25°C SOT-23-3	350	mW

Note 2: The maximum allowable power dissipation at any T_A (ambient temperature) is calculated using: P_D(max) = (T_J - T_A) / θ_{JA} ; T_J=160°C. Exceeding the maximum allowable power dissipation will result in excessive die temperature.

Recommended Operation Conditions

Symbol	Parameter	Range	Unit
V _{DD}	VDD Supply Voltage	2.2 to 24	V
T _A	Operating Ambient Temperature	-40 to 150	°C
T _J	Junction Temperature	-40 to 150	°C



Electrical Characteristics (T_A = 25°C, V_{DD} = 24V, unless otherwise noted)

Symbol	Parameter	Test Conditions	APX9137A			Unit
			Min.	Typ.	Max.	
I _{DD}	VDD Supply Current	V _{DD} =24V, Output Off	-	3	5	mA
V _{SAT}	Output Saturation Voltage	B > Bop, I _{OUT} = 20mA	-	0.2	0.4	V
I _{LEAK}	OUT Pin Leakage Current	B < Brp, V _{OUT} = V _{DD}	-	-	0.1	μA
R _{PULL}	Output Pull-up Resistor		6	-	14	kΩ



Magnetic Characteristics ($T_A = 25^\circ\text{C}$, $V_{DD} = 24\text{V}$, unless otherwise noted)

Symbol	Parameter	Test Conditions	APX9137A			Unit
			Min.	Typ.	Max.	
Bop	Magnetic Operation Point		10	30	60	Gauss
Brp	Magnetic Release Point		-60	-30	-10	Gauss
Bhys	Magnetic Hysteresis		-	60	-	Gauss

Bops




Brps




Typical Operating Characteristics


VDD Supply Current vs. VDD Supply Voltage




Output Saturation Voltage vs. Output Current




Magnetic Switching Points vs. VDD Supply Voltage



Magnetic Switching Points vs. Junction Temperature




Maximum Power Dissipation vs. Ambient Temperature




Pin Description

PIN		Function
NO.	NAME	
1	VDD	Supply Voltage Input.
2	GND	Ground of the IC.
3	OUT	Output Stage.

Block Diagram




Typical Application Circuit



Package Information


SOT-23-3



SYMBOL	SOT-23			
	MILLIMETERS		INCHES	
	MIN.	MAX.	MIN.	MAX.
A		1.45		0.057
A1	0.00	0.15	0.000	0.006
A2	0.90	1.30	0.035	0.051
b	0.30	0.50	0.012	0.020
c	0.08	0.22	0.003	0.009
D	2.70	3.10	0.106	0.122
E	2.60	3.00	0.102	0.118
E1	1.40	1.80	0.055	0.071
e	0.95 BSC		0.037 BSC	
e1	1.90 BSC		0.075 BSC	
L	0.30	0.60	0.012	0.024
θ	0°	8°	0°	8°

Note : 1. Dimension D and E1 do not include mold flash, protrusions or gate burrs. Mold flash, protrusion or gate burrs shall not exceed 10 mil per side.

Carrier Tape & Reel Dimensions



Application	A	H	T1	C	d	D	W	E1	F
SOT-23-3	178.0±2.00	50 MIN.	8.4+2.00 -0.00	13.0+0.50 -0.20	1.5 MIN.	20.2 MIN.	8.0±0.30	1.75±0.10	3.5±0.05
	P0	P1	P2	D0	D1	T	A0	B0	K0
	4.0±0.10	4.0±0.10	2.0±0.05	1.5+0.10 -0.00	1.0 MIN.	0.6+0.00 -0.40	3.20±0.20	3.10±0.20	1.50±0.20


(mm)

Devices Per Unit


Package Type	Unit	Quantity
SOT-23-3	Tape & Reel	3000

Taping Direction Information

SOT-23-3



Classification Profile



Classification Reflow Profiles

Profile Feature	Sn-Pb Eutectic Assembly	Pb-Free Assembly
Preheat & Soak Temperature min (T_{smin}) Temperature max (T_{smax}) Time (T_{smin} to T_{smax}) (t_s)	100 °C 150 °C 60-120 seconds	150 °C 200 °C 60-120 seconds
Average ramp-up rate (T_{smax} to T_p)	3 °C/second max.	3 °C/second max.
Liquidous temperature (T_L) Time at liquidous (t_L)	183 °C 60-150 seconds	217 °C 60-150 seconds
Peak package body Temperature (T_p)*	See Classification Temp in table 1	See Classification Temp in table 2
Time (t_p)** within 5°C of the specified classification temperature (T_c)	20** seconds	30** seconds
Average ramp-down rate (T_p to T_{smax})	6 °C/second max.	6 °C/second max.
Time 25°C to peak temperature	6 minutes max.	8 minutes max.
* Tolerance for peak profile Temperature (T_p) is defined as a supplier minimum and a user maximum. ** Tolerance for time at peak profile temperature (t_p) is defined as a supplier minimum and a user maximum.		

Table 1. SnPb Eutectic Process – Classification Temperatures (T_c)

Package Thickness	Volume mm ³ <350	Volume mm ³ ≥350
<2.5 mm	235 °C	220 °C
≥2.5 mm	220 °C	220 °C

Table 2. Pb-free Process – Classification Temperatures (T_c)

Package Thickness	Volume mm ³ <350	Volume mm ³ 350-2000	Volume mm ³ >2000
<1.6 mm	260 °C	260 °C	260 °C
1.6 mm – 2.5 mm	260 °C	250 °C	245 °C
≥2.5 mm	250 °C	245 °C	245 °C

Reliability Test Program

Test item	Method	Description
SOLDERABILITY	JESD-22, B102	5 Sec, 245°C
HOLT	JESD-22, A108	1000 Hrs, Bias @ $T_j=125^{\circ}\text{C}$
PCT	JESD-22, A102	168 Hrs, 100%RH, 2atm, 121°C
TCT	JESD-22, A104	500 Cycles, -65°C~150°C
HBM	MIL-STD-883-3015.7	VHBM ≥ 2KV
MM	JESD-22, A115	VMM ≥ 200V
Latch-Up	JESD 78	10ms, $1_{tr} \geq 100\text{mA}$

Customer Service

Anpec Electronics Corp.

Head Office :

No.6, Dusing 1st Road, SBIP,
Hsin-Chu, Taiwan
Tel : 886-3-5642000
Fax : 886-3-5642050

Taipei Branch :

2F, No. 11, Lane 218, Sec 2 Jhongsing Rd.,
Sindian City, Taipei County 23146, Taiwan
Tel : 886-2-2910-3838
Fax : 886-2-2917-3838