P-tec Corp. **Tel:(866) 695 4162**
2405 Commerce Circle **Tel:(719) 589 3122**
Alamosa CO 81101 **Fax:(719) 589 3592**
www.p-tec.net

PL103 Series 1.8mm Miniature Tri-Level LED Holder

Features

*Miniature Tri-Level LED Holder, Right Angled
*Space saving Circuit Board Indicator
*High Light Output
*Housing Material Black Nylon UL94V-2
*3 Yellow LEDs with Color Diffused Lens used
*Color Arranged from Top to Bottom
*RoHS Compliant

Absolute Maximum Ratings at T_A = 25°C

Power Dissipation	78mW
Reverse Voltage (<100 µA)	5.0V
Max Forward Current	30mA
Peak Forward Current (1/10 Duty Cycle, 0.1ms Pulse Width)	100mA
Operating Temperature Range	-25°C to +85°C
Storage Temperature Range	-40°C to +100°C
Soldering Temperature (1.6 mm below body)	260°C for 5 seconds

Electrical & Optical Characteristics at T_A = 25°C

Part Number	Emitting Color	Chip Material	Peak Wave Length	Dominant Wave Length	Viewing Angle 2θ ½	Forward Voltage @20mA (V)		Luminous Intensity @20mA (mcd)	
Color Diffused Lens			nm	nm	Deg	Typ	Max	Min	Typ
PL103-3Y01	Yellow	GaAsP	585	590	30°	2.1	2.6	20.0	37.0

All dimensions are in **Millimeters**. Tolerance is ± 0.5mm unless otherwise specified.

