

SERIES 45L(R), 150K/ KS(R)

STANDARD RECOVERY DIODES

Stud Version

Features

- Alloy diode
- High current carrying capability
- High surge current capabilities
- Stud cathode and stud anode version



150A

Typical Applications

- Battery charges
- Welders
- Machine tool controls
- High power drives
- Medium traction applications
- Freewheeling diodes

Major Ratings and Characteristics

Parameters	45L /150K	Units
$I_{F(AV)}$	150	A
@ T_C	150	°C
$I_{F(RMS)}$	235	A
I_{FSM} @ 50Hz	3570	A
@ 60Hz	3740	A
I^2t @ 50Hz	64	KA ² s
@ 60Hz	58	KA ² s
V_{RRM} range	100 to 600	V
T_J	- 40 to 200	°C



NJ Semi-Conductors reserves the right to change test conditions, parameter limits and package dimensions without notice. Information furnished by NJ Semi-Conductors is believed to be both accurate and reliable at the time of going to press. However, NJ Semi-Conductors assumes no responsibility for any errors or omissions discovered in its use. NJ Semi-Conductors encourages customers to verify that datasheets are current before placing orders.

Quality Semi-Conductors

ELECTRICAL SPECIFICATIONS

Voltage Ratings

Type number	Voltage Code	V_{RRM} : maximum repetitive peak reverse voltage V	V_{RSM} : maximum non-repetitive peak rev. voltage V	I_{RRM} max. @ $T_J = 175^\circ\text{C}$ mA
45L(R) 150K(R) 150KS(R)	10	100	200	35
	20	200	300	
	30	300	400	
	40	400	500	
	60	600	720	

Forward Conduction

Parameter	45L/150K	Units	Conditions
$I_{F(AV)}$ Max. average forward current @ Case temperature	150 150	A °C	180° conduction, half sine wave
$I_{F(RMS)}$ Max. RMS forward current	235	A	DC @ 142°C case temperature
I_{FSM} Max. peak, one-cycle forward, non-repetitive surge current	3570	A	$t = 10\text{ms}$ No voltage
	3740		$t = 8.3\text{ms}$ reapplied
	3000		$t = 10\text{ms}$ 100% V_{RRM}
	3140		$t = 8.3\text{ms}$ reapplied
P_t Maximum P_t for fusing	64	KA ² s	$t = 10\text{ms}$ No voltage
	58		$t = 8.3\text{ms}$ reapplied
	45		$t = 10\text{ms}$ 100% V_{RRM}
	41		$t = 8.3\text{ms}$ reapplied
$P_{\Sigma t}$ Maximum $P_{\Sigma t}$ for fusing	640	KA ² s	$t = 0.1$ to 10ms, no voltage reapplied
$V_{F(TO)1}$ Low level value of threshold voltage	0.67	V	$(16.7\% \times \pi \times I_{F(AV)}) < I < \pi \times I_{F(AV)}$, $T_J = T_{J \text{ max.}}$
$V_{F(TO)2}$ High level value of threshold voltage	0.83		$I > \pi \times I_{F(AV)}$, $T_J = T_{J \text{ max.}}$
r_{f1} Low level value of forward slope resistance	1.42	mΩ	$(16.7\% \times \pi \times I_{F(AV)}) < I < \pi \times I_{F(AV)}$, $T_J = T_{J \text{ max.}}$
r_{f2} High level value of forward slope resistance	0.91		$I > \pi \times I_{F(AV)}$, $T_J = T_{J \text{ max.}}$
V_{FM} Max. forward voltage drop	1.33	V	$I_{pk} = 471\text{A}$, $T_J = 25^\circ\text{C}$, $t_p = 10\text{ms}$ sinusoidal wave

Thermal and Mechanical Specifications

Parameter			45L /150K	Units	Conditions
T_J	Max. junction operating temperature range		-40 to 200	°C	
T_{stg}	Max. storage temperature range		-40 to 200		
R_{thJC}	Max. thermal resistance, junction to case		0.25	K/W	DC operation
R_{thCS}	Max. thermal resistance, case to heatsink		0.10		Mounting surface, smooth, flat and greased
T	Mounting torque 45L	Min.	14.1 (125)	Nm (lbf-in)	Not lubricated threads
		Max.	17.0 (150)		
		Min.	12.2 (108)		Lubricated threads
		Max.	15.0 (132)		
	150K	Min.	11.3 (100)	Nm (lbf-in)	Not lubricated threads
		Max.	14.1 (125)		
	150KS	Min.	9.5 (85)		Lubricated threads
		Max.	12.5 (110)		
wt	Approximate weight		100 (3.5)	g (oz)	
Case style	45L	DO-205AC (DO-30)		See Outline Table	
	150K-A	DO-205AA (DO-8)			
	150KS	B-42			


ΔR_{thJC} Conduction

(The following table shows the increment of thermal resistance R_{thJC} when devices operate at different conduction angles than DC)

Conduction angle	Sinusoidal conduction	Rectangular conduction	Units	Conditions
180°	0.031	0.023	K/W	$T_j = T_{j \text{ max}}$
120°	0.038	0.040		
90°	0.048	0.053		
60°	0.071	0.075		
30°	0.120	0.121		

Ordering Information Table


Device Code



- 1 - 45 = Standard version
- 2 - L = Essential Part Number
- 3 - R = Stud Reverse Polarity (Anode to Stud)
None = Stud Normal Polarity (Cathode to Stud)
- 4 - Voltage code: Code x 10 = V_{RRM} (See Voltage Ratings table)

Ordering Information Table


Device Code



- 1 - 15 = Essential Part Number
- 2 - 0 = Standard Device
- 3 - Case Style
K = DO205AA (DO-8)
KS = B-42
- 4 - R = Stud Reverse Polarity (Anode to Stud)
None = Stud Normal Polarity (Cathode to Stud)
- 5 - Voltage code: Code x 10 = V_{RRM} (See Voltage Ratings table)
- 6 - A = Essential Part Number for 150K (Omitted for 150KS)

NOTE: For Metric Device M12 x 1.75 Contact Factory

Outline Table



45L
Case Style
DO-205AC (DO-30)

All dimensions in millimeters (inches)

Outline Table

