




Model Number

20FR1-6B

Features

- Magnetically actuated reed switch
- Hermetically sealed contacts
- Heavy duty Aluminum housings

Connection




Accessories


21FR1-B
Magnetic actuator

Dimensions

20FR



Mounting bracket (included)



Technical Data

General specifications

Switching element function		Reed Contact Normally Open
Rated operating distance	s_n	61 mm
Installation		not embeddable
Output polarity		Relay output
Mechanical life		1×10^7 switching cycles

Nominal ratings

Operating voltage	U_B	250 V DC, 1.0 A max, 15 W
Hysteresis	H	15.2 mm
Release point		$\leq \leq 76$ mm

Ambient conditions

Ambient temperature		-25 ... 85 °C (-13 ... 185 °F)
---------------------	--	--------------------------------

Mechanical specifications

Connection type		cable PVC, 1.83 m
Core cross-section		16 AWG
Housing material		aluminium
Sensing face		aluminium
Protection degree		IP68
Material		
Activation target		21FR1-B

Temperature Effects

Temperature must be taken into consideration when using magnetically operated switches. The sensing ranges given on the following pages are for head-on operations at room temperature (75° F). Sub-zero temperatures can cause permanently reduced sensitivity. Use the following table as a guide for potential sensitivity loss.

Model	Maximum possible sensitivity loss
20FR1-6B	2.03 mm
20FR3-6B	1.52 mm
20FR4-6B	1.52 mm
20FR5-6B	4.95 mm

Release date: 2010-05-25 21:38 Date of issue: 2010-06-14 450010_ENG.xml