

Surface Mount PTC

0ZCC Series

1812 Chip
RoHS6 Compliant & Halogen-Free



Application

All high-density boards

Product Features

1812 Chip Size, Fast Trip Time, Low DCR Resistance

Operating (Hold Current) Range

140mA ~ 3A

Maximum Voltage

6V ~ 60V (per table)

Temperature Range

-40°C to 85°C

Agency Approval


TiLV (Std. FNA0738-1.1 Part R50102187 R50102117)

UL Component (Std. UL1434, File E305051)

UL Conditions of Acceptability:

- These devices have been investigated for use in safety circuits and are suitable as a limiting device.
- These devices have been calibrated to limit the current to 8 amps within 5 seconds, per ANSI/NFPA 70, "National Electrical Code"

Product Dimensions



Part Number	Fig.	A Min	A Max	B Min	B Max	C Min	C Max	D Min	D Max	E Min	E Max
0ZCC0014FF2C Thru 0ZCC0075FF2C	1	4.37	4.73	3.07	3.41	0.35	0.90	0.30	0.95	----	----
0ZCC0075AF2B	2	4.37	4.73	3.07	3.41	0.80	1.55	0.25	0.95	0.25	0.65
0ZCC0075BF2B	2	4.37	4.73	3.07	3.41	0.80	1.55	0.25	0.95	0.25	0.65
0ZCC0110FF2C	1	4.37	4.73	3.07	3.41	0.25	0.55	0.30	0.95	----	----
0ZCC0110AF2C	1	4.37	4.73	3.07	3.41	0.25	0.90	0.30	0.95	----	----
0ZCC0110BF2B	2	4.37	4.73	3.07	3.41	0.80	1.30	0.25	0.95	0.25	0.65
0ZCC0125FF2C	1	4.37	4.73	3.07	3.41	0.25	0.55	0.30	0.95	----	----
0ZCC0150FF2C	1	4.37	4.73	3.07	3.41	0.25	0.55	0.30	0.95	----	----
0ZCC0150AF2C	2	4.37	4.73	3.07	3.41	0.60	1.10	0.25	0.95	0.25	0.65
0ZCC0150BF2C	2	4.37	4.73	3.07	3.41	0.60	1.55	0.25	0.95	0.25	0.65
0ZCC0160FF2C	1	4.37	4.73	3.07	3.41	0.25	0.90	0.30	0.95	----	----
0ZCC0160AF2C	2	4.37	4.73	3.07	3.41	0.60	1.35	0.25	0.95	0.25	0.65
0ZCC0160BF2C	2	4.37	4.73	3.07	3.41	0.60	1.35	0.25	0.95	0.25	0.65
0ZCC0200FF2C	2	4.37	4.73	3.07	3.41	0.55	1.20	0.25	0.95	0.25	0.65
0ZCC0260FF2C	2	4.37	4.73	3.07	3.41	0.55	1.20	0.25	0.95	0.25	0.65
0ZCC0260AF2B	2	4.37	4.73	3.07	3.41	0.80	1.55	0.25	0.95	0.25	0.65
0ZCC0260BF2B	2	4.37	4.73	3.07	3.41	0.80	1.55	0.25	0.95	0.25	0.65
0ZCC0300FF2B	2	4.37	4.73	3.07	3.41	0.80	1.55	0.25	0.95	0.25	0.65

Standard Package & Marking

Part Number	Reel/Tape	"b" code	1H code
0ZCC0014FF2C	2K	0014	
0ZCC0020FF2C	2K	0020	
0ZCC0035FF2C	2K	0035	
0ZCC0050FF2C	2K	0050	
0ZCC0075FF2C	2K	0075	
0ZCC0075AF2B	1.5K		075 24
0ZCC0075BF2B	1.5K		075 33
0ZCC0110FF2C	2K	0110	
0ZCC0110AF2C	2K		110 16
0ZCC0110BF2B	1.5K		110 24
0ZCC0125FF2C	2K	0125	
0ZCC0150FF2C	2K	0150	
0ZCC0150AF2C	2K		150 12
0ZCC0150BF2C	2K		150 24
0ZCC0160FF2C	2K	0160	
0ZCC0160AF2C	2K		160 12
0ZCC0160BF2C	2K		160 16
0ZCC0200FF2C	2K		200 A
0ZCC0260FF2C	2K	0260	
0ZCC0260AF2B	1.5K		260 13
0ZCC0260BF2B	1.5K		260 16
0ZCC0300FF2B	1.5K	0300	

2000 or 1500 fuses in 7 inches dia. Reel, 8mm wide tape, 4mm pitch, per EIA-481 (equivalent IEC-286 part 3).

Electrical Characteristics (23°C)

	Part Number	Hold Current	Trip Current	Max.Time to Trip		Maximum Current	Rated Voltage	Typical Power	Resistance Tolerance			Agency Approvals	
		I _H , A	I _T , A	Current,A	Seconds	I _{max} , A	V _{max} , Vdc	P _d , W	R _{min}	R _{max}	R _{1max}		
A	0ZCC0014FF2C	0.14	0.30	8	0.008	10	60	0.8	1.20	2.50	6.50	Y	Y
B	0ZCC0020FF2C	0.20	0.40	8	0.02	10	30	0.8	0.800	2.573	5.000	Y	Y
C	0ZCC0035FF2C	0.35	0.70	8	0.10	40	16	0.8	0.32	0.80	1.50	Y	Y
D	0ZCC0050FF2C	0.50	1.00	8	0.15	40	16	0.8	0.15	0.57	1.00	Y	Y
E	0ZCC0075FF2C	0.75	1.50	8	0.20	40	16	0.8	0.11	0.27	0.45	Y	Y
E	0ZCC0075AF2B	0.75	1.50	8	0.20	40	24	1.0	0.11	0.20	0.29	Y	Y
E	0ZCC0075BF2B	0.75	1.50	8	0.20	40	33	1.0	0.11	0.25	0.40	Y	Y
F	0ZCC0110FF2C	1.10	2.20	8	0.30	100	8	0.8	0.04	0.11	0.21	Y	Y
F	0ZCC0110AF2C	1.10	1.95	8	0.50	40	16	0.8	0.04	0.12	0.18	Y	Y
F	0ZCC0110BF2B	1.10	2.20	8	0.50	100	24	1.0	0.06	0.13	0.20	Y	Y
G	0ZCC0125FF2C	1.25	2.50	8	0.40	40	6	0.8	0.05	0.08	0.14	Y	Y
H	0ZCC0150FF2C	1.50	3.00	8	0.50	40	6	0.8	0.04	0.07	0.11	Y	Y
H	0ZCC0150AF2C	1.50	3.00	8	0.50	100	12	1.0	0.040	0.075	0.110	Y	Y
H	0ZCC0150BF2C	1.50	3.00	8	1.50	100	24	1.0	0.040	0.070	0.120	Y	Y
I	0ZCC0160FF2C	1.60	3.20	8	0.50	40	6	0.8	0.030	0.066	0.100	Y	Y
I	0ZCC0160AF2C	1.60	3.20	8	1.0	100	12	1.0	0.030	0.060	0.100	Y	Y
I	0ZCC0160BF2C	1.60	3.20	8	1.0	100	16	1.0	0.030	0.060	0.100	Y	Y
J	0ZCC0200FF2C	2.00	3.50	8	2.0	100	8	1.0	0.020	0.045	0.070	Y	Y
K	0ZCC0260FF2C	2.60	5.00	8	2.5	100	6	1.0	0.015	0.031	0.047	Y	Y
K	0ZCC0260AF2B	2.60	5.00	8	5.0	100	13.2	1.3	0.015	0.030	0.050	Y	Y
K	0ZCC0260BF2B	2.60	5.00	8	5.0	100	16	1.3	0.015	0.030	0.050	Y	Y
L	0ZCC0300FF2B	3.00	5.00	8	4.0	100	6	1.0	0.012	0.025	0.040	Y	Y

I_H Hold current-maximum current at which the device will not trip in still air at 23°C.

I_T Trip current-minimum current at which the device will always trip in still air at 23°C.

I_{max} Maximum fault current device can withstand without damage at rated voltage (V_{max}).

V_{max} Maximum voltage device can withstand without damage at its rated current.

P_d Typical power dissipated by device when in tripped state in 23°C still air environment.

R_{min} Minimum device resistance at 23°C.

R_{max} Maximum device resistance at 23°C.

R_{1max} Maximum device resistance at 23°C, 1 hour after initial device trip.

Termination pad characteristics

Termination pad materials


Matte Tin-plated Copper

Pad Layout, Solder Reflow and Rework Recommendations

The dimensions in the table below provide the recommended pad layout for each 0ZCC device

	A		B		C	
	Nominal		Nominal		Nominal	
	mm	inch	mm	inch	mm	inch
	3.45	0.136	1.78	0.070	3.50	0.138

Profile Feature	Pb-Free Assembly
Average Ramp-Up Rate (T _{smax} to T _p)	3 °C/second max.
Preheat:	
Temperature Min (T _{smin})	150 °C
Temperature Max (T _{smax})	200 °C
Time (t _{min} to t _{smax})	60-180 seconds
Time maintained above:	
Temperature (T _i)	217 °C
Time (t _i)	60-150 seconds
Peak/Classification Temperature (T _p)	260 °C
Time within 5°C of actual Peak:	
Temperature (t _p)	20-40 seconds
Ramp-Down Rate:	6 °C/second max.
Time 25 °C to Peak Temperature:	8 minutes max.



Solder Reflow

* Due to "lead free/RoHS6" construction of these PTC devices, the required Temperature and Dwell Time in the "Soldering" zone of the reflow profile are greater than those used for non-RoHS devices.

1. Recommended reflow methods; IR, vapor phase oven, hot air oven.
2. The 0ZCC Series is suitable for wave solder application methods.
3. Recommended maximum paste thickness is 0.25mm.
4. Devices are compatible with standard industry cleaning solvents and methods.

Caution

If reflow temperature/dwell times exceed the recommended profile, the electrical performance of the PTC may be affected.

Rework

MIL-STD-202G Method 210F. Test Condition A.

HALOGEN FREE = HF

LEAD FREE = Pb

Specifications subject to change without notice

Surface Mount PTC

0ZCC Series


1812 Chip
RoHS6 Compliant & Halogen-Free




bel

0ZCCCJAN2011

Typical Time - To - Trip at 23°C



Thermal Derating Curve



a = 0ZCC0075, 0ZCC0110, 0ZCC0125, 0ZCC0150, 0ZCC0160, 0ZCC0200, 0ZCC0260 & 0ZCC0300
b = 0ZCC0014, 0ZCC0020, 0ZCC0035 & 0ZCC0050

Cautionary Notes

1. Operation beyond the specified maximum ratings or improper use may result in damage and possible electrical arcing and/or flame.
2. These Polymer PTC (PPTC) devices are intended for protection against occasional overcurrent/ overtemperature fault conditions and may not be suitable for use in applications where repeated and/ or prolonged fault conditions are anticipated.
3. Avoid contact of PTC device with chemical solvent. Prolonged contact may adversely impact the PTC performance.
4. These PTC devices may not be suitable for use in circuits with a large inductance, as the PTC trip can generate circuit voltage spikes above the PTC rated voltage.

Specifications subject to change without notice

Corporate Office

Bel Fuse Inc.

206 Van Vorst Street, Jersey City, NJ 07302
Tel: 201-432-0463
Fax: 201-432-9542
E-Mail: belfuse@belfuse.com
Website: www.belfuse.com

Far East Office

Bel Fuse Ltd.

8F / 8 Luk Hop Street
San Po Kong
Kowloon, Hong Kong
Tel 852-2328-5515
Fax 852-2352-3706
E-Mail : bel_hk@belfuse.com

European Office

Bel Stewart GmbH

Industriestrasse 20
61381 Friedrichsdorf
Germany
Tel 49-6172-9552-0
Fax 49-6172-9552-40
E-Mail : cperebeck@bel-stewart.com