

JWT100-522



Sales Region	Worldwide
Series	JWT
Status	Production
Feature	
Option	
Option Lineup	Please refer to here.
Recommended EMC Filter	Please refer to here.
Accessories	Please refer to the catalog



Electrical Characteristics	
Input Voltage Range[AC]	85 to 265V
Input Voltage Range[DC]	120 to 330V
Efficiency	72% Typ.
Rated Output Voltage[DC]	<u>+5V</u> <u>+12V</u> <u>-12V</u>
Output Voltage Range[DC]	<u>+5 to +5.25V</u> <u>Fixed</u> <u>Fixed</u>
Minimum Output Current	<u>1.3A</u> <u>0A</u> <u>0A</u>
Maximum Output Current	<u>13A</u> <u>5.5A</u> <u>1A</u>
Maximum Average Current	
Maximum Peak Current	
Total Maximum(Average) Output Power	100W
Total Maximum Peak Power	

Cases Shape & Size	
Case'□ shape	Unit
Width(W)	48mm Nom.
Height(H)	92mm Nom.
Depth(D)	203mm Nom.
Weight	720g Typ.

Other	
Operating Temp. Range	-10 to 65°C
Cooling	Convection cooling
Safety Standard(Certified)	UL60950-1 CSA C22.2 No.60950-1 EN60950-1
Safety Standard(Conformed)	Den-an

