

## Description

The BCR405UW6 monolithically integrates a transistor, diodes and resistors to function as a Constant Current Regulator (CCR) for LED driving. The device regulates with a preset 50mA nominal that can be adjusted with external resistor up to 100mA. It is designed for driving LEDs in strings and will reduce current at increasing temperatures to self-protect. Operating as a series linear CCR for LED string current control then it can be used in applications with supply voltages up to 40V.

With no need for additional external components, this CCR is fully integrated into a SOT26 minimizing PCB area and component count.

## Applications

Constant current regulation (CCR) in:

- Emergency lighting
- Signage, advertising, decorative and architectural lighting
- Retail lighting in fridge, freezer case and vending machines

## Features

- LED Constant Current Regulator Using PNP Emitter-Follower with Emitter Resistor to Current Limit
- $I_{OUT} = 50mA \pm 10\%$  constant current (Preset)
- $I_{OUT}$  up to 100mA adjustable with an external resistor
- Negative temperature coefficient (NTC) reduces  $I_{out}$  with increasing temperature
- Parallel devices to increase regulated current
- **Totally Lead-Free & Fully RoHS Compliant (Notes 1 & 2)**
- **Halogen and Antimony Free. "Green" Device (Note 3)**


## Mechanical Data

- Case: SOT26 (SC-74)
- Case Material: Molded Plastic. "Green" Molding Compound. UL Flammability Rating 94V-0
- Moisture Sensitivity: Level 1 per J-STD-020
- Terminals: Finish - Matte Tin Plated Leads, Solderable per MIL-STD-202, Method 208 
- Weight: 0.018 grams (Approximate)


SOT26 (SC-74)



Top View



Internal Device  
Schematic



Top View  
Pin-Out


| Pin Name | Pin Function                                   |
|----------|------------------------------------------------|
| Vs       | Supply Voltage                                 |
| OUT      | Regulated Output Current                       |
| Rext     | External resistor for adjusting Output Current |
| GND      | Power Ground                                   |

## Ordering Information (Note 4)

| Product     | Marking | Reel size (inches) | Tape width (mm) | Quantity per reel |
|-------------|---------|--------------------|-----------------|-------------------|
| BCR405UW6-7 | 405     | 7                  | 8               | 3,000             |

- Notes:
1. No purposely added lead. Fully EU Directive 2002/95/EC (RoHS) & 2011/65/EU (RoHS 2) compliant.
  2. See [http://www.diodes.com/quality/lead\\_free.html](http://www.diodes.com/quality/lead_free.html) for more information about Diodes Incorporated's definitions of Halogen- and Antimony-free, "Green" and Lead-free.
  3. Halogen- and Antimony-free "Green" products are defined as those which contain <900ppm bromine, <900ppm chlorine (<1500ppm total Br + Cl) and <1000ppm antimony compounds.
  4. For packaging details, go to our website at <http://www.diodes.com/products/packages.html>.

## Marking Information



405 = Part Marking (See Ordering Information)  
 YM = Date Code Marking  
 Y = Year (ex: D = 2016)  
 M = Month (ex: 9 = September)

### Date Code Key

| Year | 2016 | 2017 | 2018 | 2019 | 2020 | 2021 | 2022 |
|------|------|------|------|------|------|------|------|
| Code | D    | E    | F    | G    | H    | I    | J    |

| Month | Jan | Feb | Mar | Apr | May | Jun | Jul | Aug | Sep | Oct | Nov | Dec |
|-------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| Code  | 1   | 2   | 3   | 4   | 5   | 6   | 7   | 8   | 9   | O   | N   | D   |

## Absolute Maximum Ratings (Voltage relative to GND, @T<sub>A</sub> = +25°C, unless otherwise specified.)

| Characteristic                        | Symbol           | Value | Unit |
|---------------------------------------|------------------|-------|------|
| Supply Voltage                        | V <sub>S</sub>   | 40    | V    |
| Output Current                        | I <sub>OUT</sub> | 100   | mA   |
| Output Voltage                        | V <sub>OUT</sub> | 40    | V    |
| Reverse voltage between all terminals | V <sub>R</sub>   | 0.5   | V    |

## Thermal Characteristics

| Characteristic                                           | Symbol                            | Value       | Unit |
|----------------------------------------------------------|-----------------------------------|-------------|------|
| Power Dissipation                                        | P <sub>D</sub>                    | 1,190       | mW   |
|                                                          |                                   | 912         |      |
| Thermal Resistance, Junction to Ambient                  | R <sub>θJA</sub>                  | 105         | °C/W |
|                                                          |                                   | 137         |      |
| Thermal Resistance, Junction to Lead                     | R <sub>θJL</sub>                  | 50          |      |
| Recommended Operating Junction Temperature Range         | T <sub>J</sub>                    | -55 to +150 | °C   |
| Maximum Operating Junction and Storage Temperature Range | T <sub>J</sub> , T <sub>STG</sub> | -65 to +150 |      |

## ESD Ratings (Note 8)







| Characteristics                            | Symbols | Value | Unit | JEDEC Class |
|--------------------------------------------|---------|-------|------|-------------|
| Electrostatic Discharge – Human Body Model | ESD HBM | 800   | V    | 1B          |
| Electrostatic Discharge – Machine Model    | ESD MM  | 300   | V    | B           |

- Notes:
- For a device mounted with the OUT leads on 50mm x 50mm 2oz copper that is on a single-sided 1.6mm FR4 PCB; device is measured under still air conditions while operating in steady-state.
  - Same as Note 5, except mounted on 15mm x 15mm 1oz copper.
  - R<sub>θJL</sub> = Thermal resistance from junction to solder-point (at the end of the OUT leads).
  - Refer to JEDEC specification JESD22-A114 and JESD22-A115.







**Electrical Characteristics** (@T<sub>A</sub> = +25°C, unless otherwise specified.)

| Characteristic                                                       | Symbol                              | Min | Typ   | Max | Unit | Test Condition                                |
|----------------------------------------------------------------------|-------------------------------------|-----|-------|-----|------|-----------------------------------------------|
| Collector-Emitter Breakdown Voltage                                  | BV <sub>CEO</sub>                   | 40  | -     | -   | V    | I <sub>C</sub> = 1mA                          |
| GND (Enable) Current                                                 | I <sub>GND</sub>                    | 340 | 420   | 500 | μA   | V <sub>S</sub> = 10V; V <sub>OUT</sub> = open |
| GND (Enable) Current                                                 | I <sub>GND</sub>                    | -   | 380   | -   | μA   | V <sub>S</sub> = 10V; V <sub>OUT</sub> = 8.6V |
| DC Current Gain                                                      | h <sub>FE</sub>                     | 100 | 220   | 470 | -    | I <sub>C</sub> = 50mA; V <sub>CE</sub> = 1V   |
| Internal Resistor                                                    | R <sub>int</sub>                    | 13  | 16.5  | 22  | Ω    | I <sub>Rint</sub> = 50mA                      |
| Output Current (nominal)                                             | I <sub>OUT</sub>                    | 45  | 50    | 55  | mA   | V <sub>OUT</sub> = 8.6V; V <sub>S</sub> = 10V |
| Voltage Drop (V <sub>Rext</sub> )                                    | V <sub>drop</sub>                   | -   | 0.83  | -   | V    | I <sub>OUT</sub> = 50mA                       |
| Lowest Sufficient Supply Voltage (V <sub>S</sub> -V <sub>OUT</sub> ) | V <sub>Smin</sub>                   | -   | 1.4   | -   | V    | I <sub>OUT</sub> > 18mA                       |
| Output Current Change vs. Temperature                                | ΔI <sub>OUT</sub> /I <sub>OUT</sub> | -   | -0.25 | -   | %/°C | V <sub>S</sub> = 10V                          |
| Output Current Change vs. Supply Voltage                             | ΔI <sub>OUT</sub> /I <sub>OUT</sub> | -   | 1.5   | -   | %/V  | V <sub>S</sub> = 10V                          |

**Typical Thermal Characteristics** (@ $T_A = +25^\circ\text{C}$ , unless otherwise specified.)




**Typical Electrical Characteristics** (continued) (@ $T_A = +25^\circ\text{C}$ , unless otherwise specified.)



## Package Outline Dimensions

Please see <http://www.diodes.com/package-outlines.html> for the latest version.

### SOT26 (SC74R)




| SOT26 (SC74R)        |       |      |      |
|----------------------|-------|------|------|
| Dim                  | Min   | Max  | Typ  |
| A1                   | 0.013 | 0.10 | 0.05 |
| A2                   | 1.00  | 1.30 | 1.10 |
| A3                   | 0.70  | 0.80 | 0.75 |
| b                    | 0.35  | 0.50 | 0.38 |
| c                    | 0.10  | 0.20 | 0.15 |
| D                    | 2.90  | 3.10 | 3.00 |
| e                    | -     | -    | 0.95 |
| e1                   | -     | -    | 1.90 |
| E                    | 2.70  | 3.00 | 2.80 |
| E1                   | 1.50  | 1.70 | 1.60 |
| L                    | 0.35  | 0.55 | 0.40 |
| a                    | -     | -    | 8°   |
| a1                   | -     | -    | 7°   |
| All Dimensions in mm |       |      |      |

## Suggested Pad Layout

Please see <http://www.diodes.com/package-outlines.html> for the latest version.

### SOT26 (SC74R)



| Dimensions | Value (in mm) |
|------------|---------------|
| C          | 2.40          |
| C1         | 0.95          |
| G          | 1.60          |
| X          | 0.55          |
| Y          | 0.80          |
| Y1         | 3.20          |

#### IMPORTANT NOTICE

DIODES INCORPORATED MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARDS TO THIS DOCUMENT, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION).

Diodes Incorporated and its subsidiaries reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to this document and any product described herein. Diodes Incorporated does not assume any liability arising out of the application or use of this document or any product described herein; neither does Diodes Incorporated convey any license under its patent or trademark rights, nor the rights of others. Any Customer or user of this document or products described herein in such applications shall assume all risks of such use and will agree to hold Diodes Incorporated and all the companies whose products are represented on Diodes Incorporated website, harmless against all damages.

Diodes Incorporated does not warrant or accept any liability whatsoever in respect of any products purchased through unauthorized sales channel. Should Customers purchase or use Diodes Incorporated products for any unintended or unauthorized application, Customers shall indemnify and hold Diodes Incorporated and its representatives harmless against all claims, damages, expenses, and attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized application.

Products described herein may be covered by one or more United States, international or foreign patents pending. Product names and markings noted herein may also be covered by one or more United States, international or foreign trademarks.

This document is written in English but may be translated into multiple languages for reference. Only the English version of this document is the final and determinative format released by Diodes Incorporated.

#### LIFE SUPPORT

Diodes Incorporated products are specifically not authorized for use as critical components in life support devices or systems without the express written approval of the Chief Executive Officer of Diodes Incorporated. As used herein:

A. Life support devices or systems are devices or systems which:

1. are intended to implant into the body, or
2. support or sustain life and whose failure to perform when properly used in accordance with instructions for use provided in the labeling can be reasonably expected to result in significant injury to the user.

B. A critical component is any component in a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or to affect its safety or effectiveness.

Customers represent that they have all necessary expertise in the safety and regulatory ramifications of their life support devices or systems, and acknowledge and agree that they are solely responsible for all legal, regulatory and safety-related requirements concerning their products and any use of Diodes Incorporated products in such safety-critical, life support devices or systems, notwithstanding any devices- or systems-related information or support that may be provided by Diodes Incorporated. Further, Customers must fully indemnify Diodes Incorporated and its representatives against any damages arising out of the use of Diodes Incorporated products in such safety-critical, life support devices or systems.

Copyright © 2016, Diodes Incorporated

[www.diodes.com](http://www.diodes.com)