

Tripp Lite 1111 W. 35th Street Chicago, IL 60609 USA Telephone: 773.869.1234 www.tripplite.com

2-Port Compact USB KVM Switch with Audio and Cable

MODEL NUMBER: B004-VUA2-K-R





Highlights

- Fast, easy switching via keyboard hot keys, push buttons or software (not required)
- PC and Mac compatible
- Allows sharing of audio components between systems; listen to music from one computer while switching to the other computer
- Compact design saves desk space
- No AC adapter required
- (x2) 6ft USB KVM Cable kits and (x2) 6ft 3.5mm Audio Cable kits included
- Compatible with all major operating systems

System Requirements

- Console: VGA, SVGA or Multisync Monitor, USB Keyboard and USB Mouse
- Computers: VGA, SVGA or Multisync Monitor Port and USB Port
- Audio (Optional): Speakers with standard 3.5 mm Connectors and a computer with 3.5mm ports
- Compatible with all major operating systems

Package Includes

- Compact 2-port USB KVM Switch with Audio
- (2) 6ft USB KVM Cable Kits and
 (2) 6ft 3.5mm Audio Cable Kits
- CD-ROM with KVM Switcher

Description

The B004-VUA2-K-R is a 2-port Compact USB KVM Switch with optional audio and microphone switching function. It allows you to access, control, boot and reboot two USB-enabled computers from a single console (keyboard, monitor and mouse). The independent audio/mic switching function allows an uninterrupted audio experience - you can continue listening to audio even when you switch to the other computer.

It includes innovative, easy-to-use KVM Switcher Software for Windows and Macintosh platforms. A small client application facilitates your KVM switching operations such as computer selection, hot key sequence programming, auto-scanning, auto-scan delay time programming, independent or simultaneous audio/computer switching and more. Compatible with all major operating systems.

Features

- · Fast, easy switching via keyboard hot keys, push buttons or software
- Plug-and-play setup no software required
- Hot-swap capability allows easy addition or removal of computers without powering down the switch or other computers
- Speaker and microphone connections allow sharing of audio components between systems (standard 3.5 mm audio connections)
- Independent audio switching allows you to listen to audio from one computer while switching to the other computer
- Supports video resolutions up to 2048 x 1536 (standard 15-pin VGA connectors)
- Supports Microsoft® IntelliMouse® and the scrolling wheel on most mice]
- Compact design saves desk space
- Does not require an AC adapter



- Compatible with all major operating systems
- Includes two, 6ft Cable Kits

Software

Owner's Manual with Warranty
Information

Specifications

OVERVIEW		
UPC Code	037332140043	
Console	No	
Max CPU	2	
INPUT		
Bus Powered	Yes	
USER INTERFACE, ALERTS & CONTROLS		
LED Indicators	Green (Selected PC)	
PHYSICAL		
Shipping Dimensions (hwd / in.)	3.00 x 7.90 x 7.80	
Shipping Dimensions (hwd / cm)	7.62 x 20.07 x 19.81	
Shipping Weight (lbs.)	1.80	
Shipping Weight (kg)	0.82	
Unit Packaging Type	Box	
Unit Dimensions (hwd / in.)	1.3 x 4 x 2.6	
Unit Weight (lbs.)	0.22	
Unit Weight (kg)	0.10	
Material of Construction	ABS	
Color	Black	
ENVIRONMENTAL		
Operating Temperature Range	32 to 104 F (0 to 40 C)	
Storage Temperature Range	-4 to 140 F (-20 to 60 C)	
Relative Humidity	0%-90% RH, Non-Condensing	
BTUs	1.7 BTU/Hr	
Power Consumption (Watts)	0.5	



COMMUNICATIONS	
IP Remote Access	No
CONNECTIONS	
Ports	2
PC/Server Connections	USB; VGA
Side A - Connector 1	(2) HD15 (FEMALE)
Side B - Connector 1	HD15 (FEMALE)
Side B - Connector 2	(2) USB A (FEMALE)
Side B - Connector 3	(2) 3.5MM (FEMALE)
Computer Keyboard and Mouse Interface	PS/2
Computer Monitor Interface	VGA
Console Keyboard and Mouse Interface	USB
Console Monitor Interface	VGA
Connector Plating	Nickel
FEATURES & SPECIFICATIONS	
Number of Users	1
NIAP-Certified Secure	No
Port Selection	Pushbutton; Hotkey; Software
Max Supported Video Resolution	2048 x 1536 @60Hz
USB Specification	USB 1.1 (up to 12 Mbps)
Audio Specification	Stereo Audio
Cat5 KVM Switch	No
Technology	USB; VGA/SVGA; Stereo Audio
CERTIFICATIONS	
Certifications	Tested to CE, FCC, RoHS, REACH
WARRANTY	
Product Warranty Period (Worldwide)	3-year limited warranty

© 2019 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies