

VOLTAGE RANGE: 400 - 600V



CURRENT: 3.5 A

Features

- Low cost
- Diffused junction
- Low leakage
- Low forward voltage drop
- High current capability
- Easily cleaned with freon, alcohol, Isopropand and similar solvents
- The plastic material carries U/L recognition 94V-0

Mechanical Data

- Case: DO-201AD, Molded Plastic
- Terminals: Plated Leads Solderable per MIL-STD-202, Method 208
- Polarity: Cathode Band
- Weight: 1.2 grams (approx.)
- Mounting Position: Any
- Marking: Type Number



DO-201AD		
Dim	Min	Max
A	25.40	—
B	7.20	9.50
C	1.20	1.30
D	4.80	5.30
All Dimensions in mm		

Maximum Ratings and Electrical Characteristics T_A = 25°C unless otherwise specified

Single phase, half wave, 60Hz, resistive or inductive load. For capacitive load, derate current by 20%.



Characteristic	Symbol	RU4M	RU4AM	Units
Maximum peak repetitive reverse voltage	V_{RRM}	400	600	V
Maximum RMS voltage	V_{RMS}	280	420	V
Maximum DC blocking voltage	V_{DC}	400	600	V
Maximum average forward rectified current 9.5mm lead length, @T _A =75°C	$I_{F(AV)}$	3.5		A
Peak forward surge current 10ms single half-sine-wave superimposed on rated load @T _J =125°C	I_{FSM}	70.0		A
Maximum instantaneous forward voltage @ 3.5A	V_F	1.3		V
Maximum reverse current @T _A =25°C at rated DC blocking voltage @T _A =100°C	I_R	10.0 300.0		μA
Maximum reverse recovery time (Note1)	t_{rr}	100		ns
Typical junction capacitance (Note2)	C_J	70	50	pF
Typical thermal resistance (Note3)	$R_{\theta JL}$	8		°C/W
Operating junction temperature range	T_J	- 55 ----- + 150		°C
Storage temperature range	T_{STG}	- 55 ----- + 150		°C

NOTE: 1. Measured with $I_F=0.5A$, $I_R=1A$, $t_{rr}=0.25A$.

2. Measured at 1.0MHz and applied reverse voltage of 4.0V DC.

3. Thermal resistance junction to ambient.

FIG.1 -- TEST CIRCUIT DIAGRAM AND REVERSE RECOVERY TIME CHARACTERISTIC



NOTES:1.RISE TIME = 7ns MAX.INPUT IMPEDANCE =1MΩ . 22pF.
2.RISE TIME =10ns MAX.SOURCE IMPEDANCE=50 Ω.

SET TIME BASE FOR 10/20 ns/cm

FIG.2 -- TYPICAL FORWARD CHARACTERISTIC




FIG.3 -- FORWARD DERATING CURVE




FIG.4 -- PEAK FORWARD SURGE CURRENT




FIG.5-- TYPICAL JUNCTION CAPACITANCE

